



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Ceramic Singlelayer DC Disc Capacitors, 6 kV_{DC} General Purpose



| QUICK REFERENCE DATA | |
|----------------------------|-------------------------------|
| DESCRIPTION | VALUE |
| Ceramic Class | 1 2 |
| Ceramic Dielectric | N750, Y5T, Y5U |
| Voltage (V _{DC}) | 6000 |
| Min. Capacitance (pF) | 10 56 |
| Max. Capacitance (pF) | 330 6800 |
| Mounting | Radial |

MARKING

Marking indicates, capacitance, tolerance code, and rated voltage.

OPERATING TEMPERATURE RANGE

-40 °C to +85 °C

TEMPERATURE CHARACTERISTICS

Class 1 N750 (U2J)

Class 2 Y5T, Y5U

SECTIONAL SPECIFICATIONS

Climatic category (according to EN 60068-1):
40 / 085 / 21

FEATURES

- High capacitance in small sizes
- Low losses
- Wide range of different lead styles
- Material categorization:
for definitions of compliance please see
www.vishay.com/doc?99912



RoHS
COMPLIANT

APPLICATIONS

- Lighting ballasts
- SMPS

DESIGN

The capacitors consist of a ceramic disc which is silver plated on both sides. Connection leads are made of tinned copper having diameters of 0.6 mm or 0.8 mm.

The capacitors may be supplied with straight or kinked leads having a lead spacing of 12.5 mm.

Coating is made of blue colored flame retardant epoxy resin in accordance with UL 94 V-0.

CAPACITANCE RANGE

10 pF to 6.8 nF

RATED VOLTAGE

6 kV_{DC}

DIELECTRIC STRENGTH

9000 V_{DC}, 2 s Component test

INSULATION RESISTANCE AT 500 V_{DC}

≥ 10 000 MΩ (60 s)

TOLERANCE ON CAPACITANCE

± 10 %, ± 20 %

DISSIPATION FACTOR

Class 1:


$C < 30 \text{ pF: } \left(\frac{100 \text{ pF}}{C} + 0.7 \right) \times 10^{-4} \text{ max. (1 MHz)}$

$C \geq 30 \text{ pF: } \text{max. 0.1 \% (1 MHz)}$

Class 2: max. 2.5 % (1 kHz)



DIMENSIONS in millimeters



ORDERING INFORMATION

| CAPACITANCE (pF) | TOLERANCE (%) | BODY DIAMETER D _{max.} (mm) | BODY THICKNESS S _{max.} (mm) | LEAD SPACING ⁽¹⁾ F (mm) ± 1 mm | LEAD DIAMETER ⁽¹⁾ d (mm) ± 0.05 mm | WIDTH ⁽¹⁾ V (mm) ± 0.5 mm | ORDERING CODE | | | |
|-------------------|----------------|--------------------------------------|---------------------------------------|---|---|--------------------------------------|--|----------------|----------------|----------------|
| | | | | | | | MISSING DIGITS SEE ORDERING CODE BELOW | | | |
| N750 (U2J) | | | | | | | | | | |
| 10 | ± 10 | 7.0 | 4.8 | 12.5 | 0.6 | 2.2 | HFU100KBF###KR | | | |
| 15 | | | | | | | HFU150KBF###KR | | | |
| 22 | | | | | | | HFU220KBF###KR | | | |
| 33 | | | | | | | HFU330KBF###KR | | | |
| 47 | | 9.5 | 5.2 | | 0.8 | 2.4 | HFU470KBF###KR | | | |
| 68 | | | | | | | HFU680KBF###KR | | | |
| 82 | | 12.0 | 5.2 | | 0.8 | 2.4 | HFU820KBF###KR | | | |
| 100 | | | | | | | HFU101KBF###KR | | | |
| 150 | | | | | | | HFU151KBF###KR | | | |
| 220 | | | | | | | HFU221KBF###KR | | | |
| 330 | | | | | | | HFU331KBF###KR | | | |
| | | | | | | | | | | |
| Y5T (2E3) | | | | | | | | | | |
| 56 | | ± 20 ⁽²⁾ | 7.0 | | 5.0 | 12.5 | 0.6 | 3.5 | HFZ560#BF###KR | |
| 68 | HFZ680#BF###KR | | | | | | | | | |
| 82 | HFZ820#BF###KR | | | | | | | | | |
| 100 | 8.0 | | 5.0 | 0.6 | | | | | 3.5 | HFZ101#BF###KR |
| 120 | | | | | | | | | | HFZ121#BF###KR |
| 150 | | | | | | | | | | HFZ151#BF###KR |
| 180 | 10.0 | | 5.0 | 0.6 | | | | | 3.5 | HFZ181#BF###KR |
| 220 | | | | | | | | | | HFZ221#BF###KR |
| 270 | | | | | | | | | | HFZ271#BF###KR |
| 330 | 12.0 | | 5.0 | 0.8 | | | | | 3.5 | HFZ331#BF###KR |
| 390 | | | | | | | | | | HFZ391#BF###KR |
| 470 | | | | | | | | | | HFZ471#BF###KR |
| 560 | 13.0 | | 5.0 | 0.8 | | | | | 3.5 | HFZ561#BF###KR |
| 680 | | | | | | | | | | HFZ681#BF###KR |
| 820 | | | | | | | | | | HFZ821#BF###KR |
| 1000 | 17.0 | | 5.0 | 0.8 | | | | | 3.5 | HFZ102#BF###KR |
| 1200 | | | | | | | | | | HFZ122#BF###KR |
| 1500 | | | | | | | | | | HFZ152#BF###KR |
| 1800 | 21.0 | | 5.0 | 0.8 | | | 3.5 | HFZ182#BF###KR | | |
| 2200 | | | | | | | | HFZ222#BF###KR | | |
| 2700 | | | | | | | | HFZ272#BF###KR | | |



| ORDERING INFORMATION | | | | | | | |
|----------------------|---------------|--------------------------------------|---------------------------------------|---|---|--------------------------------------|---|
| CAPACITANCE (pF) | TOLERANCE (%) | BODY DIAMETER D _{max.} (mm) | BODY THICKNESS S _{max.} (mm) | LEAD SPACING ⁽¹⁾ F (mm) ± 1 mm | LEAD DIAMETER ⁽¹⁾ d (mm) ± 0.05 mm | WIDTH ⁽¹⁾ V (mm) ± 0.5 mm | ORDERING CODE MISSING DIGITS SEE ORDERING CODE BELOW |
| Y5U (2E3) | | | | | | | |
| 150 | ± 20 | 7.0 | 5.0 | 12.5 | 0.6 | 3.5 | HFE151MBF###KR |
| 220 | | | | | | | HFE221MBF###KR |
| 330 | | | | | | | HFE331MBF###KR |
| 470 | | 9.0 | | | | | HFE471MBF###KR |
| 680 | | | | | | | HFE681MBF###KR |
| 1000 | | | | | | | HFE102MBF###KR |
| 1500 | | 13.0 | HFE152MBF###KR | | | | |
| 2200 | | 15.0 | HFE222MBF###KR | | | | |
| 3300 | | 21.0 | 5.5 | | HFE332MBF###KR | | |
| 4700 | | | | | 0.8 | | HFE472MBF###KR |
| 6800 | | | | | HFE682MBF###KR | | |

Notes

- ⁽¹⁾ Standard lead configuration, other lead spacing and diameter available on request
- ⁽²⁾ ± 10 % available on request

| ORDERING CODE | | | | | | | |
|----------------|--|-----------------------|---------------------------|--------------|--------------------|---------------|----------------|
| # | 7 th digit | Capacitance tolerance | ± 10 % = K, ± 20 % = M | | | | |
| ### | 10 th to 12 th digit | Lead configuration | see "General Information" | | | | |
| Example | HFE | 682 | M | BF | EF0 | K | R |
| | Series | Capacitance value | Tolerance code | Voltage code | Lead configuration | Internal code | RoHS compliant |

| MARKING | |
|--|--|
| | |
| HFU 10 pF to 100 pF HFZ 56 pF to 470 pF HFE 150 pF to 1.0 nF | HFU 150 pF to 330 pF HFZ 560 nF to 2.7 nF HFE 1.5 nF to 6.8 nF |

| RELATED DOCUMENTS | |
|---------------------|--|
| General Information | www.vishay.com/doc?22001 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.