

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







HI2220Q401R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:

A 5.59 [.220] ± 0.51 [.020]

B 5.08 [.200] ± 0.25 [.010]

C 3.20 [.126] ± 0.25 [.010]

D 0.76 [.030] ± 0.25 [.010]

A B C C

ELECTRICAL CHARACTERISTICS:							
Z @ 100N (Ω)	1Hz	DCR $\left(\begin{array}{c}\Omega\end{array}\right)$	Rated Current				
Nominal	400						
Minimum	300						
Maximum	500	0.030	4500 mA				

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 13" REELS, 2,000 PCS/REEL.
- 2. TERMINATION FINISH IS 100% TIN.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATEING TEMPERATURE TEMP: -40°C~+125°C (INCLUDING SELF-HEATING)


100 FREQUENCY (MHz)

Z vs. FREQUENCY

LAND PATTERNS FOR REFLOW SOLDERING

RECOMMENDED SOLDERING CONDITIONS





(For wave soldering, add 0.762 [0.030] to this dimension)

500	Z , R, ANI	O XL vs. FRE	QUENCY		
300				###	
450		\square		\blacksquare	
400		// \		\blacksquare	
350		# 1		#	
G 300				##	
<u>U</u> 250		// /		##	
U 250 V 200 V 200 V 150				₩	
150				▦	
≥ 100			Z	▦	
50				#	
0			R	##	
1	10	100	1000	10000	
	FREQUENCY (MHz)				
	Z	R	XL		

2002/95/E

DIMENSIONS ARE IN mm [INCHES].			This print is the property of Laird						
				Tech and is loaned in confidence subject to return upon request with the understanding that no copies shall be made without the written consent of Laird Tech. Al	L	a	ir		
				rights to design or invention are reserved.					
				PROJECT/PART NUMBER:	П	REV	PART TY	rPE:	DRAWN BY:
С	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU	HI2220Q401R-10		C co-		-FIRE	тмв
В	UPDATE COMPANY LOGO ADD ROHS	01/25/08	JRK	DATE: 04/03/04 scal		LE: NTS		SHEET:	
Α	ORIGINAL DRAFT	04/03/04	ТМВ	CAD #	rooL #			2	of 2
REV	DESCRIPTION	DATE	INT	HI2220Q401R-10-C			-	-	01 2

AGILENT E4991A RF Impedance/Material Analyzer HP 16092A Test Fixture. TEST REF. 3185