



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# EMI Ferrite Chip Beads



*Steward's* surface mount ferrite chips provide compact, cost effective EMI filtering for densely packed PCB designs. The small footprint enables placement very close to troublesome high frequency devices. Our proprietary SMT construction yields rugged components with impedance versus frequency characteristics superior to those of similar products.

## Features:

- Small footprint
- Excellent retention under bias
- Rugged, monolithic construction
- Superior impedance vs. frequency characteristics
- Economical
- Broad range of sizes ( from 0402 up to 2220 and 3312 )
- Broad range of impedance values and current ratings

## Applications:


- Filtering of power input pins and devices using high speed clocks
- Filtering of low frequency input/output signals of shielded enclosures
- High frequency filtering of medium speed clocks and video signals
- Prevention of oscillations in high frequency amplifiers
- Data bus filtration
- Discrete component filtration in power supplies
- Telecom Products

## Test Specifications:

- Maximum current ratings are determined by testing to a maximum temperature rise of 40°C with continuous operating current
- Board level components are rated up to a maximum of 75 volts.

**Tested with:** •E4991A (100kHz - 3.0 GHz) or HP8753 (to 6 GHz) Network/Spectrum Analyzer •HP43961A Impedance Test Kit •HP16193A Test Fixture or Inter-Continental Microwave custom fixtures •HP16200A DC Bias Adapter •Philips PM2811 DC Power Supply •Ambient Temperature 23.5°C ± 2° •Bandwidth 3 kHz •Sweep Time 423 ms •Impedance is rated at ± 25% @100MHz

STEWARD PART NUMBERING SYSTEM					
HI	805	Q	310	R	- 00
PRODUCT SERIES CODE	PART SIZE CODE	RATED CURRENT CODE	IMPEDANCE VALUE CODE	PACKAGING CODE	ADDITIONAL DESCRIPTION
DM	Ultra High Current Chips (10 Amps +)		LI	Low Current Chips (< 1 Amp and < 400 Ohms)	
HI	High Current Chips		HZ	High Impedance Chips (<1 Amp and > 400 Ohms)	
MI	Mid Current Chips (1-2 Amps)		DA	Chip Array (< 1 Amp)	



Chip Bead



Chip Array

Ambient Temperature Range: -55°C to +125°C

PART NUMBER	METRIC ( EIA ) PKG. SIZE	IMPEDANCE ( Z ) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>Ultra High Current Chips</b>						
DM1612X560R-00	4131 (1612)	56	90	100	0.004	10,000
DM3312X101R-00	8531 (3312)	100	175	225	0.004	10,000
<b>High Current Chips</b>						
HI0603P600R-00	1608 (0603)	60	90	95	0.040	3,000
HI0805Q310R-00	2012 (0805)	31	42	46	0.025	4,500
HI0805P121R-00		120	183	152	0.040	3,000
HI0805R121R-00		120	183	152	0.020	5,000
HI1206P330R-00	3216 (1206)	33	45	50	0.030	4,000
HI1206T500R-00		50	73	80	0.010	6,000
HI1206N800R-00		80	120	129	0.035	3,000

continued on right

PART NUMBER	METRIC ( EIA ) PKG. SIZE	IMPEDANCE ( Z ) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>High Current Chips (Continued)</b>						
HI1206N101R-00		100	144	150	0.035	3,000
HI1206P121R-00		120	168	124	0.030	4,000
HI1806T600R-00	4516 (1806)	60	102	107	0.010	6,000
HI1806N750R-00		75	168	124	0.030	3,000
HI1812T800R-00	4532 (1812)	80	121	129	0.010	6,000
HI2220T101R-00	5650 (2220)	100	148	152	0.015	6,000
HI2220R151R-00		150	215	196	0.020	5,000
HI2220P171R-00		170	318	349	0.035	4,000
HI2220R181R-00		180	279	265	0.020	5,000
HI2220P251R-00		250	172	91	0.035	4,000

continued on next page

**Steward**

U.S.A. • Telephone: +1-(423)-867-4100 • Fax +1-(423)-867-4102 • Internet: <http://www.steward.com>  
 SCOTLAND • Telephone: +44-(0)-1506-414200 • Fax +44-(0)-1506-410694  
 SINGAPORE • Telephone: +65-337-9667 • Fax +65-337-9686

BROCH0009  
4/2001 REV 5

PART NUMBER	METRIC (EIA) PKG. SIZE	IMPEDANCE (Z) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>High Current Chips (Continued)</b>						
HI2220Q301R-00	5650 (2220)	300	188	108	0.020	5,000
HI2220Q401R-00		400	159	99	0.025	4,500
HI2220P551R-00		550	670	343	0.035	4,000
HI2220P601R-00		600	184	106	0.035	4,000
HI2220P701R-00		700	140	90	0.035	4,000
HI2220V801R-00		800	123	78	0.010	8,000
HI2520P501R-00	6350 (2520)	500	215	133	0.035	4,000
HI2520P601R-00		600	639	165	0.035	4,000
HI2520P751R-00		750	173	114	0.035	4,000
<b>Mid Current Chips</b>						
MI0603K300R-00	1608 (0603)	30	41	43	0.090	1,500
MI0603J600R-00		60	92	103	0.100	1,000
MI0603J680R-00		68	106	99	0.100	1,000
MI0603M121R-00		120	195	155	0.050	2,500
MI0603L301R-00		300	225	120	0.100	2,000
MI0603K501R-00		500	180	50	0.150	1,500
MI0603J601R-00		600	400	200	0.200	1,000
MI0805J070R-00	2012 (0805)	7	23	28	0.100	1,000
MI0805K110R-00		11	18	19	0.060	1,500
MI0805K170R-00		17	24	24	0.060	1,500
MI0805K260R-00		26	43	45	0.060	1,500
MI0805K320R-00		32	51	51	0.060	1,500
MI0805K400R-00		40	60	63	0.050	1,500
MI0805M201R-00		200	210	115	0.050	2,500
MI0805M221R-00		220	274	167	0.050	2,500

continued on right.



PART NUMBER	METRIC (EIA) PKG. SIZE	IMPEDANCE (Z) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>Mid Current Chips (Continued)</b>						
MI0805L301R-00		300	271	147	0.100	2,000
MI0805L331R-00		330	262	142	0.100	2,000
MI0805K601R-00		600	275	140	0.100	1,500
MI1206K190R-00	3216 (1206)	19	55	70	0.080	1,500
MI1206K260R-00		26	38	40	0.060	1,500
MI1206K310R-00		31	45	50	0.080	1,500
MI1206J700R-00		70	104	107	0.100	1,000
MI1206K900R-00		90	142	158	0.080	1,500
MI1206K101R-00		100	146	152	0.075	1,500
MI1206M301R-00		300	142	158	0.050	2,500
MI1206L501R-00		500	150	82	0.060	2,000
MI1206K601R-00		600	250	130	0.100	2,000
MI1806J800R-00	4516 (1806)	80	129	131	0.150	1,000
MI1812K121R-00	4532 (1812)	120	198	213	0.060	1,500
<b>Low Current Chips</b>						
LI0402E300R-00	1005 (0402)	30	65	68	0.300	500
LI0402E600R-00		60	90	93	0.300	500
LI0402D121R-00		120	175	164	0.400	400
LI0402B241R-00		240	65	68	0.400	200
LI0402B301R-00		300	454	351	0.800	200
LI0603G600R-00	1608 (0603)	60	115	118	0.200	700
LI0603G800R-00		80	120	107	0.200	700
LI0603G121R-00		120	156	113	0.200	700
LI0603E141R-00		140	228	144	0.250	500
LI0603E151R-00		150	210	150	0.250	500


continued on next page

PART NUMBER	METRIC ( EIA ) PKG. SIZE	IMPEDANCE ( Z ) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>Low Current Chips (Continued)</b>						
LI0603G221R-00		220	279	168	0.300	700
LI0603D301R-00		300	286	165	0.350	400
LI0805H400R-00	<b>2012 (0805)</b>	40	60	63	0.150	800
LI0805H600R-00		60	78	75	0.150	800
LI0805H750R-00		75	112	113	0.150	800
LI0805H800R-00		80	116	98	0.150	800
LI0805H121R-00		120	167	129	0.150	800
LI0805H151R-00		150	207	138	0.150	800
LI0805G221R-00		220	229	139	0.300	700
LI0805G301R-00		300	248	146	0.200	700
LI1206E260R-00	<b>3216 (1206)</b>	26	38	40	0.200	500
LI1206E520R-00		52	83	92	0.150	500
LI1206H900R-00		90	142	156	0.150	800
LI1206H121R-00		120	144	135	0.150	800
LI1206H151R-00		150	173	123	0.150	800
LI1206F241R-00		240	354	164	0.300	600
LI1206G301R-00		300	138	88	0.200	700
LI1210E600R-00	<b>3225 (1210)</b>	60	92	97	0.300	500
LI1806E800R-00	<b>4516 (1806)</b>	80	117	124	0.300	500
LI1806E101R-00		100	131	130	0.300	500
LI1806C151R-00		150	219	227	0.500	300
LI1812D121R-00	<b>4532 (1812)</b>	120	203	195	0.400	400
<b>High Impedance Chips</b>						
HZ0402A601R-00	<b>1005 (0402)</b>	600	644	399	1.000	100
HZ0603C601R-00	<b>1608 (0603)</b>	600	338	171	0.450	300



continued on right

PART NUMBER	METRIC ( EIA ) PKG. SIZE	IMPEDANCE ( Z ) TYPICL OHMS @			DCR MAX OHMS	RATED I MAX (continuous) mA
		100MHz	500MHz	1GHz		
<b>High Impedance Chips (Continued)</b>						
HZ0603B751R-00		750	331	168	0.600	200
HZ0603B102R-00		1,000	376	187	0.600	200
HZ0603A152R-00		1,500	426	216	1.500	100
HZ0805E401R-00	<b>2012 (0805)</b>	400	390	180	0.300	500
HZ0805G471R-00		470	286	150	0.350	700
HZ0805E601R-00		600	304	151	0.300	500
HZ0805D102R-00		1,000	328	168	0.350	400
HZ0805D152R-00		1,500	265	140	0.400	400
HZ0805C202R-00		2,000	345	175	0.500	300
HZ1206E601R-00	<b>3216 (1206)</b>	600	202	103	0.300	500
HZ1206E801R-00		800	137	95	0.300	500
HZ1206D102R-00		1,000	185	100	0.400	400
HZ1206E152R-00		1,500	115	99	0.300	500
HZ1206C202R-00		2,000	427	231	0.500	300
<b>4-Line Chip Arrays</b>						
DA1206E300R-00	<b>3216 (1206)</b>	30	55	64	0.300	500
DA1206D600R-00		60	115	60	0.200	400
DA1206C121R-00		120	181	151	0.200	300
DA1206C151R-00		150	195	198	0.200	300
DA1206C221R-00		220	450	90	0.350	300
DA1206D301R-00		300	437	245	0.400	400
DA1206B471R-00		470	510	90	0.500	200
DA1206B601R-00		600	475	230	0.600	200
DA1206B102R-00		1,000	520	240	0.800	200



Chip Size						Land Patterns for Reflow Soldering			
  	Metric ( EIA ) Pkg. Size	A mm (inches)	B mm (inches)	C mm (inches)	D mm (inches)	L**	G	H	
	<b>1005 (0402)</b>	1.01 ± 0.18 (0.040 ± 0.007)	0.50 ± 0.20 (0.020 ± 0.008)	0.50 ± 0.20 (0.020 ± 0.008)	0.30 MAX (0.012 MAX)		2.10 (0.083)	0.50 (0.020)	0.55 (0.022)
	<b>1608 (0603)</b>	1.60 ± 0.15 (0.063 ± 0.006)	0.80 ± 0.15 (0.031 ± 0.006)	0.80 ± 0.15 (0.031 ± 0.006)	0.36 ± 0.15 (0.014 ± 0.006)		2.60 (0.102)	0.60 (0.023)	0.80 (0.031)
	<b>2012 (0805)</b>	2.00 ± 0.20 (0.079 ± 0.008)	1.25 ± 0.20 (0.049 ± 0.008)	0.90 ± 0.20 (0.035 ± 0.008)	0.51 ± 0.25 (0.020 ± 0.010)		3.00 (0.118)	1.00 (0.039)	1.00 (0.039)
	<b>2012 (0805)</b>	2.00 ± 0.20 (0.079 ± 0.008)	1.25 ± 0.20 (0.049 ± 0.008)	1.25 ± 0.20 (0.049 ± 0.008)	0.51 ± 0.25 (0.020 ± 0.010)		3.00 (0.118)	1.00 (0.039)	1.00 (0.039)
	<b>3216 (1206)</b>	3.20 ± 0.20 (0.126 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	1.10 ± 0.20 (0.043 ± 0.008)	0.51 ± 0.25 (0.020 ± 0.010)		4.40 (0.173)	2.20 (0.087)	1.40 (0.055)
	<b>3225 (1210)</b>	3.20 ± 0.20 (0.126 ± 0.008)	2.50 ± 0.20 (0.098 ± 0.008)	1.40 ± 0.20 (0.055 ± 0.008)	0.46 ± 0.20 (0.018 ± 0.008)		4.06 (0.160)	1.62 (0.084)	2.92 (0.115)
	<b>4030 (1612)</b>	4.06 ± 0.20 (0.160 ± 0.008)	3.05 ± 0.20 (0.120 ± 0.008)	2.28 ± 0.20 (0.090 ± 0.008)	0.46 ± 0.20 (0.018 ± 0.008)		8.64 (0.340)	2.13 (0.084)	4.06 (0.160)
	<b>4516 (1806)</b>	4.50 ± 0.25 (0.177 ± 0.010)	1.60 ± 0.25 (0.063 ± 0.010)	1.60 ± 0.25 (0.063 ± 0.010)	0.51 ± 0.25 (0.020 ± 0.010)		5.70 (0.224)	2.70 (0.106)	1.40 (0.055)
	<b>4532 (1812)</b>	4.50 ± 0.25 (0.177 ± 0.010)	3.20 ± 0.25 (0.126 ± 0.010)	1.40 ± 0.25 (0.055 ± 0.010)	0.46 ± 0.20 (0.018 ± 0.008)		5.90 (0.232)	2.57 (0.101)	4.22 (0.166)
	<b>5650 (2220)</b>	5.59 ± 0.51 (0.220 ± 0.020)	5.08 ± 0.25 (0.200 ± 0.010)	3.45 ± 0.25 (0.136 ± 0.010)	0.76 ± 0.25 (0.030 ± 0.008)		9.19 (0.362)	3.07 (0.121)	6.10 (0.240)
	<b>6350 (2520)</b>	6.40 ± 0.51 (0.252 ± 0.020)	5.00 ± 0.25 (0.197 ± 0.010)	3.00 ± 0.25 (0.118 ± 0.010)	0.76 ± 0.25 (0.030 ± 0.010)		9.50 (0.374)	3.81 (0.1507)	6.10 (0.240)
<b>8530 (3312)</b>	8.50 ± 0.20 (0.335 ± 0.008)	3.05 ± 0.20 (0.120 ± 0.008)	2.28 ± 0.20 (0.090 ± 0.008)	0.51 ± 0.25 (0.020 ± 0.010)		13.08 (0.515)	6.48 (0.255)	4.06 (0.160)	



Chip Bead

4-Line Chip Array Size						Land Patterns for Reflow Soldering			
  	Metric ( EIA ) Pkg. Size	A mm (inches)	B mm (inches)	C mm (inches)	D mm (inches)	L**	G	H	E
	<b>3216 (1206)</b>	3.20 ± 0.20 (0.126 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	1.10 ± 0.20 (0.043 ± 0.008)	0.40 ± 0.15 (0.016 ± 0.006)		2.85 (0.112)	0.40 (0.016)	2.44 (0.096)

Recommended Soldering Conditions



4-Line Array

\*\* - For wave soldering, add 0.762mm (0.030") to the L dimension

**Steward**

5 Cochrane Square  
Brucefield Industry Park  
Livingston EH54 9DR  
**Scotland, UK**  
Phone: +44-(0)1506-414200  
Fax: +44-(0)1506-410694  
Internet: <http://www.steward.com>  
e-mail: [europa@steward.com](mailto:europa@steward.com)

**Steward**

1200 East 36th Street  
P.O. Box 510  
Chattanooga, Tennessee 37401-0510  
**U.S.A.**  
Phone: +1-(423)-867-4100  
Fax: +1-(423)-867-4102  
Internet: <http://www.steward.com>  
e-mail: [americas@steward.com](mailto:americas@steward.com)

**Steward**

47 Hill Street, #08-07  
SCCCI Building  
**Singapore 179365**  
Phone: +65-337-9667  
Fax: +65-337-9686  
Internet: <http://www.steward.com>  
e-mail: [asia@steward.com](mailto:asia@steward.com)  
e-mail: [stewarda@pacific.net.sg](mailto:stewarda@pacific.net.sg)