

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# HI2220R181R-10

### UNCONTROLLED **DOCUMENT**


#### PHYSICAL DIMENSIONS:

A 5.59 [.220] ± 0.51 [.020]

B 5.08 [.200] ± 0.25 [.010]

C 1.80 [.071] ± 0.25 [.010]

D 0.76 [.030] ± 0.25 [.010]



ELECTRICAL CHARACTERISTICS:								
Z @ 100M ( <u>Ω</u> )	1Hz	DCR $\left(\begin{array}{c}\Omega\end{array} ight)$	Rated Current					
Nominal	180							
Minimum	135							
Maximum	225	0.020	5000 mA					

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 13" REELS, 2,000 PCS/REEL.
- 2. TERMINATION FINISH IS 100% TIN.

**REFLOW SOLDERING** 

[491

180 [356]

(236 (446) (2)

- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATEING TEMPERATURE TEMP: -40°C~+125°C (INCLUDING SELF-HEATING)

#### 300 250 - 0amp — 1amp **C** 200 — 2amp — 3amp IMPEDANCE 150 4amp 5amp 100 50 1000 FREQUENCY (MHz)

|Z| , R, AND XL vs. FREQUENCY


Z vs. FREQUENCY


IMPEDANCE UNDER DC BIAS

#### LAND PATTERNS FOR REFLOW SOLDERING

#### RECOMMENDED SOLDERING CONDITIONS

SOLDERING 255 ± 5°C





(For wave soldering, add 0.762 [0.030] to this dimension)

250		Z					
200			<del>                                      </del>				
5)		R					
J 150		/// `					
200 B 150 B 150 B 100 B							
M M M		/////x					
50			<del>                                     </del>				
0							
1	10	100	1000	10000			
FREQUENCY (MHz)							

AGILENT E4991A RF Impedance/Material Analyzer HP 16092A Test Fixture. TEST REF. 3185

XL

	<u> </u>								
	DIMENSIONS ARE IN mm [INCHES].			This print is the property of Lair	ď				
				Tech. and is loaned in confidence subject to return upon request and				<b>=</b>	1
				with the understanding that no		7	ir(		
				copies shall be made without the written consent of Laird Tech. A		<b>U</b>			
				rights to design or invention are	_				
				reserved.					
				PROJECT/PART NUMBER:	Т	REV	PART TO	PE:	DRAWN BY:
С	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13		HI2220R181R-10		С	CO-	-FIRE	тмв
В	LIDDATE COMPANY LOCO ADD DOUG	01 /25 /09	עפו	DATE: 04/03/04	SCA	LE: N	TS	SHEET:	
Α	ORIGINAL DRAFT	04/03/04	TMB		TOO		<del></del>	2	of 2
REV	DESCRIPTION	DATE	INT	1 <sup>™</sup> *HI2220R181R−10−C					01 2