

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Spec Sheet

Multilayer Chip Inductors for High Frequency Applications (HK series)

HK2125R47J-T



Features

- Item Summary
 0.47uH±5%, 0.3A, 0805/2012 (EIA/JIS)
- Lifecycle Stage
 Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 3000pcs

Products characteristics table

Inductance	0.47 uH ± 5 %
Case Size (EIA/JIS)	0805/2012
Rated Current (max)	0.3 A
DC Resistance (max)	1.5 Ω
DC Resistance (typ)	0.95 Ω
Q (min)	10
LQ Measuring Frequency	50 MHz
Self Resonant Frequency (min)	200 MHz
Self Resonant Frequency (typ)	350 MHz
Operating Temp. Range	-40 to +85 ℃
Temperature characteristic (Inductance change)	± 10 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow/Wave

External Dimensions

Dimension L	2.0 +0.3/-0.1 mm
Dimension W	1.25 ±0.2 mm
Dimension T	1.0 +0.2/-0.3 mm
Dimension e	0.5 ±0.3 mm

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification.