

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sous autorisation ecrite du propietaire. Propriete de FCI. Droits de reproduction FCI.











PERFORMANCE CHARACTERISTICS

I.5A AT 20°C (FULLY LOADED)

CURRENT RATING

I A AT 70°C (FULLY LOADED)

RATED VOLTAGE: 500 V AC (CONT /CONT)

OPERATING TEMPERATURE : -55°C TO 125°C

CONTACT RESISTANCE 20 M Ω MAX INSULATION RESISTANCE : 10 4 M Ω MIN

INSERTION FORCE: 0.75N MAX/CONT EXTRACTION FORCE: 0.15N MIN/CONT

<u>NOTES</u>

-LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16) 1.HM2S30PE5100立立立

- PLATING CODE(DIGIT 13&14)

Plating cod	e Plating	Performance Level					
AA	0.75µm Au	IEC performance level 2(250mating cycles)orTELCORDIA CO)					
AB	1.25µm Au	TELCORDIA UE					

- 2. THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
- 3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
- 4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

	Material Mat code Heattreat Plating/Finish				Spec ref					
					. /	tolerance IDEC±0.2 IDEC 2DEC±0,I 2DEC ANGLES±1, HOEKEN	projection			
							$\oplus \Box$			
	Dr	Nickor Zuo		Jul-20-09				size A4	Scale	
date	Eng	ing Nickor Zuo Jul-20-09 Produ		t family MILLIPACS		A 4	2.000			
Jul-20-2009 Mar-08-2010	Chr	PeiMing Zheng		Jul-20-09	Model Name		ECN			
Jun-08-2010	Appr	Appr Joseph Hsia		Jul-20-09	Model Revision			REL Level		
-	-	FC) ‡		MILLIPACS 2/TYPE C(/ NO SHIEL			è DCC	0014100	.1 7	Rev.
,	,					DING	§ R2C	2014180	11/	С

rev ecn no DG09-0243

DG10-0093

DG10-0110

NZ

NZ

NZ

Pro/E file catalog no

D2CC0141001/

HM2S30PE5100--- CUMSTOMER DRAWING | sheet | of |

PDM: Rev:C

STATUS: Released