



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Features:

- *2.4GHz frequency hopping spread spectrum technology*
- *460Kbps over the air and 115Kbps I/O data rates*
- *64 hopping patterns*
- *FCC certified and CE marked*
- *Integral 6dB patch antenna*
- *RS-232 asynchronous serial interface*

Benefits:

- *Exceptional immunity to multipath fading and jamming*
- *Supports high speed applications needing long range*
- *Co-location of multiple networks without interference*
- *License-free application worldwide*
- *Cost-effective, simple installation*
- *Connects to PC serial ports*

HN-210D

2.4GHz Frequency Hopping Wireless Data Modem

The HN-210D is a versatile, low cost, multi-purpose 2.4 GHz frequency-hopping wireless data modem. The HN-210D communicates through a serial port and over the air at 460.8Kbps and supports both point-to-point and point-to-multipoint networks.



Specifications

	HN-210D	HN-210DX	HN-214D
Frequency Band	2401 - 2471 MHz (USA) 2448 - 2480 MHz (France, Spain)		
Licensing	Unlicensed under FCC Part 15, ETSI 300.328		
Number of Channels	75 - US & ETSI, 25 France		
Hopping Patterns	User configurable, 64 patterns (networks) available		
I/O Data Rates	Up to 115.2 Kbps asynchronous		
RF Channel Rate	460 Kbps		
Line of Site Range	> 5 miles		
RF Bandwidth	750 KHz		
Modulation Type	GFSK		
Output Impedance	50 ohms		
Network Protocol	Dynamically assigned TDMA with ARQ		
Transmit Power	EIRP: +16dBm/+24dBm	+18dBm	EIRP: +16dBm/+24dBm
Receive Sensitivity	-99dBm for 10 ⁻⁵ BER	-93 dBm for 10 ⁻⁵ BER	-99dBm for 10 ⁻⁵ BER
Power Requirements	9 Vdc 160mA typ. 750mA surge		
Serial Data Interface	Async. RS-232		

Mechanical Specifications

	HN-210D	HN-210DX	HN-214D
Antenna	Integrated 6dB patch	n/a	Integrated 6dB patch
Case Materials	Polycarbonate, NEMA 4X		
Dimensions (mm)	130 x 79 x 35 (excl. flange)		
Weight excl. cable	235g		
Antenna Connector	n/a	TNC male	n/a
Data Connector	9-Pin D		
Power Connector	2 terminal connector		

Environmental Specifications

Temperature Range	-30°C to +70°C (radio enclosure)
Humidity	95% at +40°C, Non-condensing



HN-210D with 50 feet of cable



Serial adapter box



Power supply

Built around the WIT2410 radio, the HN-210D has an integral 6dB patch antenna creating a "single piece" modem. Communication with the HN-210D is through a 115.2Kbps asynchronous serial port supporting a standard RS-232 interface. The HN-210D communicates over the air at 460.8Kbps and supports both point-to-point and point-to-multipoint networks.

With a NEMA 4X weatherproof enclosure and aluminum mounting flange, the HN-210D is simple to install on the side of a building or attached to a mast. With no antenna to connect, the HN-210D is simply mounted where the antenna would ordinarily be mounted. This removes the need for long antenna cable runs, expensive in terms of both cost and performance.

The HN-210D comes with a 50-foot cable that connects to a DIN-rail mount serial adapter box (standard RS-232 serial 9-pin D connection) making installation in equipment cabinets simple. The HN-214D comes with a 4-foot cable for use when long cable runs are not needed. The serial adapter box also provides power to the HN-210D through a universal 110/220 50/60 wall-mount power supply (also included).

The integral 6dB patch antenna provides a line-of-site range of several miles, making the HN-210D ideal for a variety of "last mile" applications. For applications requiring more antenna gain, the HN-210DX replaces the built-in patch antenna with an external TNC connector.

When paired with the Cirronet SNAP2410 family of products, the HN-210D provides a cost-effective link from remote devices to Ethernet/IP-based applications. These applications include Intranet-based applications as well as Internet access. The HN-210D also is ideal for use in SCADA applications as remote modems in multipoint configurations and is an extremely cost-effective solution for point-to-point installations. Selectable transmit power levels of 10mW and 100mW allow the HN-210D to be used worldwide, even with the gain of the patch antenna.

Based on the Cirronet WIT2410 spread spectrum frequencyhopping radio, the HN-210D has exceptional multipath fade rejection as well as immunity to jamming. The WIT2410 is a field proven performer that delivers robust, reliable, real-world performance.

The HN-210D is both FCC and CE marked. Operating in the 2.4GHz ISM band, the HN-210D can be deployed around the world without a license.