

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








# **HPC-7000**

#### Server Tower Chassis for EATX/ATX/ MicroATX Motherboard



#### **Features**

- Supports EATX/ATX/MicroATX motherboard with dual processors
- Three internal 3.5" HDD bays and one slim ODD drive bay
- Dual front USB 3.0 ports
- System fan easy maintainance design

### C € FCC


## **Specifications**

Drive Bay		External	Internal
	Slim Optical Drive	1	-
	3.5"	3	-
Cooling	Fan	2 (12cm/150CFM)	
	Air Filter	-	
Front I/O Interface	USB3.0	2	
Miscellaneous	LED Indicators	Power	
IVIISCEITATIEOUS	Rear Panel	Two USB reserved ports	
		Operating	Non-Operating
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-40 ~ 60 °C (-40 ~ 140 °F)
Environment	Humidity	95% @ 40 °C, non-condensing	95% @ 60 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms	2 G
	Shock	10 G (with 11 ms duration, half sine wave)	
Physical Characteristics	Dimensions (W x H x D)	267.1 x 458 x 500mm (10.52" x 18.03" x 19.69")	

#### **Front View**




#### **Rear View**



#### **Inside View**





## **Ordering Information**

Part Number	Description
HPC-7000-50ZXE	HPC-7000 Tower chassis w/ 500W SPS
HPC-7000-85ZXE	HPC-7000 Tower chassis w/ 850W SPS

## **Optional Accessories**

•			
	Part Number	Description	
	96CB-SATAPOWER-6P2	SATA power wire 6-pin to big 4-pin (for slim ODD)	
	989K008734	Convert module for dual 9.6mm(H) 2.5" HDDs in a 3.5" cage	
	IPC-DT-3120E	Mobile rack for converting a 3.5" drive bay to dual 9.6mm(H) 2.5" HDD trays	
	1700026948-01	USB 3.0 cable (30cm) for rear panel	
	1700011592	USB 2.0 cable (50cm) for rear panel	
	1750006117	6cm system fan (23.6CFM) for rear panel	

## **Packing List**

Part Number	Description	Quantity
1750008562-01	12cm system fan	2

Note

1. HPC-7000 does not support AIMB series motherboard