



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





VRLA Rechargeable Battery

HR6-12



FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- The battery is designed for high rate usage.
- Absorbent Glass Mat technology for efficient gas recombination.
- The power density at 5 min~15min discharging rate is 30% higher than BP series.

APPLICATION

- UPS
- Toy-Cars
- Power Packs
- Laboratory Equipment
- Fishing Lights



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	5.5Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	2100g(4.63lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	≤22mΩ (Fully Charged)
Max. Discharge Current	82.5 A (5 sec.)
Max. Charge Current	1.65 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL 94-HB) HR6-12 Optional: Flame Retardant ABS(UL 94-V0) HR6-12FR

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 151±1.5 (5.94±0.06) ■ Width 51±1.5 (2.01±0.06) ■ Container Height 94±1.5 (3.70±0.06) ■ Total Height 100±2.0 (3.94±0.08) 		<ul style="list-style-type: none"> • Terminal T1 • Terminal T2

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	246.0	168.0	121.7	103.8	78.9	60.0	50.1	44.1	24.3
1.70V	294.0	187.5	132.3	109.9	82.2	62.3	51.7	45.1	24.8
1.60V	315.0	197.3	138.3	114.0	84.0	63.7	52.8	45.9	25.2
1.50V	324.0	201.0	141.3	115.8	85.1	64.5	53.4	46.3	25.3
1.40V	330.0	203.7	142.9	116.9	85.7	64.9	53.9	46.7	25.4
1.30V	333.0	205.5	144.0	117.6	86.1	65.3	54.1	46.8	25.5

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	21.96	14.74	10.53	8.90	6.69	5.05	4.19	3.68	2.03
1.70V	26.73	16.45	11.44	9.43	6.97	5.24	4.33	3.76	2.07
1.60V	28.64	17.31	11.96	9.78	7.12	5.36	4.42	3.83	2.10
1.50V	29.45	17.63	12.22	9.93	7.21	5.42	4.47	3.86	2.11
1.40V	30.00	17.87	12.36	10.03	7.26	5.46	4.51	3.89	2.12
1.30V	30.27	18.03	12.46	10.09	7.30	5.49	4.53	3.90	2.13

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.