

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










2

3

PRODUCT NUMBER PITCH HSxx30x000J0G 5.08mm







## Material:

- Item (all Insulator (Cover): Thermoplastic (UL94V-0)
- Item(b)Insulator(Side housing): Thermoplastic (UL94V-0)
- Item ⓒ Insulator (Middle housing): Thermoplastic (UL94V-0)
- Item d Spring clamp: Stainless steel
- Item@Solder Pin (The fourth level): Brass, Tin plated
- Item(f)Solder Pin (The third level) : Brass, Tin plated
- •Item@Solder Pin (The second level): Brass, Tin plated
- Item (Solder Pin (The first level): Brass, Tin plated

Electrical: cULus ● Voltage rating: 300V

• Current rating: 10 A

• Wire range:

Solid wire(AWG): 12-28 12-28 Stranded wire(AWG):

• Wire strip length: 6-7mm

Withstanding Voltage: 1.6KV • Operating temperature: -40°C to +115°C


260°C±5°C/5 Sec Soldering temperature:

Safety Approval:



N=Number of poles								
Dim $L=N/4\times5.08+1.0$								
Dim $B=(N/4-1)\times5.08$								

ט.עס אוווע ש=(וווע + אוווע ש											
Poles	Dim L	Dim B									
4×1p	±0.10										
4×2p-4×6p	±0.15	±0.15									
4×7p-4×12p	±0.25	±0.25									
4×13p-4×18p	±0.35	±0.30									
4×19p-4×24p	±0.45	±0.40									



	•••		Green(RAL6018/I)
•	4x24 poles	6	Blue (RAL5015/A)
		8	Grey(RAL7004/P)
		9	White(RAL1102)
		C	Multiple colors

mat'l. code					surf	surface			tolerance			projection			product family									
				ASME	ASME Y14.5 ASME Y14.5					ا	1	TERMINAL BLOCK												
Itr	ecr	n no	dr	date	tolera	tolerances unless otherwise spec							title	<del>)</del>										
					angl	es		X.±			MM		TERMINAL BLOCK											
							X.X:		X±0.3 XX±0.1					SPRING CLAMP, 45D WIRE INLET, 4-L				I FVF	ı					
					X*±	1.	X.XX:	sco			le		PARALLEL TYPE											
					dr	-		N ZHONG N ZHONG		053014 053014		FÇj		dwg	, no			5	heet	: 1	of 1	size		
					engr										HSxx30x000J0G						١,,			
					chr	1AH	NKE FENG SHI JUN		053014 053014				7		סטנטטאטכאאכוו						A4			
					appd	S						-		typ	е				CUST	OME	₹ Dro	wing		
sh	eet	et revision		Α																				
lindex		sheet		1																				

PDS: Rev :A 3

form: A4mmXLc

В

STATUS:Released

Printed: Jul 22, 42014

2

В