mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



32-Channel Serial To Parallel Converter With High Voltage Push-Pull Outputs

Ordering Information

		Package Options				
Device	Recommended Operating V _{PP} max	44 J-Lead Quad Plastic Chip Carrier	Dice in Waffle Pack Chip Carrier			
HV9308	80V	HV9308PJ	HV9308X			
HV9408	80V	HV9408PJ	HV9408X			

Features

- □ Processed with HVCMOS[®] technology
- Low power level shifting
- □ Shift register speed 8MHz
- Latched data outputs
- □ 5V CMOS compatible inputs
- Forward and reverse shifting options
- Diode to V_{PP} allows efficient power recovery
- □ 44-lead ceramic surface mount package
- Hi-Rel processing available

Absolute Maximum Ratings¹

Supply voltage, V _{DD} ²	-0.5V to +7V
Supply voltage, V _{PP} ²	-0.5V to +90V
Logic input levels ²	-0.5 to V _{DD} + 0.5V
Ground current ³	1.5A
Continuous total power dissipation ⁴	1200mW
Operating temperature range	-40°C to 85°C
Storage temperature range	-65°C to +150°C
Lead temperature 1.6mm (1/16 inch) from case for 10 seconds	260°C

Notes:

- 1. Device will survive (but operation may not be specified or guaranteed) at these extremes.
- 2. All voltages are referenced to GND₁.
- 3. Duty cycle is limited by the total power dissipated in the package.
- For operation above 25°C ambient derate linearly to maximum operating temperature at 20mW/°C.

02/96/022

General Description

The HV93 and HV94 are low voltage serial to high voltage parallel converters with push-pull outputs. These devices have been designed for use as drivers for AC-electroluminescent displays. They can also be used in any application requiring multiple output high voltage current sourcing and sinking capabilities such as driving plasma panels, vacuum fluorescent, or large matrix LCD displays.

These devices consist of a 32-bit shift register, 32 latches, and control logic to enable outputs. HV_{OUT} 1 is connected to the first stage of the shift register through the Output Enable logic. Data is shifted through the shift register on the low to high transition of the clock. The HV94 shifts in the counterclockwise direction when viewed from the top of the package and the HV93 shifts in the clockwise direction. A data output buffer is provided for cascading devices. This output reflects the current status of the last bit of the shift register (32). Operation of the shift register is not affected by the LE (latch enable) or the OE (output enable) inputs. Transfer of data from the shift register to the latch occurs when the LE input is high. The data in the latch is retained when LE is low.

Supertex Inc. does not recommend the use of its products in life support applications and will not knowingly sell its products for use in such applications unless it receives an adequate "products liability indemnification insurance agreement." Supertex does not assume responsibility for use of devices described and limits its liability to the replacement of devices determined to be defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the Supertex website: http://www.supertex.com. For complete liability information on all Supertex products, refer to the most current databook or to the Legal/Disclaimer page on the Supertex website.

Electrical Characteristics ($V_{PP} = 60V$, $V_{DD} = 5V$, $T_A = 25^{\circ}C$)

DC Characteristics

Symbol	Parameter	Min	Max	Units	Conditions
I _{PP}	V _{PP} Supply Current		100	μΑ	HV _{OUT} outputs HIGH to LOW
I _{DDQ}	I _{DD} Supply Current (Quiescent)		100	μΑ	All inputs = V _{DD} or GND
I _{DD}	I _{DD} Supply Current (Operating)		15	mA	$V_{DD} = V_{DD} max,$ $f_{CLK} = 8 MHz$
V _{OH} (Data)	Shift Register Output Voltage	V _{DD} -0.5		V	I _O = -100μA
V _{OL} (Data)	Shift Register Output Voltage		0.5	V	I _O = 100μA
I _{IH}	Current Leakage, any input		1.0	μΑ	Input = V_{DD}
I _{IL}	Current Leakage, any input		-1.0	μA	Input = GND
V _{oc}	HV _{OUT} Output Clamp Diode Voltage		-1.5	V	I _{OC} = -5mA
V _{OH}	HV _{OUT} Output when Sourcing	52		V	I _{OH} = -20mA, 0 to 70°C
V _{OL}	HV _{OUT} Output when Sinking		4.0	V	I _{OL} = 5mA, 0 to 70°C

AC Characteristics

Symbol	Parameter	Min	Max	Units	Conditions
f _{CLK}	Clock Frequency		8.0	MHz	
t _{wL} or t _{wH}	Clock width, HIGH or LOW	62		ns	
t _{SU}	Setup time before CLK rises	25		ns	
t _H	Hold time after CLK rises	10		ns	
t _{DLH} (Data)	Data Output Delay after L to H CLK		110	ns	C _L = 15pF
t _{DHL} (Data)	Data Output Delay after H to L CLK		110	ns	C _L = 15pF
t _{DLE}	LE Delay after L to H CLK	50		ns	
t _{WLE}	Width of LE Pulse	50		ns	
t _{SLE}	LE Setup Time before L to H CLK	50		ns	
t _{ON}	Delay from LE to HV _{OUT} , L to H		500	ns	
t _{OFF}	Delay from LE to HV _{OUT} , H to L		500	ns	

Recommended Operating Conditions

Symbol	Parameter	Min	Мах	Units	
V _{DD}	Logic Voltage Supply	4.5	5.5	V	
V _{PP}	High Voltage Supply	8.0	80	V	
V _{IH}	Input HIGH Voltage	V _{DD} -0.5	V _{DD}	V	
V _{IL}	Input LOW Voltage	0	0.5	V	
f _{CLK}	Clock Frequency	0	8.0	MHz	
T _A	Operating Free-Air Temperature Plastic		-40	+85	°C
		Ceramic	-55	+125	°C

Notes:

Power-up sequence should be the following:

1. Connect ground.

Apply V_{DD}.
Set all inputs (Data, CLK, Enable, etc.) to a known state.

4. Apply V_{PP}.

Power-down sequence should be the reverse of the above.

The V_{PP} should not drop below V_{DD} during operations.

Input and Output Equivalent Circuits



Switching Waveforms



Functional Block Diagram



Function Tables

Data Input	CLK*	Data Output
Н		Н
L		L
Х	No _	No Change

* _ = LOW-to-HIGH level transition

Data Input	LE	OE	HV _{out} Output
Х	Х	L	All HV _{OUT} = LOW
Х	L	Н	Previous Latched Data
Н	н	Н	Н
L	н	Н	L

Pin Configuration

HV93

44 Pin J-Lead Package

Pin	Function	Pin	Function
1	HV _{OUT} 17	23	GND
2	HV _{OUT} 16	24	V _{PP}
3	HV _{OUT} 15	25	V _{DD}
4	HV _{OUT} 14	26	Latch Enable
5	HV _{OUT} 13	27	Data In
6	HV _{OUT} 12	28	Output Enable
7	HV _{OUT} 11	29	N/C
8	HV _{OUT} 10	30	HV _{OUT} 32
9	HV _{OUT} 9	31	HV _{OUT} 31
10	HV _{OUT} 8	32	HV _{OUT} 30
11	HV _{OUT} 7	33	HV _{OUT} 29
12	HV _{OUT} 6	34	HV _{OUT} 28
13	HV _{OUT} 5	35	HV _{OUT} 27
14	HV _{OUT} 4	36	HV _{OUT} 26
15	HV _{OUT} 3	37	HV _{OUT} 25
16	HV _{OUT} 2	38	HV _{OUT} 24
17	HV _{OUT} 1	39	HV _{OUT} 23
18	Data Out	40	HV _{OUT} 22
19	N/C	41	HV _{OUT} 21
20	N/C	42	HV _{OUT} 20
21	N/C	43	HV _{OUT} 19
22	Clock	44	HV _{OUT} 18



Package Outline

top view 44-pin J-Lead Package

HV94 44 Pin J-Lead Package

Pin	Function	Pin	Function
1	HV _{OUT} 16	23	GND
2	HV _{OUT} 17	24	V _{PP}
3	HV _{OUT} 18	25	V _{DD}
4	HV _{OUT} 19	26	Latch Enable
5	HV _{OUT} 20	27	Data In
6	HV _{OUT} 21	28	Output Enable
7	HV _{OUT} 22	29	N/C
8	HV _{OUT} 23	30	HV _{OUT} 1
9	HV _{OUT} 24	31	HV _{OUT} 2
10	HV _{OUT} 25	32	HV _{OUT} 3
11	HV _{OUT} 26	33	HV _{OUT} 4
12	HV _{OUT} 27	34	HV _{OUT} 5
13	HV _{OUT} 28	35	HV _{OUT} 6
14	HV _{OUT} 29	36	HV _{OUT} 7
15	HV _{OUT} 30	37	HV _{OUT} 8
16	HV _{OUT} 31	38	HV _{OUT} 9
17	HV _{OUT} 32	39	HV _{OUT} 10
18	Data Out	40	HV _{OUT} 11
19	N/C	41	HV _{OUT} 12
20	N/C	42	HV _{OUT} 13
21	N/C	43	HV _{OUT} 14
22	Clock	44	HV _{OUT} 15

. .

02/06//02

44-Lead PLCC Package Outline (PJ)



1. A

1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier may be either a mold, or an embedded metal or marked feature. 2. Exact shape of this feature is optional.

Symbol		Α	A1	A2	b	D	D1	E	E1	е
Dimension (inches)	MIN	.165	.090	.062	.013	.685	.650	.685	.650	050
	NOM	.172	.105	-	-	.690	.653	.690	.653	.050 BSC
	MAX	.180	.120	.083	.021	.695	.656	.695	.656	Dee

JEDEC Registration MS-018, Variation AC, Issue A, June, 1993. Drawings are not to scale.

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell its products for use in such applications, unless it receives an adequate "product liability indemnification insurance agreement". **Supertex** does not assume responsibility for use of devices described and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the **Supertex** website: http://www.supertex.com.

©2007 Supertex inc. All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex Inc. 1235 Bordeaux Drive, Sunnyvale, CA 94089 TEL: (408) 222-8888 / FAX: (408) 222-4895 *www.supertex.com*