



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HVF Series

High Voltage
Flip Chip Film



This product has been
DISCONTINUED

December 2017



Ohmite's High Voltage Flip Chip Series incorporates high accuracy screen printing technology to achieve high voltage capability in a stable flip chip SMD chip resistor package. The HVF Series offers unmatched performance in comparison to standard chip resistors. Its unique design provides lower voltage and temperature coefficients, less noise, tighter tolerances, better stability, higher resistance values, and higher voltage ratings. HVF is available in convenient 1206 and 2512 footprints.

FEATURES

- High voltage up to 3,000 volts
- Industry standard sizes
- Working temperature range -55°C to 200°C
- Designed for automatic insertion
- Non-magnetic construction

SERIES SPECIFICATIONS

| Series | Resistance Range | Tol. | Power Rating (mW) | Voltage Rating* |
|---------|------------------|---------|-------------------|-----------------|
| HVF1206 | 1K-100M | 1% std. | 300 | 1,500 |
| | >100M-10G | 5% | | |
| | >10G-100G | 10% | | |
| HVF2512 | 1K-100G | 1% std. | 1000 | 3,000 |

*Use Ohm's Law ($V = \sqrt{P \cdot R}$) to calculate maximum working voltage.

**Maximum available quantity per reel is 3,500 for 1206 size and 2,000 for 2512 size; call 1-866-9-OHMITE for details.

CHARACTERISTICS

Resistance Range 1K Ω to 100G Ω

Resistance Tolerance $\pm 1\%$ std.; 5% for HVF1206 100M Ω -10G Ω more; 10% for 10G Ω +

Temperature Coefficient ± 100 ppm std.

Coating Silicone


Solder Pad Material Silver (PdAg)

Note: HVF Series should not be used with tin-lead based solder compositions. Only silver-based solder compositions are recommended. Care should be taken in the selection of the solder flux contained in the solder paste. Some pastes are "corrosive" and can damage the coating and also the resistive layer during the soldering process at high temperature. PCBs must be properly cleaned to remove any layers of moisture containing halides below the resistor.

We recommend Halide Free (or Halogen Free) solder pastes, containing for example ROL0 or similar.

It is advisable for the PCB layout to provide a slot, or air gap, underneath the downward facing resistor element, thereby increasing insulation resistance and reducing the possibility of capacitive coupling to the PCB. Under no circumstances should any copper trace be present in the layout directly under the resistive element.

Derating



Voltage coefficient of Resistance

| Series | Resistance Range | VCR (-ppm/V)* |
|--------|-----------------------------|---------------|
| 1206 | 1K ..10M Ω | <3.20 |
| | >10M ..100M Ω | <15.00 |
| | >100M ..1G Ω | <29.00 |
| | >1G Ω .. 5G Ω | <40.00 |
| 2512 | 1K ..30M Ω | <0.80 |
| | >30M ..300M Ω | <4.00 |
| | >300M ..3G Ω | <7.00 |
| | >3G Ω .. 5G Ω | <10.00 |

*Typical values. Voltage coefficient of resistance strongly depends on the resistance value. Contact Ohmite for details.

HVF Series


High Voltage Flip Chip Film

PERFORMANCE DATA


| | | |
|------------------------------|-------------------------------|---|
| Insulation Resistance | >10,000 MΩ | 500 Volt 25 °C 75% relative humidity |
| Dielectric Strength | >1,000 Volt | 25 °C 75% relative humidity |
| Thermal Shock | Δ R/R < 0.1% typ., 0.50% max. | MIL Std. 202, method 107, Cond. C (IEC 68 -2 -14) |
| Overload | Δ R/R < 0.1% typ., 0.50% max. | 1,5 x Pnom, 5 sec (do not exceed max. voltage) |
| Moisture Resistance | Δ R/R < 0.1% typ., 0.50% max. | MIL Std. 202, method 106 (IEC 68 -2 -3) |
| Load Life | Δ R/R < 0.1% typ., 0.50% max. | 1000 hours at rated power (IEC 115 -1) |

DIMENSIONS

(in. ±0.008)



Land pattern



| Series | L | W | a | T (max.) | M | N | O | L |
|---------|-------|-------|-------|----------|-------|-------|-------|-------|
| HVF1206 | 0.128 | 0.063 | 0.018 | 0.028 | 0.150 | 0.040 | 0.080 | 0.070 |
| HVF2512 | 0.252 | 0.126 | 0.026 | 0.032 | 0.288 | 0.062 | 0.140 | 0.164 |

ORDERING INFORMATION

HVF1206T1004JET

| | | | |
|---|-----------------------|---|---|
| <p>High Voltage Flip Chip Series</p> <p>Case Size 1206 2512</p> <p>TCR T = 100 ppm V = 50 ppm*</p> <p>Ohms First 3 digits are significant; last digit specifies number of zeros to follow. Example: 1006 = 100MΩ</p> | <p>RoHS Compliant</p> | <p>Taping Code blank = bulk package T = tape & reel</p> | <p>Tolerance F = 1% G = 2% J = 5% K = 10%</p> |
|---|-----------------------|---|---|

*Not available for all resistance values; consult factory


Standard part numbers

| Ohms | HVF1206--- | HVF2512--- |
|-------|------------|------------|
| 25K | ---T2502FE | ---T2502FE |
| 50K | ---T5002FE | ---T5002FE |
| 75K | ---T7502FE | ---T7502FE |
| 100K | ---T1003FE | ---T1003FE |
| 250K | ---T2503FE | ---T2503FE |
| 500K | ---T5003FE | ---T5003FE |
| 1000K | ---T1004FE | ---T1004FE |
| 1500K | ---T1504FE | ---T1504FE |
| 2000K | ---T2004FE | ---T2004FE |
| 2500K | ---T2504FE | ---T2504FE |
| 5000K | ---T5004FE | ---T5004FE |
| 7500K | ---T7504FE | ---T7504FE |
| 1G | ---T1007JE | ---T1007FE |
| 5G | --- | ---T5007FE |
| 10G | ---T1008JE | --- |


TAPE AND REEL

Per EIA Std. RS-481

Tape



DIRECTION OF FEED →



Trailer


230mm min.–560mm max. May consist of carrier and/or cover tape followed by a minimum of 160mm of carrier with sealed cover tape

Components

Leader

Minimum of 40 empty component pockets sealed with cover tape

Reel



Standard Qty/Reel is 1000; maximum available quantity per reel is 3,500 for 1206 size and 2,000 for 2512 size; call 1-866-9-OHMITE for details.