



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Wrap-Unwrap Tool - Data Sheet

These two sided wire wrapping and unwrapping tools are intended to be two tools in one. They are designed to produce perfect wire wrapping connections. Precision, long-lasting tools for use where occasional wire wraps are required or where power wire-wrapping tools are not practical. Compact and convenient. To switch from wire wrapping to unwrapping takes only seconds - just a quick change of the cap from one end to the other.



## SPECIFICATIONS

PART NO.	HW-UW-18-19	HW-UW-20	HW-UW-224	HW-UW-224-1	HW-UW-2426	HW-UW-26SM*	HW-UW-2829M*	HW-UW-30*
<b>WRAP TYPE</b>	Regular	Regular	Regular	Regular	Regular	Modified	Modified	Modified
<b>WIRE GAUGE</b>	18-19 AWG (1.00-0.91 mm)	20 AWG (0.8 mm)	22-24 AWG (0.65-0.50 mm)	22-24 AWG (0.65-0.50 mm)	24-26 AWG (0.50-0.40 mm)	26 AWG (0.40 mm)	28-29 AWG (0.32-0.29 mm)	30 AWG (0.25 mm)
<b>MAXIMUM INSULATION DIAMETER</b>	N/A	N/A	N/A	N/A	N/A	0.031" (0.79 mm)	0.036" (0.91 mm)	0.027" (0.69 mm)
<b>WRAP TERMINAL HOLE DIAMETER</b>	.075" (1.90mm)	.075" (1.90mm)	.075" (1.90mm)	.075" (1.90mm)	.075" (1.90mm)	.040" (1.02mm)	.040" (1.02mm)	.036" (0.91mm)
<b>WRAP TERMINAL HOLE DEPTH</b>	1" (25.40mm)	1" (25.40mm)	.807" (20.50mm)	1" (25.40mm)	.75" (19.05mm)	.75" (19.05mm)	.75" (19.05mm)	.75" (19.05mm)
<b>WRAP OUTSIDE DIAMETER</b>	.250" (6.35mm)	.218" (6.35mm)	.218" (6.35mm)	.218" (6.35mm)	.218" (6.35mm)	.125" (3.17mm)	.156" (3.96mm)	.125" (3.17mm)
<b>WRAP POST SIZE</b>	0.045" (1.14 mm)	0.045" (1.14 mm)	0.045" (1.14 mm)	0.045" (1.14 mm)	0.045" (1.14 mm)	0.025" (0.63 mm)	0.025" (0.63 mm)	0.025" (0.63 mm)
<b>UNWRAP WIRE GAUGE</b>	18-19 AWG (1.0-0.91 mm)	20-26 AWG (0.80-0.40 mm)	20-26 AWG (0.80-0.40 mm)	20-26 AWG (0.80-0.40 mm)	20-26 AWG (0.80-0.40 mm)	24-32 AWG (0.5-0.20 mm)	24-32 AWG (0.5-0.20 mm)	24-32 AWG (0.5-0.20 mm)
<b>UNWRAP TERMINAL HOLE DIAMETER</b>	.075" (1.90mm)	.070" (1.77mm)	.070" (1.77mm)	.070" (1.77mm)	.070" (1.77mm)	.038" (0.96mm)	.038" (0.96mm)	.038" (0.96mm)
<b>UNWRAP TERMINAL HOLE DEPTH</b>	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)	1" (25.40mm)
<b>HANDLE TYPE</b>	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
<b>WEIGHT</b>	0.161 lbs	0.155 lbs	0.125 lbs	0.150 lbs	0.150 lbs	0.150 lbs	0.148 lbs	0.150 lbs
<b>UPC NO</b>	811490014176	811490013599	811490010499	811490013131	811490013575	811490013148	811490013605	811490013155

\* These tools are recommended for .025" (0.63 mm) square terminals on .100" (2.54 mm) centers. A modified wrap provides 1.5-2 turns of insulation.