



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## HW-UW-2829M - Wrap-Unwrap Tool, 28-29 AWG - Data Sheet

This two sided wire wrapping and unwrapping tool is intended to be two tools in one. It is designed to produce perfect wire wrapping connections. Precision, long-lasting tools for use where occasional wire wraps are required or where power wire-wrapping tools are not practical. Compact and convenient. To switch from wire wrapping to unwrapping takes only seconds - just a quick change of the cap from one end to the other.



Specifications	
Wrap Type	Modified
Wire Gauge	28-29 AWG (0.32-0.29 mm)
Maximum Insulation Diameter	0.036" (0.91 mm)
Wrap Terminal Hole Diameter	.040" (1.02mm)
Wrap Terminal Hole Depth	.75" (19.05mm)
Wrap Outside Diameter	.156" (3.96mm)
Wrap Post Size	0.025" (0.63 mm)
Unwrap Wire Gauge	24-32 AWG (0.5-0.20 mm)
Unwrap Terminal Hole Diameter	.038" (0.96mm)
Unwrap Terminal Hole Depth	1" (25.40mm)
Features	Provides 1.5 to 2 turns of insulation
For Use With	.025" (0.63 mm) square terminals on .100" (2.54 mm) center to center of the pins.
Handle Type	Aluminum
Weight	0.148 lbs
UPC No	811490013605