

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









HZ0603B102R-10

UNCONTROLLED DOCUMENT


PHYSICAL DIMENSIONS:

Α	1.60	[.063]	± 0.15	[.006]
В	0.80	[.031]	± 0.15	[.006]
С	0.80	[.031]	[±] 0.15	[.006]
D	0.36	[.014]	± 0.15	[.006]





AGILENT E4991A RF Impedance/Material Analyzer HP 16092A Test Fixture. TEST REF. 3124



2002/95/EC




ELECTRICAL CHARACTERISTICS:									
Z @ 100M (<u>Ω</u>)	1Hz	DCR $\left(\begin{array}{c}\Omega\end{array} ight)$	Rated Current						
Nominal	1000								
Minimum	750								
Maximum	1250	0.60	200 mA						


NOTES: UNLESS OTHERWISE SPECIFIED

- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL.
- 2. COMPONENTS SHOULD BE ADEQUETELY PREHEATED BEFORE SOLDERING.
- 3. TERMINATION FINISH IS 100% TIN.
- 4. OPERATEING TEMPERATURE TEMP: -40°C~+125°C (INCLUDING SELF-HEATING)

LAND PATTERNS FOR REFLOW SOLDERING

RECOMMENDED SOLDERING CONDITIONS





(For wave soldering, add 0.762 [0.030] to this dimension)

DIMENSIONS ARE IN mm [INCHES].				This print is the property of Lai					
				Tech, and is loaned in confidence subject to return upon request		▗▎▐▎▗▄▗▐▘ ▗ ▗▗▊▘			
			with the understanding that no			Laird			
				copies shall be made without th		Luiiu			
				written consent of Laird Tech. All rights to design or invention are reserved.					
				PROJECT/PART NUMBER:	R	EV	PART TY	PE:	DRAWN BY:
С	ADD OPERATING TEMPERATURE, NOTE3 UPDATE LAIRD LOGO AND REFLOW CURVE			HZ0603B102R-10		С	CO-FIRE		JRK
В	UPDATE COMPANY LOGO ADD ROHS	02/26/08	JRK	DATE: 03/01/04	SCALE	;		SHEET:	
Α	ORIGINAL DRAFT	03/01/04	JRK	CAD #	TOOL			2	of 2
REV	DESCRIPTION	DATE	INT		_		-		01 2