



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



[Home](#) > [Products](#) > > [950902](#) > [950902DFLFT](#)
[Add to myIDT \[?\]](#)

You may also like...

## 950902DFLFT

<b>Category:</b>	
<b>Generic Part:</b>	950902
<b>Market Group:</b>	PC CLOCK
<b>Description:</b>	PC MAIN CLOCK

### Parameters

<b>Package</b>	SSOP 56 (PVG56)
<b>Speed</b>	NA
<b>Temperature</b>	C
<b>Voltage</b>	3.3 V
<b>Status</b>	Active
<b>Sample</b>	No
<b>Minimum Order Quantity</b>	1000
<b>Factory Order Increment</b>	1000

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

<b>Description</b>	SSOP 300 MIL, 56LD
<b>Class</b>	PLASTIC
<b>Moisture Sensitivity Level (MSL)</b>	1
<b>Category</b>	Green
<b>Moisture Exposure Floor Life</b>	Unlimited @ <30°C/85% RH
<b>Peak Reflow Temperature</b>	260°C
<b>Rebake Conditions</b>	NA
<b>Length</b>	18.4
<b>Mark</b>	G
<b>Width</b>	7.5
<b>Pitch</b>	0.64
<b>Thickness</b>	2.3
<b>Status</b>	Active