

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Search Entire Site

Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets >

Add to myIDT [?]

953805CF

Category: Desktop Chipsets

Generic Part: 953805

Market Group: PC CLOCK

Description: PC MAIN CLOCK

The ICS953805 is a two chip clock solution for desktop designs using SiS756/761 style chipsets. The ICS953805

provides all the necessary clock signals for such a system.

Output Features:

- 1 Pair of differential push-pull CPU outputs
- 1 Pair of differential push-pull NB outputs
- 1 Pair of current mode differential serial reference clock
- 8 PCICLK @ 3.3V
- 5 Pairs of current mode differential PCI-Express clocks
- 2 REF @ 3.3V
- 2 ZCLK @ 3.3V
- 1 12_48MHz@3.3V
- 1 24_48MHz@3.3V

You may also like.



Parameters

SSOP 56 (PV56)
3.3 V
SSOP 56
NA
С
Active
Yes
130
26

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 56LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	225°C
Rebake Conditions	N/A
Length	18.4
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active