



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Clock Synthesizer by Chipset Vendor](#) > [Desktop Chipsets](#) > [954135](#) > [954135AF](#)

[Add to myIDT \[?\]](#)

You may also like...

## 954135AF

**Category:** [Desktop Chipsets](#)

**Generic Part:** [954135](#)

**Market Group:** [PC CLOCK](#)

**Description:** [PC MAIN CLOCK](#)

ICS954135 provides Intel CK410 compliant clocking. This clock synthesizer provides a single chip solution for next generation Intel chipsets. ICS954135 is driven with a 14.318MHz crystal. It generates CPU outputs up to 400MHz, while providing highly accurate Serial ATA and PCI-Express clocks.

### Output Features:

- 2 - 0.7V current-mode differential CPU pairs
- 4 - 0.7V current-mode differential SRC pairs for SATA and PCI-Express
- 1 - 0.7V current-mode differential CPU\_ITP/SRC selectable pair
- 4 - PCI Clocks (33 MHz)
- 2 - PCI Free Running Clocks (33 MHz)
- 2 - USB Clocks (48 MHz)
- 1 - 0.7V current-mode differential DOT clock pair (96 MHz)
- 2 - 14.31818 MHz Reference Clocks



### Parameters

Package	SSOP 48 (FV48)
Voltage	3.3 V
Package	SSOP 48
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	120
Factory Order Increment	30

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	225°C
Rebake Conditions	NA
Length	15.9
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active