



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




Integrated Device Technology
The Analog and Digital Company™

[Products](#) | [Applications](#) | [Search](#) | [Support](#) | [Investor](#) | [About IDT](#)
[Clock / Timing Devices](#) | [PC Motherboard Clocks](#) | [Mobile](#) > [9LPRS397](#) > [9LPRS397EKLFT](#)

9LPRS397EKLFT

[Description](#) | [Parameters](#) | [Package](#) | [Documents](#) | [Distributor Inventory](#) | [Contacts](#)

DESCRIPTION

PC MAIN CLOCK

Generic Part:
[9LPRS397](#)
Category:

PARAMETERS

Package	VFQFPN 72
Speed	NA
Temperature	C
Voltage	1.8 V
CPU Manufacturer	Intel®
Chipset	910
Yellow Cover Spec.	
Embedded	
Core Supply Voltage (VDD)	3.3 V
Input Style	XTAL
Output Style	TYPE-SR
Output Supply Voltage (VDDO)	1.05-3.3
Temp. Grade	C
Suggested - Pkg. Voltage	

PACKAGE

Package	VFQFPN 72 (NLG72)
Description	VFQFP-N 10.0 X 10.0 X 0.9 MM - NO LEAD
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Pb Free Category	e3 Sn
Mark	K
Package Type	VFQFPN
Lead Count	72
Length	10.0 mm
Width	10.0 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	168
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	3
Moisture Exposure Floor Life	168hrs@<30C/60% RH
Peak Reflow Temperature	260°C
Rebake Conditions	48hrs@125C
Related Package Documents	view documents

DOCUMENTS

Type	Title	Size	Revision Date
Product Change Notice	PCN# : A0808-02R2 ALTERNATE ASSEMBLY LOCATION FOR VFQFP-N-64 AND VFQFP-N-72	2259 KB	08/26/2010
	PCN# : TB0909-03 Changed of Moisture Barrier Bag for Tape & Reel Packing	1133 KB	10/05/2009
	PCN# : A0903-04 Chipmos Taiwan & Carsem Malaysia as Alternate Assembly Site for Copper Wire Proces	101 KB	05/12/2009
	PCN# : A0808-02 ALTERNATE ASSEMBLY LOCATION FOR VFQFP-N-64 AND VFQFP-N-72	129 KB	08/27/2008
	PCN# : TB0807-01 Reel Quantity Change on VFQFP-N-68, VFQFP-N-72	56 KB	07/10/2008

DISTRIBUTOR INVENTORY

Part	Distributor	Qty	Date	RFQ	Order
------	-------------	-----	------	-----	-------

No matches found.

CONTACTS

Sales Offices

- ▶ [Sales Offices and authorized distributors](#)

Technical Support

Clock Help

- ▶ [WWW: Clock Help](#)