



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Integrated Device Technology

The Analog and Digital Company™



[Products](#) |
 [Applications](#) |
 [Search](#) |
 [Support](#) |
 [Investor](#) |
 [About IDT](#)

[9LRS4123A](#) |
 [9LRS4123AKLF](#)

9LRS4123AKLF

[Description](#) |
 [Parameters](#) |
 [Package](#) |
 [Documents](#) |
 [Distributor Inventory](#) |
 [Contacts](#)

DESCRIPTION

PC MAIN CLOCK - PIKETON

Generic Part:

[9LRS4123A](#)

Category:

PARAMETERS

Package VFQFPN 32
Voltage 1.8V/3V
Temperature C
Speed NA

PACKAGE

Package VFQFPN 32 (NLG32)
Description VFQFP-N 5 X 5 X 1.0MM NO LEAD
Status Active
Class PLASTIC
Category Green
Pb (Lead) Free Yes
Pb Free Category e3 Sn
Mark K
Package Type VFQFPN
Lead Count 32
Length 5.0 mm
Width 5.0 mm
Thickness 1.0 mm
Pitch 0.5 mm
Tube / Tray TRAY
Quantity per Tube/Tray 490
Quantity per Reel 2500
Moisture Sensitivity Level (MSL) 3
Moisture Exposure 168 hrs@-<30C/60%
Floor Life RH
Peak Reflow Temperature 260°C
Rebake Conditions 48hrs@125C
Related Package Documents [view documents](#)

DOCUMENTS

Type	Title	Size	Revision Date
Product Change Notice	PCN# : A1004-01(R1) Alternate Assembly Facilities for VFQFPN-32	131 KB	06/04/2010
	PCN# : A1004-01 Alternate Assembly Facilities for VFQFPN-32	130 KB	04/02/2010
	PCN# : A0910-01 Alternate Assembly Facility for Copper Wire Process on VFQFPN-20, 32, 40, 48, 56	117 KB	11/05/2009

DISTRIBUTOR INVENTORY

Part	Distributor	Qty	Date	RFQ	Order
No matches found.					

CONTACTS

Sales Offices

▶ [Sales Offices and authorized distributors](#)

Technical Support

Clock Help

▶ [WWW: Clock Help](#)

Copyright © 2011 Integrated Device Technology, Inc. | [Legal](#) | [Careers](#) | [Contact Us](#) | [myIDT](#) | [Press Room](#) | [Site Map](#)