

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## Accessories

#### Slide Rail



#### For 1U rackmount chassis

- 26" P/N: 9680009153
- Maximum acceptable load: 25kg
- 1 pair included



#### For 2U and higher rackmount chassis

- 26" P/N: 9680006905
- Maximum acceptable load: 45kg
- 1 pair included

## **Industrial Disk Tray/Bay**



#### IPC-DT-5121/ IPC-DT-5121B

Shockproof industrial hard disk drive tray with cooling fan and optional front USB and PS/2 interfaces

- Accepted Device: 1 x 3.5" HDD (only for 9.5mm thickness)
- Cooling Fan: 1 x 4 cm
- Color (Codes): Gray (414U), Black (4C2X)
- Dimensions (W x H x D): 148.5 x 42.6 x 171 mm³



#### 989K008733

A frame to securely fix a 3.5" HDD in a 5.25" drive bay

Accepted Device: 3.5" HDD x 1



#### **IPC-DT-3120E**

Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD/SSD trays

- Accepted Device: 2 x 2.5" SATA HDD/SSD (only for HDD/SSD thickness less than 9.6 mm)
- Dimensions (W x H x D): 101.6 x 25.4 x 139 mm³



#### 989K008734

A frame to securely fix two 2.5" HDDs/SSDs in a 3.5" drive bay

 Accepted Device: 2.5" SATA HDD/SSD x 2 (only for HDD thickness less than 9.6 mm)



#### 9892200013E

Module to convert a 5.25" drive bay to a slim ODD and a 3.5" drive bay

 Accepted Device: 3.5" device x 1, slim ODD x 1



#### 96RACK-5SS-CAGE-CR

Mobile rack for converting one 5.25" drive bay to four 2.5" SAS/SATA HDD/SSD trays

- Accepted Device: 2.5" SAS/SATA HDD/SSD x 4
- Dimension (W x H x D): 146 x 41 x 170 mm<sup>3</sup>



#### IPC-DT-5230E

Mobile rack for converting dual 5.25" drive bays to three 3.5" SAS/SATA HDD trays

- Accepted Device: 3.5" SAS/SATA HDD x 3 or 2.5" SAS/SATA HDD/SSD x3
- Cooling Fan: 1 x 8 cm
- Dimensions (W x H x D): 146.5 x 86 x 225 mm³



#### 96RACK-5-SS-CR-B2

Mobile rack for converting one 5.25" drive bay to one slim ODD and two 2.5" SAS/SATA HSS/SSD trays

- Accepted Device: slim ODD x 1, 2.5" SAS/ SATA HDD/SSD x 2
- Dimension (W x H x D): 146 x 41.3 x 170 mm<sup>3</sup>





#### 98RKBTOSO9E

Add-on card hold down kit (short)

- Bracket Q'ty of each kit : 5 pcs
- For PCI add-on card with height 72.3mm ~ 87.3mm and PCIe add-on card with height 81.7mm ~ 91.8mm



#### 98RKBTOS10E

Add-on card hold down kit (long)

- Bracket Q'ty of each kit : 5 pcs
- For PCI add-on card with height 54.8mm ~ 75.7mm and PCIe add-on card with height 59.3mm ~ 80.2mm

## Accessories

## **USB Cables**











| Part Number  | 1700008461                           | 1700003195                 | 1700002204                 | 1700014398                 | 1700020277-01                             |
|--------------|--------------------------------------|----------------------------|----------------------------|----------------------------|---|
| Description  | USB 2.0 cable with 4 ports           | USB 2.0 cable with 2 ports | USB 2.0 cable with 2 ports | USB 2.0 cable with 4 ports | USB 3.0 cable with 2 ports                |
| Cable Length | 30.5 cm (12.01")                     | 17.5 cm (6.89")            | 27 cm (11.92")             | 30.5 cm (12.01")           | 30 cm (11.81")                            |
| Remark       | For ATX/Micro-ATX MB, full-sized SBC |                            |                            | For half-sized SBC         | For ATX/Micro-ATX MB, full/half-sized SBC |

#### **SATA Cables**











| Part Number  | 96CB-SATAPOWER-6P1                       | 1700022749-11                           | 1700019381   | 1700007351   | 1700003194  |
|--------------|--|---|--|--|---|
| Description  | SATA power cable for slim ODD            | SATA power cable for<br>HDD/SSD         | SATA data cable (right angle)                                      | SATA data cable (right angle)                                | SATA data cable                                     |
| Cable Length | 10 cm (3.94")                            | 10 cm (3.94")                           | 55 cm (21.65")   | 40 cm (15.75")   | 60 cm (23.62")                                      |
| Remark       | Big 4 P to SATA power cable for Slim ODD | Big 4 P to SATA power cable for HDD/SSD | SATA data cable with 1<br>right angle and 1 vertical<br>connectors | SATA data cable with 1 right angle and 1 vertical connectors | SATA data cable with vertical connectors with locks |

## **COM** and **Printer Ports Cables**









| Part Number  | 1701092300                           | 1701090401            | 1700020294-01                           | 1700008762             |
|--------------|--------------------------------------|-----------------------|---|------------------------|
| Description  | COM cable with 2 ports               | COM cable with 1 port | Printer (Parallel) port cable           | COM cable with 2 ports |
| Cable Length | 28.5 cm (11.22")                     | 40 cm (15.75")        | 42.0 cm (16.54")                        | 22.5 cm (8.86")        |
| Remark       | For ATX/Micro-ATX MB, full-sized SBC |                       | For ATX/Micro-ATX MB,<br>full-sized SBC | For half-sized SBC     |

# Accessories

## **Video Cables**







| Part Number  | PCE-DP10-00A1E  | 1700021831-01   | 1700008822-11  |
|--------------|---|---|--|
| Description  | Display port cable  | DP to DVI port cable  | DVI to DVI port cable  |
| Cable Length | 25 cm (9.84")   | 30 cm (11.81")  | 30 cm (11.81")   |
| Remark       | Video cable for converting on board DP connector to external DP port supporting DP 1.1a/1.2 signaling | Video cable for converting on board DP connector to external DVI-D port | Video cable for converting on board DVI connector to external DVI-D port |

## **Other Cables**







| Part Number  | 1700006915  | 1700006916  | 1700024754-01            |
|--------------|---|---|--------------------------|
| Description  | Cable for<br>ACP-4000MB front LED board           | Cable for IPC-610MB-H front LED board                             | Power cable for GPU card |
| Cable Length | 60 cm (23.62")                                    | 60 cm (23.62")  | 10 cm                    |
| Remark       | For those Advantec<br>VOLT1 connector too far awa | 2*B4P Molex power connector to 6+2P PCle power cable for GPU card |                          |