



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Home > Products >> VPP1500 > VPP1500BFG

You may also like...

VPP1500BFG

Category:	
Generic Part:	VPP1500
Market Group:	VIDEO
Description:	DUAL LVDS TCON



Parameters

Speed	NA
Temperature	C
Voltage	1.8 V
Status	Active
Sample	Yes
Minimum Order Quantity	126
Factory Order Increment	126

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

No documents available for this part at this time.

Package

Package	CABGA 289 (BFG289)
Description	CHIP ARRAY BGA 15MM X 15MM X 0.8MM PITCH
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	BFG
Package Type	CABGA
Lead Count	289
Length	15.0 mm
Width	15.0 mm
Thickness	1.4 mm
Pitch	0.8 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	112
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	3
Moisture Exposure Floor Life	168hrs@<30C/60%RH
Peak Reflow Temperature	260Å°C
Rebake Conditions	48hrs@125C
Related Package Documents	view documents