



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



INDUSTRIAL FIBER OPTICS

You Are Here: [Home](#) > [Assemblies](#) > [SMA to SMA \(SERCOS\) POF Patch Cords](#) > [SMA/ SMA \(SERCOS\) Standard POF Patch Cords](#) > [IF 636-3-0](#)

SMA/ SMA (SERCOS) Standard POF Patch Cords, 3.00 m

SMA 905 connectors, 1.0 mm core, UL-rated PE 2.2 mm jacket



Industrial Fiber Optics manufactures multiple product lines of premium quality fiber optic patch cords suitable for SERCOS networking and other industrial networking applications. This patch cord series utilizes plastic optical fiber and is recommended for short distance applications such as those inside cabinets or where they will not be subject to physical abuse or exposure to chemicals. Patch cord consists of a UL-rated fiber cable with industry-standard 1.0 mm optical core/cladding surrounded by a chlorinated polyethylene jacket terminated with all stainless steel SMA 905 connectors. Equivalent to Allen Bradley 2090-SCEP series. Available to all customers and OEM manufacturing companies as a direct purchase item.

Part Number: IF 636-3-0



Features

- ◆ UL-rated fiber cable
- ◆ Strain reliefs to minimize fiber stress at terminations
- ◆ 1 μ m polish terminations ensure high optical coupling efficiency
- ◆ Epoxied and crimped connector terminations for maximum retention strength
- ◆ Assembly processes exceed industry-standard procedures

Specifications

Fiber Cable	GHCP4001	
Connector 1	SMA 905	
Connector 2	SMA 905	
RoHS Compliance	YES	
	Unit	Value
Length	m	3.00 +/-0.05
Loss Typical (per term.)	dB	
Loss Maximum (per term.)	dB	2.57
Optical Loss	dB/m	.17 Max. @ 650 nm
Operating Temperature	° C	-55 ~ 85
Storage Temperature	° C	-55 ~ 85
Fiber Tensile Strength	N	70

Copyright 2000-11. All Rights Reserved Industrial Fiber Optics