



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





ILSEU series

External Mount Hydrostatic Level Transmitter



- **Piezo-resistive sensor**
- **Accuracy $\leq \pm 0.25\%$ FS BFSL**
- **Various outputs including Volts and mA.**
- **Level ranges from 0-48" (0-4ft) to 0-480" (0-40ft) water gauge (Custom ranges available on request)**

The external mount hydrostatic level transmitter, ILSEU, has a piezo-resistive silicon pressure sensor which is an oil-filled isolated diaphragm. The sensor and housing are made from stainless steel with a choice of internal O-ring seals to ensure the product is suitable for a wide range of applications.

The electronics incorporate a microprocessor based amplifier, requiring no adjusting and giving stable electronics, especially in high vibration/shock applications.

Every device is temperature compensated, calibrated and supplied with a traceable serial number and calibration certificate.

Input Pressure Ranges

Nominal level, Gauge,	inchWG	40	100	200	280	400
Permissible Overpressure	inchWG	800	800	800	2000	2000

Suitable applications

Environmental engineering	Container or chamber level
Rainwater harvesting	Automotive testing
Static tank level	Vehicle tank level
Laboratory testing	IBC, IBC Tote or pallet tank

Performance

Accuracy (Non-Linearity & Hysteresis)	$\leq \pm 0.25\%$ / FS (BFSL)	
Setting Errors (offsets)	2-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
	3-wire	Zero & Full Scale, $\leq \pm 0.5\%$ / FS
Permissible Load	2-wire	$R_{max} = [(VS-VSmin)/0.02] \Omega$
	3-wire	$R_{min} = 10k\Omega$
Influence Effects	Supply	$< 0.005\%$ FS / 1V
	Load	0.05% FSO / $k\Omega$

Material Specifications

Housing	303 Stainless Steel
"O" ring seals	Viton
Diaphragm	316L Stainless Steel
Media wetted parts	Housing & process connection, "O" ring seal, diaphragm

Miscellaneous

Current consumption	2-wire - limits at 28mA 3-wire - typical 6mA
Weight	Approx 3.5oz (100g)
Installation position	Any, small zero shift when tilted through 90°
Operational Life	$> 100 \times 10^6$ cycles
Insulation resistance	$> 50M\Omega$ at 50Vdc

Electrical Protection

Supply reverse polarity	No damage but also no function
Electromagnetic compatibility	CE Compliant

Mechanical Stability

Shock	100g / 11s
Vibration	10g RMS (20 - 2000Hz)

Temperatures & Thermal Effects

Media Temperature	-40°C to +125°C
Ambient Temperature	-20°C to +80°C
Storage temperature	-40°C to +125°C
Compensated temperature range	+20°C to +80°C
Thermal Zero Shift (TZS)	$\leq \pm 0.04\%$ /FS/°C
Thermal Span Shift (TSS)	$\leq -0.015\%$ /°C

Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969
Email:sales@cynergy3.com

ISO9001 CERTIFIED

www.cynergy3.com



ILSEU series

External Mount Hydrostatic Level Transmitter

Output Signal and Supply Voltage

Wire system	Output	Supply Volts	Connection	Pin No. (Large plug and socket)
2-wire	4-20mA	9-32Vdc	+ve Supply -ve Supply Ground	Pin 1 Pin 2 Earth pin
3-wire	0.5 - 4.5Vdc (non-ratiometric)	9-32 Vdc	+ve Supply -ve Supply +ve Output Ground	Pin 1 Pin 2 Pin 3 Earth Pin

Part No	Pressure Range	Output
ILSEU-Gi048-5	0-48" WG	4-20mA
ILSEU-Gi120-5	0-120" WG	4-20mA
ILSEU-Gi240-5	0-240" WG	4-20mA
ILSEU-Gi360-5	0-360" WG	4-20mA
ILSEU-Gi480-5	0-480" WG	4-20mA
ILSEU-Gi048-D	0-48" WG	0.5 to 4.5V 3Wire
ILSEU-Gi120-D	0-120" WG	0.5 to 4.5V 3Wire
ILSEU-Gi240-D	0-240" WG	0.5 to 4.5V 3Wire
ILSEU-Gi360-D	0-360" WG	0.5 to 4.5V 3Wire
ILSEU-Gi480-D	0-480" WG	0.5 to 4.5V 3Wire

Part No	Pressure Range	Output
ILSEU-G0100-5	0 - 1mWG	4-20mA
ILSEU-G0250-5	0 - 2.5mWG	4-20mA
ILSEU-G0500-5	0 - 5mWG	4-20mA
ILSEU-G0700-5	0 - 7mWG	4-20mA
ILSEU-G1000-5	0 - 10mWG	4-20mA
ILSEU-G0100-D	0 - 1mWG	0.5 to 4.5V 3Wire
ILSEU-G0250-D	0 - 2.5mWG	0.5 to 4.5V 3Wire
ILSEU-G0500-D	0 - 5mWG	0.5 to 4.5V 3Wire
ILSEU-G0700-D	0 - 7mWG	0.5 to 4.5V 3Wire
ILSEU-G1000-D	0 - 10mWG	0.5 to 4.5V 3Wire

(Custom ranges and outputs available on request)

