



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Internet Office 120V 350VA 180W Standby UPS, 6 Outlets (NEMA 5-15R), 5-15P Plug, DB9, Tel/DSL

MODEL NUMBER: INTERNET350SER



Compact desktop UPS system protects your computer and its peripherals from blackouts, brownouts, power surges and line noise that can damage or destroy equipment, wipe out valuable data, and degrade component performance.

### Description

The INTERNET350SER Internet Office® 120V 350VA 180W Standby UPS protects your PC and other expensive equipment against common power threats, such as blackouts and surges. Reliable battery backup support allows you to work through short power failures, and gives you enough time to safely save files and shut down your system in case of a prolonged blackout. The internal battery provides 12.2 minutes of runtime at half load and 3.3 minutes at full load. During normal operation, incoming utility power keeps the UPS battery fully charged, so backup power will always be available.

Connect your equipment to the six NEMA 5-15R outlets. Three outlets provide both battery backup and surge protection to your computer, monitor and other crucial components. The other three are surge-protected only for printers, scanners and other non-essential equipment. A single-line RJ11 jack protects a standard dial-up/DSL phone connection from dataline surges.

A built-in audible alarm and front-panel LEDs provide real-time line and battery status at a glance. A DB9 interface port works with Tripp Lite's free downloadable PowerAlert® software to enable safe unattended system shutdown and file saves in the event of a prolonged power failure when you aren't around.

The UPS system's compact housing fits easily on a desktop, shelf or anywhere else convenient to your workstation. The six-foot power cord with right-angle NEMA 5-15P plug connects to a standard AC outlet.

### Features

#### 350VA 180W Standby UPS System

- Protects PC and other equipment against common power threats, such as blackouts and surges

### Highlights

- 6 NEMA 5-15R outlets—3 battery-backup, 3 surge-protected only
- Single-line RJ11 jack protects phone/fax line against surges
- 6 ft. power cord with space-saving right-angle NEMA 5-15P plug
- LEDs and audible alarm provide instant status reports
- 12.2 min. runtime at half load; 3.3 min. at full load

### Package Includes

- INTERNET350SER Internet Office 120V 350VA 180W Standby UPS
- DB9 serial interface cable
- Owner's manual





- Allows enough time to safely save files and shut down system in case of prolonged blackout
- Supports half load for 12.2 min. and full load for 3.3 min.
- Incoming AC power keeps internal battery charged during normal operation
- Compatible with 120V 60Hz applications in North America and other countries

#### 6 NEMA 5-15R Outlets for Connecting Equipment

- 3 outlets provide both battery backup and surge protection to crucial components (PCs, monitor, router)
- 3 outlets provide surge protection only for non-essential equipment (printers, scanners)
- Robust 510-joule surge protection rating keeps equipment safe
- RJ11 jack protects standard dial-up/DSL phone line from surges

#### EMI/RFI Line Noise Filtering

- Filters out electromagnetic and radio frequency interference that can cause hardware damage, data loss or audio/video transmission problems

#### DB9 Communication Port

- Enables data-saving unattended shutdown with Tripp Lite's PowerAlert software (available via free download at [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert))

#### Diagnostic LEDs and Audible Alarm

- Alarm sounds to indicate power failure and overloads
- LEDs indicate power status and overload/check battery status

#### Compact Housing for Convenient Installation

- Space-saving housing fits on desktop, shelf or almost anywhere convenient to your workstation
- 6 ft. power cord with right-angle NEMA 5-15P plug allows furniture to be placed flush against the wall

## Specifications

OVERVIEW	
UPC Code	037332123428
OUTPUT	
Output Volt Amp Capacity (VA)	350
Output Watt Capacity (Watts)	180
Nominal Output Voltage(s) Supported	110V; 115V; 120V
Nominal Voltage Details	115v nominal output in battery mode
Frequency Compatibility	60 Hz



Output Voltage Regulation (Battery Mode)	+/- 5%
Output Receptacles	(6) 5-15R
UPS Output Receptacles (Surge Suppression Only)	3 UPS outlets, 3 surge-only outlets
Output AC Waveform (AC Mode)	Sine wave
Output AC Waveform (Battery Mode)	PWM sine wave
<b>INPUT</b>	
Rated input current (Maximum Load)	10A
Nominal Input Voltage(s) Supported	120V AC
UPS Input Connection Type	5-15P; Right-Angled
UPS Input Cord Length (ft.)	6
UPS Input Cord Length (m)	1.8
Recommended Electrical Service	15A 120V
Input Phase	Single-Phase
<b>BATTERY</b>	
Full Load Runtime (min.)	3.3 min. (180W)
Half Load Runtime (min.)	12.2 min. (90w)
DC System Voltage (VDC)	12
Expandable Runtime	No
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Switches	Combination switch controls on/off power status and self-test operation
Audible Alarm	Audible alarm indicates on-battery, low-battery and overload status
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC Suppression Joule Rating	420
UPS AC Suppression Response Time	Instantaneous
UPS Dataline Suppression	1 line TEL/DSL (1 in / 1 out)
EMI / RFI AC Noise Suppression	Yes
<b>PHYSICAL</b>	
Installation Form Factors Supported with Included Accessories	Tower; Ultra-compact desktop
Primary Form Factor	Desktop



UPS Power Module Dimensions (hwd, in.)	3 x 8.25 x 6.5
UPS Power Module Dimensions (hwd, cm)	7.62 x 20.96 x 16.51
UPS Power Module Weight (lbs.)	5.25
UPS Power Module Weight (kg)	2.38
Shipping Dimensions (hwd / in.)	4.300 x 12.300 x 7.800
Shipping Dimensions (hwd / cm)	10.92 x 31.24 x 19.81
Shipping Weight (lbs.)	8.6000
Shipping Weight (kg)	3.90
UPS Housing Material	ABS
Primary UPS Height (mm)	76
Primary UPS Width (mm)	210
Primary UPS Depth (mm)	165
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC Mode BTU / Hr. (Full Load)	7
AC Mode Efficiency Rating (100% Load)	99%
<b>COMMUNICATIONS</b>	
Communications Interface	DB9 Serial
PowerAlert Software	For local monitoring via the UPS's built-in DB9 Serial port, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a>
Communications Cable	DB9 interface cable included
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	2-4 milliseconds
Low Voltage Transfer to Battery Power (Setpoint)	99
High Voltage Transfer to Battery Power (Setpoint)	139
<b>SPECIAL FEATURES</b>	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
<b>CERTIFICATIONS</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI)
<b>WARRANTY</b>	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Product Warranty Period (Latin America)	3-year limited warranty
Product Warranty Period (International)	2-year limited warranty
Product Warranty Period (Mexico)	3-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>