



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Available in
500ft Spools

TRUE DMX 512

This cable features 4 conductors plus a ground, which makes it a true DMX 512 cable.

DOUBLE PROTECTION


Inside, this 4 conductor cable features both an aluminum and a braided shield which provides double the protection from EMI and cross talk.

FLEXIBLE PVC JACKET

This DMX cable comes complete with a matte PVC jacket that protects the interior workings of the cable from the harsh environment. It also helps the cable keep its shape for a perfect coil every time.

Product specifications may change without prior notification

Configuration



Product

Part number IO-D22428-500SP
 Number of Conductors 4 plus shield

Conductors

Details 20/0.12
 Size 24 AWG

Insulation

Material PE
 Colors Blue, White, Red, & Green

Shield

Material Tinned Copper & Aluminum
 Details Braided 16*9/0.10

Drain Wire

Material Tinned Copper
 Details 7/0.20

Jacket

O.D. 8.0mm
 Material PVC
 Color Black

Electrical and Mechanical Characteristics

Conductor DC Resistance ohm/1km < 87.5
 Shield DC Resistance ohm/1km < 18.1
 Voltage Breakdown 300V
 Flex Life > 58,800
 Tensile Strength > 745N
 Applicable Temperature -20°C ~ +60°C (-4°F ~ +140°F)
 Peak Temperature -40°C ~ +70°C (-40°F ~ +158°F)

PART NUMBER BREAKDOWN:

IO-A12326-500SP
 Type. "A" for Audio. "D" for Data

IO-A12326-500SP
 Number of Twisted Pairs

IO-A12326-500SP
 AWG Conductor Size

IO-A12326-500SP
 "1" for Spiral Shield. "2" for Braided Shield.

IO-A12326-500SP
 Outer Diameter. In mm.

IO-A12326-500SP
 500ft. Spool

Product specifications may change without prior notification

