



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## PURPOSE BUILT

In order to meet our requirements for audio quality, we not only sourced high quality materials, but also designed a cable that feels as great as it sounds.

## TWO BRAIDED SHIELDS

We've introduced two braided shields which provide a new level of EMI resistance for use in the most offensive of electromagnetic or RF environments.

## DURABLE PVC JACKET

Under the nylon sleeve, a tough PVC jacket protects the cable from dust and water.

## NYLON BRAIDED SLEEVE

A Premium cable with a Premium feel. This Nylon Braided sleeve adds other dimension of toughness and finesse.

## RUGGED CONNECTORS

Our sleek, black connectors feature an extremely durable zinc die cast shell, which can withstand the rigors of any musical environment. They also come complete with a rubber boot just the right amount of strain relief.

Our Premium Series was made to provide incredible signal to noise ratio using our Four Core Technology.




Part Number	IO-XLR3-3-X	IO-XLR3-6-X	IO-XLR3-10-X	IO-XLR3-25-X	IO-XLR3-50-X	IO-XLR3-100-X
Length*	3 Ft	6 Ft	10 Ft	25 Ft	50 Ft	100 Ft
	0.9m	1.8m	3m	7.6m	15m	30.5m
AWG	24AWG	24AWG	24AWG	24AWG	24AWG	24AWG
Jacket Color	Black	Black	Black	Black	Black	Black

\*Custom Lengths available upon request

Product specifications may change without prior notification

## Configuration



### Product

Part Number IO-XLR3-XX-X  
 Number of Conductors 4 plus 2 shields

### Conductors

Details 20/12  
 Size 24 AWG

### Insulation

Material LDPE  
 Colors 2 Blue and 2 White  
 Resistance > 500KΩ

### Shield

1 Braided TC and 1 Braided OFC

### Jacket

O.D. 7.6mm (8.4mm with Nylon Sleeve)  
 Material PVC with Braided Nylon Sleeve  
 Color Black

### Electrical and Mechanical Characteristics

Conductor DC Resistance (ohm/m) 0.073 +/- 1%  
 Shield DC Resistance (ohm/m) 0.007 +/- 1%  
 Voltage Breakdown 500V  
 Flex Life > 17,700  
 Tensile Strength > 1,159N  
 Applicable Temperature -20°C ~ +60°C (-4°F ~ +140°F)  
 Peak Temperature -40°C ~ +70°C (-40°F ~ +158°F)


## PART NUMBER BREAKDOWN:

IO-XLR3-XX-E  
 Type of cable

IO-XLR3-XX-E  
 Number of pins

IO-XLR3-XX-E  
 Length of the cable in feet

IO-XLR3-XX-E  
 Series identifier



Product specifications may change without prior notification