imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





PLRs

PLCS

OIT Touch Panels

PC Touch Panels

LCD Monitors

Fanless PCs

Temperature Controllers



iCube: All-in-One Control Solution Intelligence raised by the power of three!





Features

- Programmable function keys
- 2 communication ports RS232/RS485
- Embedded Ethernet with Webserver (i3C only)

MODBUS

- GSM modem for SMS/Data or Ethernet (options)
- Micro SD up to 2GB (option)
- Digital and analog I/O (up to 42 points)
- Expansion I/O (options)
- 4 high-speed counters (10Khz Max)
- PID control (up to 32 loops)
- Alarm / Recipe / Animation / Bitmaps
- Floating Point MathReal Time Clock
- 20+ Protocols (Modbus, AB DF1, Mitsubishi, GE Fanuc, etc.)
- 256KB RAM (Ladder), 1MB Graphical
- IP65 (NEMA4) CE, cUL, UL, Class 1 Div 2 (A & B versions)
- Free configuration software
- Input power: 10-30 VDC supply
- Class 1, Div 2

Advantages of an Integrated Solution

• 3 solutions in one (HMI, PLC and open bus connectivity)

The Power of i3:

• 3 screen options

3-year warranty

• 3 built-in Î/O options

• 3 communication options

The iCube has capitalized on the progress made in microprocessor technology by condensing traditional control components into a single, compact unit - reducing manufacturing costs, overall power consumption of control solutions and application development time. Allows standardization to a single controller fitting most applications and greater flexibility for future development.

The i3 controller offers the benefit of a full PLC - all the timers, math and complex functions as most standard PLC's - combined with PID, temperature and process control, on-board I/O, and expandability. The color HMI is a fantastic interface offering 1,040 custom screens supporting a variety of bit maps, and animation. i3 controllers also have expandable options: Ethernet and GSM/GPRS modem communications, optional built-in web server for the color touch screen controllers. Free configuration manager included - straight-forward programming software used for programming logic and screens.

Model No.	Screen	Keys	MicroSD Card	Solid State Digital Outputs	Relay Outputs	Digital Inputs	Analog Inputs	Universal Analog Inputs	Analog Outputs
i3 - "A" Version - Monod	chrome Graphical Screen and	l Keys - W	/ MicroSD fun	ction (96.0W x 96.0H)	x 75.5D mm)			
i3A12X/10A01-SOOF	2.25" Monotone 128x64	20	Y		6	12	1		
i3A12X/20B05-SOHF	2.25" Monotone 128x64	20	Y	16		24	2		
i3A12X/13C14-SOHF	2.25" Monotone 128x64	20	Y	12		12		2	2
i3 - "B" Version - Monod	chrome Graphical Touchscree	n - W/ Mi	icroSD functio	n (96.0W x 96.0H x 75	.5D mm)				
i3B12Y/10D03-SCHF	3.5" Monotone 160x128	5	Y		6	12	4		
i3B12Y/20B05-SCHF	3.5" Monotone 160x128	5	Y	16		24	2		
i3B12Y/13C14-SCHF	3.5" Monotone 160x128	5	Y	12		12		2	2
i3 - "C" Version - 32 bit	Color Graphical Touchscreen	- W/ Mic	roSD function	(186.1W x 143.6H x 7	7.0D mm)				
i3C12Z/10D03-SCHF	5.7" 32k Color 320x240	6	Y		6	12	4		
i3C12Z/20B05-SCHF	5.7" 32k Color 320x240	6	Y	16		24	2		
i3C12Z/13C14-SCHF	5.7" 32k Color 320x240	6	Y	12		12		2	2

You May Also Need...

Description Ethernet Attachment				
Programming Cable 9-pin female to RJ-45				
USB-Serial converter				

i3 - Serial Expansion Modules - DIN-Rail Mounted

Model No.	Description
IOS/M04ITX-D1	4 Channel TC input
IOS/M08BDR-D1	8 Channel Digital I/O - 4 inputs + 4 Relay outputs
IOS/M12BDD-D2	12 Channel Digital I/O - 4 inputs + 8 Trn outputs
IOS/M04IPX-D1	4 Channel RTD input
IOS/M08ICX-D1	8 Channel DC current input
IOS/M12IDX-D1	12 Channel Digital Inputs
IOS/M04OXA-D1	4 channel Analog output 14bit, 0-10/4-20mA

