



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Typical values (unless otherwise specified)

$V_{DSS}$	$V_{GS}$	$R_{DS(on)}$	$R_{DS(on)}$
20V max	$\pm 20V$ max	1.65mΩ @ 10V	2.2mΩ @ 4.5V
$Q_g$ tot	$Q_{gd}$	$Q_{gs2}$	$Q_{rr}$
38nC	13nC	3.5nC	18nC



Applicable DirectFET Outline and Substrate Outline (see p.7,8 for details) ①

SQ	SX	ST		MQ	MX	MT			
----	----	----	--	----	----	----	--	--	--

### Description

The IRF6619PbF combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest on-state resistance in a package that has the footprint of an SO-8 and only 0.7 mm profile. The DirectFET package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques, when application note AN-1035 is followed regarding the manufacturing methods and processes. The DirectFET package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6619PbF balances both low resistance and low charge along with ultra low package inductance to reduce both conduction and switching losses. The reduced total losses make this product ideal for high efficiency DC-DC converters that power the latest generation of processors operating at higher frequencies. The IRF6619PbF has been optimized for parameters that are critical in synchronous buck operating from 12 volt bus converters including  $R_{ds(on)}$ , gate charge and  $C_{dv/dt}$ -induced turn on immunity. The IRF6619PbF offers particularly low  $R_{ds(on)}$  and high  $C_{dv/dt}$  immunity for synchronous FET applications.

### Absolute Maximum Ratings

	Parameter	Max.	Units
$V_{DS}$	Drain-to-Source Voltage	20	V
$V_{GS}$	Gate-to-Source Voltage	$\pm 20$	
$I_D$ @ $T_A = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10\text{V}$ ③	30	
$I_D$ @ $T_A = 70^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10\text{V}$ ③	24	A
$I_D$ @ $T_C = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10\text{V}$ ④ (Package Limited)	150	
$I_{DM}$	Pulsed Drain Current ⑤	240	
$E_{AS}$ (Thermally limited)	Single Pulse Avalanche Energy ⑥	240	mJ
$I_{AR}$	Avalanche Current ⑤	See Fig. 14, 15, 17a, 17b,	A
$E_{AR}$	Repetitive Avalanche Energy ⑤		mJ




Fig. 1. Typical On-Resistance Vs. Gate Voltage




Fig. 2. Typical Total Gate Charge vs Gate-to-Source Voltage

### Notes:

- ① Click on this section to link to the appropriate technical paper.
- ② Click on this section to link to the DirectFET Website.
- ③ Surface mounted on 1 in. square Cu board, steady state.

④  $T_C$  measured with thermocouple mounted to top (Drain) of part.


⑤ Repetitive rating; pulse width limited by max. junction temperature.

⑥ Limited by  $T_{Jmax}$ , starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.86\text{mH}$ ,  $R_G = 25\Omega$ ,  $I_{AS} = 24\text{A}$ ,  $V_{GS} = 10\text{V}$ . Part not recommended for use above this value.

**Static @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

	Parameter	Min.	Typ.	Max.	Units	Conditions
$\text{BV}_{\text{DSS}}$	Drain-to-Source Breakdown Voltage	20	—	—	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = 250\mu\text{A}$
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	14	—	$\text{mV}/^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $\text{I}_D = 1\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	1.65	2.2	$\text{m}\Omega$	$\text{V}_{\text{GS}} = 10\text{V}, \text{I}_D = 30\text{A}$ ⑦
		—	2.2	3.0		$\text{V}_{\text{GS}} = 4.5\text{V}, \text{I}_D = 24\text{A}$ ⑦
$\text{V}_{\text{GS}(\text{th})}$	Gate Threshold Voltage	1.55	—	2.45	V	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}, \text{I}_D = 250\mu\text{A}$
$\Delta \text{V}_{\text{GS}(\text{th})}/\Delta T_J$	Gate Threshold Voltage Coefficient	—	-5.8	—	$\text{mV}/^\circ\text{C}$	
$\text{I}_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	1.0	$\mu\text{A}$	$\text{V}_{\text{DS}} = 16\text{V}, \text{V}_{\text{GS}} = 0\text{V}$
		—	—	150		$\text{V}_{\text{DS}} = 16\text{V}, \text{V}_{\text{GS}} = 0\text{V}, T_J = 125^\circ\text{C}$
$\text{I}_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	100	nA	$\text{V}_{\text{GS}} = 20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	-100		$\text{V}_{\text{GS}} = -20\text{V}$
$\text{g}_{\text{fs}}$	Forward Transconductance	89	—	—	S	$\text{V}_{\text{DS}} = 10\text{V}, \text{I}_D = 24\text{A}$
$\text{Q}_g$	Total Gate Charge	—	38	57	nC	$\text{V}_{\text{DS}} = 10\text{V}$ $\text{V}_{\text{GS}} = 4.5\text{V}$ $\text{I}_D = 16\text{A}$ See Fig. 18
$\text{Q}_{\text{gs}1}$	Pre-V <sub>th</sub> Gate-to-Source Charge	—	10.2	—		
$\text{Q}_{\text{gs}2}$	Post-V <sub>th</sub> Gate-to-Source Charge	—	3.5	—		
$\text{Q}_{\text{gd}}$	Gate-to-Drain Charge	—	13.2	—		
$\text{Q}_{\text{godr}}$	Gate Charge Overdrive	—	11.1	—		
$\text{Q}_{\text{sw}}$	Switch Charge ( $\text{Q}_{\text{gs}2} + \text{Q}_{\text{gd}}$ )	—	16.7	—	nC	$\text{V}_{\text{DS}} = 10\text{V}, \text{V}_{\text{GS}} = 0\text{V}$
$\text{Q}_{\text{oss}}$	Output Charge	—	22	—		
$\text{R}_G$	Gate Resistance	—	—	2.3	$\Omega$	
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	21	—	ns	$\text{V}_{\text{DD}} = 16\text{V}, \text{V}_{\text{GS}} = 4.5\text{V}$ ⑦ $\text{I}_D = 24\text{A}$ Clamped Inductive Load
$t_r$	Rise Time	—	71	—		
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	25	—		
$t_f$	Fall Time	—	9.3	—		
$C_{\text{iss}}$	Input Capacitance	—	5040	—	pF	$\text{V}_{\text{GS}} = 0\text{V}$ $\text{V}_{\text{DS}} = 10\text{V}$ $f = 1.0\text{MHz}$
$C_{\text{oss}}$	Output Capacitance	—	1580	—		
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	780	—		

**Diode Characteristics**

	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_s$	Continuous Source Current @ $T_C = 25^\circ\text{C}$ (Body Diode)	—	—	110	A	MOSFET symbol showing the integral reverse p-n junction diode. 
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ⑤	—	—	240		
$V_{\text{SD}}$	Diode Forward Voltage	—	0.8	1.0	V	$T_J = 25^\circ\text{C}, I_S = 24\text{A}, V_{\text{GS}} = 0\text{V}$ ⑦
$t_{\text{rr}}$	Reverse Recovery Time	—	29	44	ns	$T_J = 25^\circ\text{C}, I_F = 24\text{A}$ $\text{di}/\text{dt} = 100\text{A}/\mu\text{s}$ ⑦
$Q_{\text{rr}}$	Reverse Recovery Charge	—	18	27	nC	

**Notes:**

⑤ Repetitive rating; pulse width limited by max. junction temperature.

⑦ Pulse width  $\leq 400\mu\text{s}$ ; duty cycle  $\leq 2\%$ .

### Absolute Maximum Ratings

	Parameter	Max.	Units
P <sub>D</sub> @ T <sub>A</sub> = 25°C	Power Dissipation ③	2.8	W
P <sub>D</sub> @ T <sub>A</sub> = 70°C	Power Dissipation ③	1.8	
P <sub>D</sub> @ T <sub>C</sub> = 25°C	Power Dissipation ④	89	
T <sub>P</sub>	Peak Soldering Temperature	270	°C
T <sub>J</sub>	Operating Junction and Storage Temperature Range	-40 to +150	

### Thermal Resistance

	Parameter	Typ.	Max.	Units
R <sub>0JA</sub>	Junction-to-Ambient ③⑩	—	45	°C/W
R <sub>0JA</sub>	Junction-to-Ambient ⑧⑩	12.5	—	
R <sub>0JA</sub>	Junction-to-Ambient ⑨⑩	20	—	
R <sub>0JC</sub>	Junction-to-Case ④⑩	—	1.4	
R <sub>0J-PCB</sub>	Junction-to-PCB Mounted	1.0	—	
	Linear Derating Factor ③	0.017		W/°C





Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient ⑥


#### Notes:

- ⑧ Used double sided cooling, mounting pad with large heatsink.
- ⑨ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.


⑩ R<sub>θ</sub> is measured at T<sub>j</sub> of approximately 90°C.



③ Surface mounted on 1 in. square Cu (still air).




⑨ Mounted to a PCB with small clip heatsink (still air)




⑨ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)

# IRF6619PbF


International  
Rectifier




**Fig 4.** Typical Output Characteristics




**Fig 5.** Typical Output Characteristics




**Fig 6.** Typical Transfer Characteristics



**Fig 7.** Normalized On-Resistance vs. Temperature



**Fig 8.** Typical Capacitance vs. Drain-to-Source Voltage



**Fig 9.** Typical On-Resistance vs. Drain Current and Gate Voltage




Fig 10. Typical Source-Drain Diode Forward Voltage




Fig 11. Maximum Safe Operating Area




Fig 12. Maximum Drain Current vs. Case Temperature




Fig 13. Typical Threshold Voltage vs. Junction Temperature




Fig 14. Typical Avalanche Current vs.Pulsewidth




Fig 15. Maximum Avalanche Energy vs. Temperature




Fig 16. Maximum Avalanche Energy Vs. Drain Current




Fig 18a. Gate Charge Test Circuit




Fig 18b. Gate Charge Waveform

Notes on Repetitive Avalanche Curves , Figures 14, 15:  
(For further info, see AN-1005 at [www.irf.com](http://www.irf.com))

1. Avalanche failures assumption:

Purely a thermal phenomenon and failure occurs at a temperature far in excess of  $T_{jmax}$ . This is validated for every part type.

2. Safe operation in Avalanche is allowed as long as  $T_{jmax}$  is not exceeded.

3. Equation below based on circuit and waveforms shown in Figures 17a, 17b.

4.  $P_D(\text{ave})$  = Average power dissipation per single avalanche pulse.

5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).

6.  $I_{av}$  = Allowable avalanche current.

7.  $\Delta T$  = Allowable rise in junction temperature, not to exceed  $T_{jmax}$  (assumed as 25°C in Figure 14, 15).

$t_{av}$  = Average time in avalanche.

D = Duty cycle in avalanche =  $t_{av} \cdot f$

$Z_{thJC}(D, t_{av})$  = Transient thermal resistance, see Figures 3

$$P_D(\text{ave}) = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$$

$$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$$

$$E_{AS}(\text{AR}) = P_D(\text{ave}) \cdot t_{av}$$




Fig 17a. Unclamped Inductive Test Circuit




Fig 17b. Unclamped Inductive Waveforms




Fig 19a. Switching Time Test Circuit





Fig 19b. Switching Time Waveforms




**Fig 20.** Diode Reverse Recovery Test Circuit for N-Channel HEXFET® Power MOSFETs

## DirectFET™ Substrate and PCB Layout, MX Outline (Medium Size Can, X-Designation)

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.


This includes all recommendations for stencil and substrate designs.




## DirectFET™ Outline Dimension, MX Outline (Medium Size Can, X-Designation).

Please see DirectFET application note AN-1035 for all details regarding the assembly of DirectFET.

This includes all recommendations for stencil and substrate designs.




## DirectFET™ Part Marking



Note: Line above the last character of the date-code indicates "Lead-Free".


## DirectFET™ Tape & Reel Dimension (Showing component orientation).



NOTE: Controlling dimensions in mm  
Std reel quantity is 4800 parts. (ordered as IRF6619TRPBF). For 1000 parts on 7"  
reel, order IRF6619TR1PBF

REEL DIMENSIONS								
	STANDARD OPTION (QTY 4800)		TR1 OPTION (QTY 1000)					
CODE	METRIC	MIN	MAX	IMPERIAL	METRIC	MIN	MAX	
A	330.0	N.C.	12.992	N.C.	177.77	N.C.	6.9	N.C.
B	20.2	N.C.	0.795	N.C.	19.06	N.C.	0.75	N.C.
C	12.8	13.2	0.504	0.520	13.5	12.8	0.53	0.50
D	1.5	N.C.	0.059	N.C.	1.5	N.C.	0.059	N.C.
E	100.0	N.C.	3.937	N.C.	58.72	N.C.	2.31	N.C.
F	N.C.	18.4	N.C.	0.724	N.C.	13.50	N.C.	0.53
G	12.4	14.4	0.488	0.567	11.9	12.01	0.47	N.C.
H	11.9	15.4	0.469	0.606	11.9	12.01	0.47	N.C.

LOADED TAPE FEED DIRECTION



DIMENSIONS			
	METRIC	MIN	MAX
A	7.90	8.10	0.311
B	3.90	4.10	0.154
C	11.90	12.30	0.469
D	5.45	5.55	0.215
E	5.10	5.30	0.201
F	6.50	6.70	0.256
G	1.50	N.C.	0.059
H	1.50	1.60	0.059

Data and specifications subject to change without notice.  
This product has been designed and qualified for the Consumer market.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information.5/06

Note: For the most current drawings please refer to the IR website at:  
<http://www.irf.com/package/>