



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China


# International **IR** Rectifier

PD - 93848A

## IRF7750

HEXFET® Power MOSFET

- Ultra Low On-Resistance
- Dual P-Channel MOSFET
- Very Small SOIC Package
- Low Profile ( $< 1.1\text{mm}$ )
- Available in Tape & Reel



$V_{DSS} = -20\text{V}$

$R_{DS(on)} = 0.030\Omega$

### Description

HEXFET® power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the ruggedized device design, that International Rectifier is well known for, provides the designer with an extremely efficient and reliable device for battery and load management.

The TSSOP-8 package has 45% less footprint area than the standard SO-8. This makes the TSSOP-8 an ideal device for applications where printed circuit board space is at a premium. The low profile ( $< 1.1\text{mm}$ ) allows it to fit easily into extremely thin environments such as portable electronics and PCMCIA cards.

### Absolute Maximum Ratings

	Parameter	Max.	Units
$V_{DS}$	Drain- Source Voltage	-20	V
$I_D @ T_C = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ -4.5\text{V}$	$\pm 4.7$	A
$I_D @ T_C = 70^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ -4.5\text{V}$	$\pm 3.8$	
$I_{DM}$	Pulsed Drain Current ①	$\pm 38$	
$P_D @ T_C = 25^\circ\text{C}$	Power Dissipation	1.0	W
$P_D @ T_C = 70^\circ\text{C}$	Power Dissipation	0.64	
	Linear Derating Factor	0.008	W/ $^\circ\text{C}$
$V_{GS}$	Gate-to-Source Voltage	$\pm 12$	V
$T_J, T_{STG}$	Junction and Storage Temperature Range	-55 to + 150	$^\circ\text{C}$

### Thermal Resistance

	Parameter	Max.	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient②	125	$^\circ\text{C/W}$


# IRF7750

International  
Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	-20	—	—	V	$V_{\text{GS}} = 0\text{V}$ , $I_D = -250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$	Breakdown Voltage Temp. Coefficient	—	0.012	—	V/ $^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $I_D = -1\text{mA}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	—	0.030	$\Omega$	$V_{\text{GS}} = -4.5\text{V}$ , $I_D = -4.7\text{A}$ ②
		—	—	0.055		$V_{\text{GS}} = -2.5\text{V}$ , $I_D = -3.8\text{A}$ ②
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	-0.45	—	-1.2	V	$V_{\text{DS}} = V_{\text{GS}}$ , $I_D = -250\mu\text{A}$
$g_{\text{fs}}$	Forward Transconductance	11	—	—	S	$V_{\text{DS}} = -10\text{V}$ , $I_D = -4.7\text{A}$
$I_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	-1.0	$\mu\text{A}$	$V_{\text{DS}} = -20\text{V}$ , $V_{\text{GS}} = 0\text{V}$
		—	—	-25		$V_{\text{DS}} = -16\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 70^\circ\text{C}$
$I_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	-100	nA	$V_{\text{GS}} = -12\text{V}$
	Gate-to-Source Reverse Leakage	—	—	100		$V_{\text{GS}} = 12\text{V}$
$Q_g$	Total Gate Charge	—	26	39	nC	$I_D = -4.7\text{A}$
$Q_{\text{gs}}$	Gate-to-Source Charge	—	3.9	5.8		$V_{\text{DS}} = -16\text{V}$
$Q_{\text{gd}}$	Gate-to-Drain ("Miller") Charge	—	8.0	12		$V_{\text{GS}} = -5.0\text{V}$ ②
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	15	—	ns	$V_{\text{DD}} = -10\text{V}$
$t_r$	Rise Time	—	54	—		$I_D = -1.0\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	180	—		$R_D = 10\Omega$
$t_f$	Fall Time	—	210	—		$R_G = 24\Omega$ ②
$C_{\text{iss}}$	Input Capacitance	—	1700	—	pF	$V_{\text{GS}} = 0\text{V}$
$C_{\text{oss}}$	Output Capacitance	—	380	—		$V_{\text{DS}} = -15\text{V}$
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	270	—		$f = 1.0\text{MHz}$

## Source-Drain Ratings and Characteristics


	Parameter	Min.	Typ.	Max.	Units	Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	-1.0	A	MOSFET symbol showing the integral reverse p-n junction diode.
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ①	—	—	-38		
$V_{\text{SD}}$	Diode Forward Voltage	—	—	-1.2		$T_J = 25^\circ\text{C}$ , $I_S = -1.0\text{A}$ , $V_{\text{GS}} = 0\text{V}$ ②
$t_{\text{rr}}$	Reverse Recovery Time	—	26	39	ns	$T_J = 25^\circ\text{C}$ , $I_F = -1.0\text{A}$
$Q_{\text{rr}}$	Reverse Recovery Charge	—	16	24	nC	$di/dt = 100\text{A}/\mu\text{s}$ ②

### Notes:


① Repetitive rating; pulse width limited by max. junction temperature.

② Pulse width  $\leq 300\mu\text{s}$ ; duty cycle  $\leq 2\%$ .


③ When mounted on 1 inch square copper board,  $t < 10$  sec




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Typical Source-Drain Diode Forward Voltage

# IRF7750


International  
Rectifier




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage




**Fig 7.** Threshold Voltage Vs. Temperature




**Fig 8.** Maximum Safe Operating Area



**Fig 9.** Maximum Drain Current Vs.  
Case Temperature




**Fig 10.** Typical Power Vs. Time




**Fig 11.** Typical Effective Transient Thermal Impedance, Junction-to-Ambient

# IRF7750


International  
Rectifier



**Fig 12.** Normalized On-Resistance Vs. Temperature




**Fig 13.** Typical On-Resistance Vs. Drain Current



**Fig 14.** Typical On-Resistance Vs. Gate Voltage

## TSSOP-8 Package Outline



### NOTES

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
2. DIMENSIONS ARE SHOWN IN MILLIMETERS AND INCHES.
3. CONTROLLING DIMENSION: MILLIMETER.
- (4) DATUM PLANE H IS LOCATED AS SHOWN.
- (5) DATUM A AND B TO BE DETERMINED AT DATUM PLANE H.
- (6) DIMENSIONS D AND E1 ARE MEASURED AT DATUM PLANE H.
- (7) DIMENSION L IS THE LEAD LENGTH FOR SOLDERING TO A SUBSTRATE.
8. OUTLINE CONFORMS TO JEDEC OUTLINE MO-153AA.

**WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, Tel: (310) 252-7105

**IR GREAT BRITAIN:** Hurst Green, Oxted, Surrey RH8 9BB, UK Tel: ++ 44 1883 732020

**IR CANADA:** 15 Lincoln Court, Brampton, Ontario L6T3Z2, Tel: (905) 453 2200

**IR GERMANY:** Saalburgstrasse 157, 61350 Bad Homburg Tel: ++ 49 6172 96590

**IR ITALY:** Via Liguria 49, 10071 Borgaro, Torino Tel: ++ 39 11 451 0111

**IR JAPAN:** K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo Japan 171 Tel: 81 3 3983 0086

**IR SOUTHEAST ASIA:** 1 Kim Seng Promenade, Great World City West Tower, 13-11, Singapore 237994 Tel: ++ 65 838 4630

**IR TAIWAN:** 16 Fl. Suite D. 207, Sec. 2, Tun Haw South Road, Taipei, 10673, Taiwan Tel: 886-2-2377-9936

*Data and specifications subject to change without notice. 5/2000*

International  
**IR** Rectifier