



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



$V_{CES} = 1200V$
$I_C = 200A$ at $T_C = 80^\circ C$
$t_{SC} \geq 10\mu sec$
$V_{CE(ON)} = 3.20V$ at $I_C = 200A$

Single Switch IGBT with Soft Recovery Diode
POWIR 62™ Package



Applications:

- Industrial Motor Drive
- Uninterruptible Power Supply
- Welding and Cutting Machine
- Switched Mode Power Supply
- Induction Heating

Features	Benefits
Low $V_{CE(ON)}$ and Switching Losses	High Efficiency in a Wide Range of Applications
RBSOA Tested	Rugged Transient Performance
10 μsec Short Circuit Safe Operating Area	
POWIR 62™ Package	Industry Standard
Lead Free	RoHS Compliant, Environmental Friendly

Base Part Number	Package Type	Standard Pack	Quantity	Orderable Part Number
IRG5U200SD12B	POWIR 62™	Box	45	IRG5U200SD12B

Absolute Maximum Ratings of IGBT

V_{CES}	Collector to Emitter Voltage	1200	V
V_{GES}	Continuous Gate to Emitter Voltage	±20	V
I_C	Continuous Collector Current	$T_C = 80^\circ C$	200 A
		$T_C = 25^\circ C$	320 A
I_{CM}	Pulse Collector Current	$T_J = 150^\circ C$	400 A
P_D	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ C, T_J = 150^\circ C$	1430 W
T_J	Maximum IGBT Junction Temperature	150	°C
T_{JOP}	Maximum Operating Junction Temperature Range	-40 to +150	°C
T_{stg}	Storage Temperature	-40 to +125	°C

Electrical Characteristics of IGBT at $T_J = 25^\circ\text{C}$ (Unless Otherwise Specified)

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
$V_{(BR)CES}$	Collector to Emitter Breakdown Voltage	1200			V	$V_{GE} = 0V, I_C = 3mA$	
$V_{GE(th)}$	Gate Threshold Voltage	4.5	5.3	6.0	V	$I_C = 2mA, V_{CE} = V_{GE}$	
$V_{CE(ON)}$	Collector to Emitter Saturation Voltage		3.20	3.50	V	$T_J = 25^\circ\text{C}$	$I_C = 200A, V_{GE} = 15V$
			3.80		V	$T_J = 125^\circ\text{C}$	
I_{CES}	Collector to Emitter Leakage Current			3	mA	$V_{GE} = 0V, V_{CE} = V_{CES}$	
I_{GES}	Gate to Emitter Leakage Current			400	nA	$V_{GE} = \pm 20V, V_{CE} = 0$	
R_{Gint}	Internal Gate Resistance		0.62		Ω		

Switching Characteristics of IGBT

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
$t_{d(on)}$	Turn-on Delay Time		460		ns	$T_J = 25^\circ\text{C}$	$V_{CC}=600V, I_C = 200A, R_G = 15 \Omega, V_{GE}=\pm 15V, \text{Inductive Load}$
			440			$T_J = 125^\circ\text{C}$	
t_r	Rise Time		280		ns	$T_J = 25^\circ\text{C}$	
			280			$T_J = 125^\circ\text{C}$	
$t_{d(off)}$	Turn-off Delay Time		1220		ns	$T_J = 25^\circ\text{C}$	
			1300			$T_J = 125^\circ\text{C}$	
t_f	Fall Time		130		ns	$T_J = 25^\circ\text{C}$	
			160			$T_J = 125^\circ\text{C}$	
E_{on}	Turn-on Switching Loss		14.4		mJ	$T_J = 25^\circ\text{C}$	
			18.4			$T_J = 125^\circ\text{C}$	
E_{off}	Turn-off Switching Loss		4.0		mJ	$T_J = 25^\circ\text{C}$	
			7.6			$T_J = 125^\circ\text{C}$	
Q_g	Total Gate Charge		2500		nC	$T_J = 25^\circ\text{C}$	
C_{ies}	Input Capacitance		23.0		nF	$V_{CE} = 25V, V_{GE} = 0V, f = 1MHz, T_J = 25^\circ\text{C}$	
C_{oes}	Output Capacitance		1.81				
C_{res}	Reverse Transfer Capacitance		0.72				
RBSOA	Reverse Bias Safe Operating Area	Trapezoid				$I_C = 400A, V_{CC} = 960V, V_P = 1200V, R_G = 4.7\Omega, V_{GE} = +15V \text{ to } 0V, T_J = 150^\circ\text{C}$	
SCSOA	Short Circuit Safe Operating Area	10			μs	$V_{CC} = 600V, V_{GE} = 15V, T_J = 150^\circ\text{C}$	

Absolute Maximum Ratings of Freewheeling Diode







V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current, $T_C = 25^\circ\text{C}$	400	A
	Diode Continuous Forward Current, $T_C = 80^\circ\text{C}$	200	
I_{FM}	Pulse Diode Current	400	A





Electrical and Switching Characteristics of Freewheeling Diode

Parameter		Typ.	Max.	Unit	Test Conditions	
V_F	Forward Voltage	2.00	2.70	V	$T_J = 25^\circ\text{C}$	$I_F = 200\text{A}$, $V_{GE} = 0\text{V}$
		2.20			$T_J = 125^\circ\text{C}$	
I_{rr}	Peak Reverse Recovery Current	160		A	$T_J = 25^\circ\text{C}$	$I_F = 200\text{A}$, $di/dt = 2400\text{A}/\mu\text{s}$, $V_{rr} = 600\text{V}$, $V_{GE} = -15\text{V}$
		180			$T_J = 125^\circ\text{C}$	
Q_{rr}	Reverse Recovery Charge	12.4		μC	$T_J = 25^\circ\text{C}$	
		22.4			$T_J = 125^\circ\text{C}$	
E_{rec}	Reverse Recovery Energy	4.08		mJ	$T_J = 25^\circ\text{C}$	
		8.04			$T_J = 125^\circ\text{C}$	


Module Characteristics

Parameter		Min.	Typ.	Max.	Unit
V_{iso}	Isolation Voltage (All Terminals Shorted), $f = 50\text{Hz}$, 1minute			2500	V
$R_{\theta JC}$	Junction-to-Case (IGBT)		0.087		$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Junction-to-Case (Freewheeling Diode)		0.217		$^\circ\text{C}/\text{W}$
$R_{\theta CS}$	Case-To-Sink (Conductive Grease Applied)		0.1		$^\circ\text{C}/\text{W}$
M	Power Terminals Screw: M6	3.0		5.0	N·m
M	Mounting Screw: M6	4.0		6.0	N·m
G	Weight		310		g




Fig.1 Typical IGBT Saturation Characteristics

Fig.2 Typical IGBT Output Characteristics

Fig.3 Typical Freewheeling Diode Characteristics

Fig. 4 Typical Capacitance Characteristics

Fig.5 Typical Switching Loss vs. Collector Current

Fig.6 Typical Switching Loss vs. Gate Resistance


Fig.7 Typical Load Current vs. Frequency

Fig.8 Reverse Bias Safe Operation Area (RBSOA)

Fig.9 Typical Transient Thermal Impedance (IGBT)

Fig.10 Typical Transient Thermal Impedance (Diode)

Internal Circuit:



Package Outline (Unit: mm):



Qualification Information†

Qualification Level	Industrial
Moisture Sensitivity Level	Not Applicable
RoHS Compliant	Yes

† Qualification standards can be found at International Rectifier's web site: <http://www.irf.com/product-info/reliability/>