

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









IRLG5AB 300X200X0.25				
Flexield				
Category: Noise Suppressing / Magnetic She	ets			
Sub Category: Noise Suppressing / Magnetic	Sheets			
TDK Series Name : IRLG5				
Application : No Data Available.				
Function: No Data Available.				
Description : No Data Available.				
▶ Submit Sample Request				
► Check Distributor Inventory				
Print Page				
Additional Search Tools:		I		
► Application ► Catalog	▶ SEAT	▶ CCV	▶ TVCL	▶ Tech Notes
Property Name		Property Descrip	otion	
Product Lifecycle Stage		Production		
Part Number Replacement	No Data Available.			
Lead (Pb) Free		Yes		
Surface Mount		No		
Body Length (L)		Nom 300 mm		
Body Breadth (W)		Nom 200 mm		
Standard Sheet Thickness		Nom 0.25 mm		
Recommended Frequency Range		Min No Data Available.		
Recommended Frequency Range		Max No Data Available.		
Category Temperature Range		Min -40 Cel		
Category Temperature Range		Max 85 Cel		
Initial Permeability		Min <i>No Data Available.</i>		
Initial Permeability Measuring Condition		13.56MHz		
Surface Resistivity		Min 10 kOhm		
Thermal Conductivity		Nom 1.5 W/(m.k)		
Density		Nom 3700 kg/m**3		
Storage Temperature Range		Min No Data Available.		
Country of Origin		Max No Data Available.		
Country of Origin Packing		JPN Box		
Minimum Package Qty		Nom 1 Pcs		
Minimum Order Oty		Nom 1 Pcs		
Weight		Nom 56 a		
Disclaimer: This information is to be used for reference characteristics/performance for the particular part number that this standard part is not designed or warrant specifications set fort in TDK's general product specificationed or warranted for use in , or permitted to be (collectively, "Excluded Applications").	e purposes only and is sumber. For product specificated to meet any specification. Note also that this	ubject to change by TDK with cation information, please ref tions of any intermediate or s standard part has not been	er to TDK's general produc end user different from or specially designed or man	t specification. Please in addition to the ufactured for, nor is it