



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Low Power, <100 Lux Optimized, Analog Output Ambient Light Sensor

## ISL76671

The [ISL76671](#) is a low cost, light-to-voltage silicon optical sensor combining a photodiode array, a non-linear current amplifier and a micro-power op amp on a single monolithic IC. Similar to the human eye, the photodiode array has peak sensitivity at 550nm and spans the wavelength range 400nm to 600nm, rejecting UV and IR light. The input luminance range is from 0.01 lux to 100 lux.

The integrated non-linear current amplifier boosts and converts the photodiode signal into a square root output format, extending dynamic range while maintaining excellent sensitivity in dimly lit conditions. As such, the part is ideal for measuring incident daylight when mounted behind heavily smoked bezels used around displays or behind mirrors.

The device consumes minimum power. A dark current compensation circuit minimizes the effect of temperature dependent leakage currents in the absence of light, improving the light sensitivity at low lux levels. The output gain has been optimized to require a relatively low value external bias resistor that falls within recommended automotive EMI limits. The built-in 1µA op amp gives the ISL76671 an output voltage driving advantage for heavier loads that can drive an ADC directly.

The ISL76671 is housed in an ultra compact 2mmx2.1mm ODFN plastic surface mount package. Operation is rated from -40°C to +105°C, Grade 2 per AEC-Q100.

## Features

- Square root voltage output
- 0.01 lux to 100 lux range
- 1.8V to 3V supply range
- Close to human eye spectral response
- Fast response time
- Internal temperature compensation
- Good IR rejection
- Low supply current
- Operating temperature range -40°C to +105°C
- 6 Ld ODFN: 2mmx2.1mmx0.7mm
- Pb-free (RoHS compliant)
- AEC-Q100 Qualified

## Applications

- Display backlight control - central info display and instrumentation
- Anti-glare mirror systems - specified to operate behind Bezel mounting





FIGURE 1. SIMPLIFIED BLOCK DIAGRAM

# ISL76671

## Pin Configuration



## Pin Descriptions

PIN NUMBER	PIN NAME	PIN DESCRIPTION
1	VDD	Voltage Supply (1.8V to 3V).
2	GND	Ground
3, 5	NC	No connect
4	REXT	Connected to an external resistor to GND, setting the light-to-voltage scaling constant. A $R_{EXT}$ value of 100k $\Omega$ is recommended.
6	VOUT	Voltage Output.
-	PAD	Thermal Pad. The thermal pad can be connected to GND or electrically isolated.

## Ordering Information

PART NUMBER (Notes 1, 2, 3)	PACKAGE Tape and Reel (RoHS Compliant)	PKG. DWG. #
ISL76671AR0Z-T7	6 Ld ODFN (Tape and Reel)	L6.2X2.1
ISL76671AR0Z-T7A	6 Ld ODFN (Tape and Reel)	L6.2X2.1
ISL76671EVAL1Z	Evaluation Board	

### NOTES:

1. Please refer to [TB347](#) for details on reel specifications.
2. These Intersil Pb-free plastic packaged products employ special Pb-free material sets; molding compounds/die attach materials and NiPdAu plate -e4 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.
3. For Moisture Sensitivity Level (MSL), please see device information page for [ISL76671](#). For more information on MSL please see techbrief [TB477](#).

# ISL76671

## Absolute Maximum Ratings (T<sub>A</sub> = +25°C)

Supply Voltage Between V <sub>DD</sub> and GND	3.6V
R <sub>EXT</sub>	(-0.5V + GND) to (0.5V + V <sub>DD</sub> )
V <sub>OUT</sub>	(-0.5V + GND) to (0.5V + V <sub>DD</sub> )
V <sub>OUT</sub> Short Circuit Current	<10mA
ESD Rating	
Human Body Model (Tested per AEC-Q100-002)	2.5kV
Machine Model (Tested per AEC-Q100-003)	250V
Charged Device Model (Tested per AEC-Q100-011)	1kV
Latch-up (Tested per AEC-Q100-004, Class II, Level A)	100mA

## Thermal Information

Thermal Resistance (Typical)	θ <sub>JA</sub> (°C/W)	θ <sub>JC</sub> (°C/W)
6 Ld ODFN (Notes 4, 5)	88	7.94
Maximum Die Temperature	+105°C	
Storage Temperature	-40°C to +105°C	
Operating Temperature	-40°C to +105°C	
Pb-Free Reflow Profile (*)	see <a href="#">TB477</a>	
*Peak temperature during solder reflow +260°C max		

CAUTION: Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions may adversely impact product reliability and result in failures not covered by warranty.

### NOTES:

- θ<sub>JA</sub> is measured in free air with the component mounted on a high effective thermal conductivity test board with “direct attach” features. See Tech Brief [TB379](#).
- For θ<sub>JC</sub>, the “case temp” location is the center of the exposed metal pad on the package underside.

**Electrical Specifications** Unless otherwise noted, all parameter limits are established over the recommended operating conditions: V<sub>DD</sub> = 3V, T<sub>A</sub> = -40°C to +105°C, R<sub>EXT</sub> = 100kΩ, no load at V<sub>OUT</sub>, and green LED light. (Typical values are at T<sub>A</sub> = +25°C). **Boldface limits apply across the operating temperature range, -40°C to +105°C.**

PARAMETER	DESCRIPTION	TEST CONDITIONS	MIN (Note 6)	TYP	MAX (Note 6)	UNITS
E	Range of Input Light Intensity for Square Root Relationship to be Held			0.01 - 100		Lux
V <sub>DD</sub>	Operating Supply Voltage		<b>1.8</b>		<b>3</b>	V
I <sub>DD</sub>	Supply Current	E = 0 lux, -40°C to +60°C		0.7	2	μA
		E = 0 lux, -40°C to +105°C			5	μA
		E = 100 lux		23	<b>35</b>	μA
V <sub>OUT</sub>	Light-to-Voltage Accuracy	E = 10 lux		0.65		V
		E = 50 lux		1.35		V
		E = 100 lux	<b>1.4</b>	1.85	<b>2.3</b>	V
V <sub>DARK</sub>	Voltage Output in the Absence of Light	E = 0 lux, -40°C to +60°C		0.95	20	mV
		E = 0 lux, -40°C to +105°C			120	mV
ΔV <sub>OUT</sub>	Output Voltage Variation Over Three Light Sources: Fluorescent, Incandescent and Halogen			10		%
PSRR	Power Supply Rejection Ratio	E = 100 lux		0.12		mV/V
V <sub>O-CMPL</sub>	Maximum Output Compliance Voltage at 95% of Nominal Output			V <sub>DD</sub> - 0.7V		V
V <sub>O-MAX</sub>	Maximum Output Voltage Swing				V <sub>DD</sub>	V
t <sub>R</sub>	Rise Time	E = 0 lux to 100 lux		95		μs
t <sub>F</sub>	Fall Time	E = 100 lux to 0 lux		155		μs
t <sub>D</sub>	Delay Time for Rising Edge	E = 0 lux to 100 lux		350		μs
t <sub>S</sub>	Delay Time for Falling Edge	E = 100 lux to 0 lux		250		μs
ISC	Short Circuit Current of Op Amp			±12		mA
SR	Slew Rate of Op Amp			13		V/ms
V <sub>OS</sub>	Offset Voltage of Op Amp			±0.9		mV

### NOTE:

- Parameters with MIN and/or MAX limits are 100% tested at +25°C, unless otherwise specified. Temperature limits established by characterization and are not production tested.




FIGURE 2. TEST CIRCUIT FOR RISE/FALL TIME MEASUREMENT




FIGURE 3. TIMING DIAGRAM

## Typical Performance Curves

$V_{DD} = 3V$ ,  $T_A = +25^\circ C$ ,  $R_{EXT} = 100k\Omega$ , no load at  $V_{OUT}$ , green LED light, unless otherwise specified.




FIGURE 4. SPECTRAL RESPONSE




FIGURE 5. SPECTRUM OF FOUR LIGHT SOURCES NORMALIZED BY LUMINOUS INTENSITY (LUX)




FIGURE 6. RADIATION PATTERN




FIGURE 7.  $V_{DD}$  OPERATING RANGE (WHITE LED)

## Typical Performance Curves $V_{DD} = 3V$ , $T_A = +25^\circ C$ , $R_{EXT} = 100k\Omega$ , no load at $V_{OUT}$ , green LED light, unless otherwise specified.




FIGURE 8. OUTPUT VOLTAGE vs LIGHT INTENSITY 0.1 LUX TO 100 LUX




FIGURE 9. OUTPUT VOLTAGE vs LIGHT INTENSITY 0.01 LUX TO 5 LUX




FIGURE 10. OUTPUT VOLTAGE vs TEMPERATURE AT 0 LUX




FIGURE 11. SUPPLY CURRENT vs TEMPERATURE AT 0 LUX




FIGURE 12. NORMALIZED OUTPUT VOLTAGE vs SUPPLY VOLTAGE




FIGURE 13. SUPPLY CURRENT vs SUPPLY VOLTAGE

# ISL76671

**Typical Performance Curves**  $V_{DD} = 3V$ ,  $T_A = +25^\circ C$ ,  $R_{EXT} = 100k\Omega$ , no load at  $V_{OUT}$ , green LED light, unless otherwise specified.




FIGURE 14. SUPPLY CURRENT vs SUPPLY VOLTAGE




FIGURE 15. SUPPLY CURRENT vs SUPPLY VOLTAGE




FIGURE 16. NORMALIZED OUTPUT VOLTAGE vs TEMPERATURE




FIGURE 17. SUPPLY CURRENT vs TEMPERATURE




FIGURE 18. DELAY TIME vs LUX CHANGE FROM 0 LUX




FIGURE 19. DELAY TIME vs LUX CHANGE TO 0 LUX

## Application Information

### Light-to-Voltage Conversion

The ISL76671 has responsiveness that is a square root function of the light intensity intercepted by the photodiode in lux. Because the photodiode has a responsivity that resembles the human eye, conversion rate is independent of the light source (fluorescent light, incandescent light or direct sunlight).

$$V_{OUT} = \frac{18\mu A}{\sqrt{100\text{lux}}} \sqrt{E} \times R_{EXT} \quad (\text{EQ. 1})$$

In [Equation 1](#),  $V_{OUT}$  is the output voltage,  $E$  is the light intensity and  $R_{EXT}$  is the value of the external resistor. The  $R_{EXT}$  is used to set the light-to-voltage scaling constant. The compliance of the ISL76671's output circuit may result in premature saturation when an excessively large  $R_{EXT}$  is used. A  $R_{EXT}$  value of 100k $\Omega$  is recommended for automotive applications. The output compliance voltage is 700mV below the supply voltage as listed in  $V_{O-MAX}$  of the "Electrical Specifications" table on [page 3](#).

### Optical Sensor Location Outline

The green area in [Figure 20](#) shows the optical sensor location outline of ISL76671. Along the pinout direction, the center line (CL) of the sensor coincides with that of the packaging. The sensor width in this direction is 0.39mm. Perpendicular to the pinout direction, the CL of the sensor has an 0.19mm offset from the CL of packaging away from pin 1. The sensor width in this direction is 0.46mm.




FIGURE 20. 6 LD ODFN SENSOR LOCATION OUTLINE



## Revision History

The revision history provided is for informational purposes only and is believed to be accurate, but not warranted. Please go to web to make sure you have the latest revision.

DATE	REVISION	CHANGE
April 20, 2015	FN7716.3	<p>Changed AEC Q100 to AEC-Q100</p> <p>Updated ordering information on page 2 by adding T7A part and Evaluation Board.</p> <p>Updated ESD Ratings in "Absolute Maximum Ratings (<math>T_A = +25^\circ\text{C}</math>)" on page 3 as follows:  <b>From:</b> Human Body Model (Tested per JESD22-A114E) . . . . . 3kV            Machine Model (Tested per JESD22-A115C) . . . . . 300V            Charged Device Model (Tested per JESD22-C101E) . . . . . 1kV            Latch Up (Tested per JESD78C) . . . . . 100mA  <b>To:</b> Human Body Model (Tested per AEC-Q100-002) . . . . . 2.5kV            Machine Model (Tested per AEC-Q100-003) . . . . . 250V            Charged Device Model (Tested per AEC-Q100-011) . . . . . 1kV            Latch-up (Tested per AEC-Q100-004, Class II, Level A) . . . . . 100mA</p> <p>Updated POD L6.2x2.1 to current rev with changes as follows:            Changed Note 5 From: Tiebar shown (if present) is a non-functional feature.            To: Tiebar shown (if present) is a non-functional feature and maybe located on any of the 4 sides (or ends).            Updated Arrows to correct arrow type</p> <p>Updated datasheet with current Intersil standards.</p>
December 23, 2013	FN7716.2	<p>Page 8            - 2nd line of the disclaimer changed from:            "Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted"            to:            "Intersil Automotive Qualified products are manufactured, assembled and tested utilizing TS16949 quality systems as noted"</p>
December 12, 2011	FN7716.1	<p>"Thermal Information" on page 3, changed from:  <b>Pb-Free Reflow Profile (*)</b> ..... see TB487            *Peak temperature during solder reflow +235 °C max  <b>To</b>  <b>Pb-Free Reflow Profile (*)</b> ..... see TB477            *Peak temperature during solder reflow +260 °C max</p> <p>"Electrical Specifications" on page 3:            Added Min value of 1.4V and Max value of 2.3V for <math>V_{OUT}</math> where e = 100 lux</p>
October 19, 2011	FN7716.0	Initial Release

## About Intersil

Intersil Corporation is a leading provider of innovative power management and precision analog solutions. The company's products address some of the largest markets within the industrial and infrastructure, mobile computing and high-end consumer markets.

For the most updated datasheet, application notes, related documentation and related parts, please see the respective product information page found at [www.intersil.com](http://www.intersil.com).

You may report errors or suggestions for improving this datasheet by visiting [www.intersil.com/ask](http://www.intersil.com/ask).

Reliability reports are also available from our website at [www.intersil.com/support](http://www.intersil.com/support)

For additional products, see [www.intersil.com/en/products.html](http://www.intersil.com/en/products.html)

Intersil Automotive Qualified products are manufactured, assembled and tested utilizing TS16949 quality systems as noted in the quality certifications found at [www.intersil.com/en/support/qualandreliability.html](http://www.intersil.com/en/support/qualandreliability.html)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*






For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)

## Package Outline Drawing

### L6.2x2.1

6 LEAD OPTICAL DUAL FLAT NO-LEAD PLASTIC PACKAGE (ODFN)

Rev 4, 2/15



**NOTES:**

1. Dimensions are in millimeters.  
Dimensions in ( ) for Reference Only.
2. Dimensioning and tolerancing conform to ASME Y14.5m-1994.
3. Unless otherwise specified, tolerance: Decimal  $\pm 0.05$
4. Dimension applies to the metallized terminal and is measured between 0.15mm and 0.30mm from the terminal tip.
5. Tiebar shown (if present) is a non-functional feature and maybe located on any of the 4 sides (or ends).
6. The configuration of the pin #1 identifier is optional, but must be located within the zone indicated. The pin #1 identifier may be either a mold or mark feature.