



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





HiPerFET™
Power MOSFET

in High Voltage ISOPLUS i4-PAC™

$$I_{D25} = 22 \text{ A}$$

$$V_{DSS} = 1000 \text{ V}$$

$$R_{DSon} = 390 \text{ m}\Omega$$


MOSFET

Symbol	Conditions	Maximum Ratings	
V_{DSS}	$T_{VJ} = 25^{\circ}\text{C to } 150^{\circ}\text{C}$	1000	V
V_{GS}		± 20	V
I_{D25}	$T_C = 25^{\circ}\text{C}$	22	A
I_{D90}	$T_C = 90^{\circ}\text{C}$	15	A
I_{F25}	(diode) $T_C = 25^{\circ}\text{C}$	120	A
I_{F90}	(diode) $T_C = 90^{\circ}\text{C}$	75	A
dv/dt	$V_{DS} < V_{DSS}; I_F \leq 100\text{A}; di_F/dt \leq 100\text{A}/\mu\text{s}; R_G = 2 \Omega$ $T_{VJ} = 150^{\circ}\text{C}$	5	V/ns
E_{AR}	$T_C = 25^{\circ}\text{C}$	64	mJ

Symbol	Conditions	Characteristic Values		
		$(T_{VJ} = 25^{\circ}\text{C, unless otherwise specified})$		
		min.	typ.	max.
R_{DSon}	$V_{GS} = 10 \text{ V}; I_D = I_{D90}$			390 m Ω
V_{GSth}	$V_{DS} = 20 \text{ V}; I_D = 8 \text{ mA};$	2.5		5 V
I_{DSS}	$V_{DS} = V_{DSS}; V_{GS} = 0 \text{ V}; T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$		0.25	0.1 mA mA
I_{GSS}	$V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$			200 nA
Q_g Q_{gs} Q_{gd}	$V_{GS} = 10 \text{ V}; V_{DS} = 500 \text{ V}; I_D = 12 \text{ A}$		250	nC
			55	nC
			135	nC
$t_{d(on)}$ t_r $t_{d(off)}$ t_f	$V_{GS} = 10 \text{ V}; V_{DS} = 500 \text{ V};$ $I_D = 12 \text{ A}; R_G = 1 \Omega$		35	ns
			35	ns
			75	ns
			21	ns
V_F	(diode) $I_F = 12 \text{ A}; V_{GS} = 0 \text{ V}$			1.5 V
t_{rr}	(diode) $I_F = 24 \text{ A}; -di/dt = 100 \text{ A}/\mu\text{s}; V_{DS} = 100 \text{ V}$	250		ns
R_{thJC}				0.32 K/W

Features

- HiPerFET™ technology
 - low R_{DSon}
 - low gate charge for high frequency operation
 - unclamped inductive switching (UIS) capability
 - dv/dt ruggedness
 - fast intrinsic reverse diode
- ISOPLUS i4-PAC™ high voltage package
 - isolated back surface
 - enlarged creepage towards heatsink
 - enlarged creepage between high voltage pins
 - application friendly pinout
 - high reliability
 - industry standard outline

Applications


- switched mode power supplies
- DC-DC converters
- resonant converters

Component

Symbol	Conditions	Maximum Ratings
T_{VJ}		-55...+150 °C
T_{stg}		-55...+125 °C
V_{ISOL}	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$	2500 V~
F_c	mounting force with clip	20...120 N

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
d_s, d_A	D pin - S pin	7.0		mm
d_s, d_A	pin - backside metal	5.5		mm
R_{thCH}	with heatsink compound		0.15	K/W
Weight			9	g

Dimensions in mm (1 mm = 0.0394")






Fig. 1. Output Characteristics @ 25°C




Fig. 2. Extended Output Characteristics @ 25°C




Fig. 3. Output Characteristics @ 125°C




Fig. 4. $R_{DS(on)}$ Normalized to $I_D = 12$ A Value versus Junction Temperature




Fig. 5. $R_{DS(on)}$ Normalized to $I_D = 12$ A Value versus Drain Current




Fig. 6. Max. Drain Current vs. Case Temperature

