



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## PolarP™ Power MOSFET

## IXTK40P50P IXTX40P50P


$$\begin{aligned} V_{DSS} &= -500V \\ I_{D25} &= -40A \\ R_{DS(on)} &\leq 230m\Omega \end{aligned}$$

P-Channel Enhancement Mode  
Avalanche Rated




| Symbol        | Test Conditions                                                          | Maximum Ratings            |                  |
|---------------|--------------------------------------------------------------------------|----------------------------|------------------|
| $V_{DSS}$     | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$                          | - 500                      | V                |
| $V_{DGR}$     | $T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$ , $R_{GS} = 1M\Omega$    | - 500                      | V                |
| $V_{GSS}$     | Continuous                                                               | $\pm 20$                   | V                |
| $V_{GSM}$     | Transient                                                                | $\pm 30$                   | V                |
| $I_{D25}$     | $T_C = 25^\circ\text{C}$                                                 | - 40                       | A                |
| $I_{DM}$      | $T_C = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$               | - 120                      | A                |
| $I_A$         | $T_C = 25^\circ\text{C}$                                                 | - 40                       | A                |
| $E_{AS}$      | $T_C = 25^\circ\text{C}$                                                 | 3.5                        | J                |
| $dv/dt$       | $I_S \leq I_{DM}$ , $V_{DD} \leq V_{DSS}$ , $T_J \leq 150^\circ\text{C}$ | 10                         | V/ns             |
| $P_D$         | $T_C = 25^\circ\text{C}$                                                 | 890                        | W                |
| $T_J$         |                                                                          | -55 ... +150               | $^\circ\text{C}$ |
| $T_{JM}$      |                                                                          | 150                        | $^\circ\text{C}$ |
| $T_{stg}$     |                                                                          | -55 ... +150               | $^\circ\text{C}$ |
| $T_L$         | Maximum Lead Temperature for Soldering                                   | 300                        | $^\circ\text{C}$ |
| $T_{SOLD}$    | 1.6 mm (0.062in.) from Case for 10s                                      | 260                        | $^\circ\text{C}$ |
| $M_d$         | Mounting Force (PLUS247)<br>Mounting Torque (TO-264)                     | 20..120/4.5..27<br>1.13/10 | N/lb<br>Nm/lb.in |
| <b>Weight</b> | PLUS247<br>TO-264                                                        | 6<br>10                    | g<br>g           |

TO-264 (IXTK)



PLUS247 (IXTX)



G = Gate      D = Drain  
S = Source    Tab = Drain

### Features

- International Standard Packages
- Rugged PolarP™ Process
- Avalanche Rated
- Fast Intrinsic Diode
- Low Package Inductance

### Advantages

- Easy to Mount
- Space Savings
- High Power Density

### Applications

- High-Side Switches
- Push Pull Amplifiers
- DC Choppers
- Automatic Test Equipment
- Current Regulators

| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified) | Characteristic Values |      |                               |
|--------------|-----------------------------------------------------------------------------|-----------------------|------|-------------------------------|
|              |                                                                             | Min.                  | Typ. | Max.                          |
| $BV_{DSS}$   | $V_{GS} = 0V$ , $I_D = -250\mu A$                                           | - 500                 |      | V                             |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = -1mA$                                            | - 2.0                 |      | - 4.5 V                       |
| $I_{GSS}$    | $V_{GS} = \pm 20V$ , $V_{DS} = 0V$                                          |                       |      | $\pm 100$ nA                  |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$ , $V_{GS} = 0V$<br>$T_J = 125^\circ\text{C}$             |                       |      | - 50 $\mu A$<br>- 250 $\mu A$ |
| $R_{DS(on)}$ | $V_{GS} = -10V$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                        |                       |      | 230 m $\Omega$                |


| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)                                                                         | Characteristic Values |      |                    |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|--------------------|
|              |                                                                                                                                                     | Min.                  | Typ. | Max.               |
| $g_{fs}$     | $V_{DS} = -10\text{V}$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                                                                                         | 23                    | 38   | S                  |
| $C_{iss}$    | $V_{GS} = 0\text{V}$ , $V_{DS} = -25\text{V}$ , $f = 1\text{MHz}$                                                                                   |                       | 11.5 | nF                 |
| $C_{oss}$    |                                                                                                                                                     |                       | 1150 | pF                 |
| $C_{rss}$    |                                                                                                                                                     |                       | 93   | pF                 |
| $t_{d(on)}$  | <b>Resistive Switching Times</b><br>$V_{GS} = -10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 0.5 \cdot I_{D25}$<br>$R_G = 1\Omega$ (External) |                       | 37   | ns                 |
| $t_r$        |                                                                                                                                                     |                       | 59   | ns                 |
| $t_{d(off)}$ |                                                                                                                                                     |                       | 90   | ns                 |
| $t_f$        |                                                                                                                                                     |                       | 34   | ns                 |
| $Q_{g(on)}$  | $V_{GS} = -10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 0.5 \cdot I_{D25}$                                                                   |                       | 205  | nC                 |
| $Q_{gs}$     |                                                                                                                                                     |                       | 55   | nC                 |
| $Q_{gd}$     |                                                                                                                                                     |                       | 75   | nC                 |
| $R_{thJC}$   |                                                                                                                                                     |                       | 0.14 | $^\circ\text{C/W}$ |
| $R_{thCS}$   |                                                                                                                                                     | 0.15                  |      | $^\circ\text{C/W}$ |

## Source-Drain Diode

| Symbol   | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)                              | Characteristic Values |      |               |
|----------|----------------------------------------------------------------------------------------------------------|-----------------------|------|---------------|
|          |                                                                                                          | Min.                  | Typ. | Max.          |
| $I_S$    | $V_{GS} = 0\text{V}$                                                                                     |                       |      | - 40 A        |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$                                                              |                       |      | -160 A        |
| $V_{SD}$ | $I_F = -20\text{A}$ , $V_{GS} = 0\text{V}$ , Note 1                                                      |                       |      | - 3.0 V       |
| $t_{rr}$ | $I_F = -20\text{A}$ , $-di/dt = -150\text{A}/\mu\text{s}$<br>$V_R = -100\text{V}$ , $V_{GS} = 0\text{V}$ |                       | 477  | ns            |
| $Q_{RM}$ |                                                                                                          |                       | 14.5 | $\mu\text{C}$ |
| $I_{RM}$ |                                                                                                          |                       | - 61 | A             |


Note 1: Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .

## TO-264 AA Outline



| Dim. | Millimeter |       | Inches   |       |
|------|------------|-------|----------|-------|
|      | Min.       | Max.  | Min.     | Max.  |
| A    | 4.82       | 5.13  | .190     | .202  |
| A1   | 2.54       | 2.89  | .100     | .114  |
| A2   | 2.00       | 2.10  | .079     | .083  |
| b    | 1.12       | 1.42  | .044     | .056  |
| b1   | 2.39       | 2.69  | .094     | .106  |
| b2   | 2.90       | 3.09  | .114     | .122  |
| c    | 0.53       | 0.83  | .021     | .033  |
| D    | 25.91      | 26.16 | 1.020    | 1.030 |
| E    | 19.81      | 19.96 | .780     | .786  |
| e    | 5.46 BSC   |       | .215 BSC |       |
| J    | 0.00       | 0.25  | .000     | .010  |
| K    | 0.00       | 0.25  | .000     | .010  |
| L    | 20.32      | 20.83 | .800     | .820  |
| L1   | 2.29       | 2.59  | .090     | .102  |
| P    | 3.17       | 3.66  | .125     | .144  |
| Q    | 6.07       | 6.27  | .239     | .247  |
| Q1   | 8.38       | 8.69  | .330     | .342  |
| R    | 3.81       | 4.32  | .150     | .170  |
| R1   | 1.78       | 2.29  | .070     | .090  |
| S    | 6.04       | 6.30  | .238     | .248  |
| T    | 1.57       | 1.83  | .062     | .072  |

## PLUS247™ Outline



Terminals: 1 - Gate  
2 - Drain  
3 - Source


| Dim. | Millimeter |       | Inches   |      |
|------|------------|-------|----------|------|
|      | Min.       | Max.  | Min.     | Max. |
| A    | 4.83       | 5.21  | .190     | .205 |
| A1   | 2.29       | 2.54  | .090     | .100 |
| A2   | 1.91       | 2.16  | .075     | .085 |
| b    | 1.14       | 1.40  | .045     | .055 |
| b1   | 1.91       | 2.13  | .075     | .084 |
| b2   | 2.92       | 3.12  | .115     | .123 |
| C    | 0.61       | 0.80  | .024     | .031 |
| D    | 20.80      | 21.34 | .819     | .840 |
| E    | 15.75      | 16.13 | .620     | .635 |
| e    | 5.45 BSC   |       | .215 BSC |      |
| L    | 19.81      | 20.32 | .780     | .800 |
| L1   | 3.81       | 4.32  | .150     | .170 |
| Q    | 5.59       | 6.20  | .220     | .244 |
| R    | 4.32       | 4.83  | .170     | .190 |

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.


IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents:

|           |           |           |           |              |              |              |              |              |             |
|-----------|-----------|-----------|-----------|--------------|--------------|--------------|--------------|--------------|-------------|
| 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665    | 6,404,065 B1 | 6,683,344    | 6,727,585    | 7,005,734 B2 | 7,157,338B2 |
| 4,860,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123 B1 | 6,534,343    | 6,710,405 B2 | 6,759,692    | 7,063,975 B2 |             |
| 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728 B1 | 6,583,505    | 6,710,463    | 6,771,478 B2 | 7,071,537    |             |


**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 3. Output Characteristics @  $T_J = 125^\circ\text{C}$**




**Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = -20\text{A}$  Value vs. Junction Temperature**




**Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = -20\text{A}$  Value vs. Drain Current**




**Fig. 6. Maximum Drain Current vs. Case Temperature**




**Fig. 7. Input Admittance**




**Fig. 8. Transconductance**




**Fig. 9. Forward Voltage Drop of Intrinsic Diode**



**Fig. 10. Gate Charge**



**Fig. 11. Capacitance**



**Fig. 12. Forward-Bias Safe Operating Area**




Fig. 13. Maximum Transient Thermal Impedance

