## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Potentiometers

		Resistive Element	Power (watts)	Resistive Range (ohms)	Tolerance	Resistance Taper (Law)	Body Dimension	Shaft	Bushing	Terminals
	) POT	TENTIOMETER	RS ■ INI	DUSTRIA	L					
	470	Conductive plast	c 0.5	150-5 meg	±10%, ±20	% Linear Non-Linear	15/16" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	PC Solder lug Wire-wrap
53		Conductive plast		50-5 meg	±10%, ±20	% Linear Non-Linear	1" dia.	Plain, Slotted Flatted Knurled 1/4 " dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
	-	Note: 53 Series a	vailable with	rotary switc	hes.					
J (F (2R	RV4) RV7)	Carbon compositio	on 2.25	50-5 meg	±10, ±20%	6 Linear Non-Linear	1.156" dia.	Plain, Slotted Flatted 1/4" dia. Metal	Plain Locking Watertight 3/8 " dia. Metal	Solder lug
+ -		Note: J Series ava	ilable as Bri	idged-T, Brid	ged-H, L an	d Straight-T atten	uators.	44		
	EJ 380	Conductive plast	c 2.0	Extra lon 50-5 meg	g life versio ±10%, ±20	n of J, with single % Linear Non-Linear	e or dual confi 1" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
230		Note: 380 Series	available wit	h rotary swit	ches. 100,0	100 cycle life.				
(A)	381	Conductive plast	c 1.0	100-5 meg	±10, ±20%	6 Linear Non-Linear	5/8" dia.	Plain, Slotted Flatted Knurled 1/8" dia. Metal	Plain Locking 1/4" dia. Metal	Solder lug Wire wrap
C. T. C.	0	Note: 381 Series	available wit	th rotary mor	nentary and	alternate action s	switches.			
E	485	Conductive plast	c 2.0	50-5 meg	±10, ±20%	6 Linear Non-Linear	1" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
555	15	Note: 485 Series I	nas rotationa	al life of +1,0	00,000 cycle	es.				
Mili	tary		•	vides Mi ed in th	• •	roducts incl	uding, bu	ıt not limit	ed to th	e following
<i>/////////////////////////////////////</i>	Indu	istrial	Boai	rd Washabl	e .	Wirewo	und .	Trimme	er <u>.</u>	Resistor
	Series Series 382(R	53(RV4) ; J(RV4) (V6), 392(RV6) and W(RV6)	Seri	92 (RV6 & R es 382(RV6) G (RV6) W(RV6)	V8)	Series 43 (I Series 58(F		Series R(R	J11)	Series RW

## Call 800-874-1874 or Fax 800-223-5138