

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







MALLORY Mallory Sonalert Products, Inc.				Part #: JT028-RG-CS		
Sales Outline Drawing				Revision:	В	
Specifications:						
Stack Number:	1	2				
LED Color:	RED	GREEN				
Connection Wires:	Red and Brown	Green and Brown				
LED Current Draw:	<50mA	<40mA	24.1/4.0/D/	3		
Rated Voltage:			24 VAC/D0 20-28 VAC/I			
Operating Voltage: Total Max Current:	_	<90mA				
Operating Temperatu	Iro.	-25° ~ +60°C				
Lens Color:			Opaque Wh			
Material:						
Mounting Method: Stainless Steel Pole						
Weight Typical (g): 580						
NEMA 12:						
Options:			Please contact f	actory.		
Dimensions: Inc	hes (mm)	cUL Recognized			ROHS Compliant	
3.8 [95.4]						
/—RED						
					\neg	
					/ /	
		48"/				
\				GASKET	wire	
	GREEN					
		—16.7 [423.2]———				
ſ				Ø0.20 [Ø5.2]	Ø0.57 [Ø14.6]	
2.4 [61.8]		3 places / for wires				
		#10 or 5mm screws for				
		mounting				
2.4	[61.8]			\vee	2.04 [51.9]	
			-	F0.39 [9.9] (b)		
			-	0.95 [24.3]	0.95 [24.3]	
- 2.7 [68.3] 						
TOP VIEW			MOUNTING DIAGRAM			
LED OPERATION: CC	NNECT STACK COL	OR WIRE TO POWER A	ND BROWN WI	RE TO POWER.		