

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Part #: **Mallory Sonalert Products, Inc.** JT028-RYGB-CS **Sales Outline Drawing** Revision: B Specifications: Stack Number: 2 3 4 LED Color: **RED** YELLOW GREEN **BLUE** Connection Wires: Red and Brown Yellow and Brown Green and Brown Blue and Brown LED Current Draw: <50mA <60mA <40mA <50mA Rated Voltage: 24 VAC/DC Operating Voltage: 20-28 VAC/DC Total Max Current: <200mA Operating Temperature: -25° ~ +60°C Lens Color: Opaque White ABS FR15U Material: Mounting Method: Stainless Steel Pole Weight Typical (g): 670 NEMA 12: Approved Options: Please contact factory **cUL** Recognized **ROHS Compliant Dimensions:** Inches (mm) 6.7 [171.1] RED GREEN 48 GASKET YELLOW BLUE -19.6 [498.9] Ø0.57 [Ø14.6] for wires Ø0.20 [Ø5.2] #10 or 5mm screws for mounting 2.4 [61.8] 2.04 [51.9] T0.39 [9.9] 0.95 [24.3] 0.95 [24.3] 2.7 [68.3] MUUNTING TOP VIEW LED OPERATION: CONNECT STACK COLOR WIRE TO POWER AND BROWN WIRE TO POWER.