

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









### Is Now Part of



# ON Semiconductor®

# To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to Fairchild <a href="guestions@onsemi.com">guestions@onsemi.com</a>.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



June 2014

# KA78RH33R Low Dropout Voltage Regulator


### **Features**

- Fixed Output Voltage of +3.3 V
- · Space-Saving SMD Types of DPAK
- 1 V (Typical) Dropout at I<sub>O</sub> = 800 mA
- · Output Current: 800 mA
- · Thermal Shutdown Protection
- · Over-Current Protection
- Output Trimmed to ±1% Tolerance
- · No Minimum Load Requirement

## **Description**

The KA78RH33 is a +3.3V, fixed, low dropout voltage regulator specifically designed for use in low-voltage operation. The maximum load current is 0.8 A and the dropout voltage is guaranteed to be 1 V (typical). The dropout voltage varies with load current. The regulator consists of composite PNP-NPN pass transistors.





D-PAK Unit Orientation

# **Ordering Information**

Part Number	Operating Tem- perature Range	Top Mark	Package	Packing Method
KA78RH33RTF	-25°C to +125°C	KA78RH33	TO-252 3L (DPAK)	Tape and Reel
KA78RH33RTM	-25°C to +125°C	KA78RH33	TO-252 3L (DPAK)	Tape and Reel

<sup>\*</sup> Refer to above unit orientation figure for TM / TF suffix packing.

### **Block Diagram**




Figure 1. Block Diagram

1

# **Absolute Maximum Ratings**

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. Values are at  $T_A = 25$ °C unless otherwise noted.

Symbol	Parameter	Value	Unit
V <sub>IN</sub>	Power Supply Input Voltage	15	V
I <sub>O</sub>	Output Load Current	800	mA
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>OPR</sub>	Operating Junction Temperature	-25 to 125	°C
T <sub>STG</sub>	Storage Temperature	-55 to 150	°C

## **Temperature Characteristics**

Symbol	Parameter	Value	Unit
$\Delta V_{O} / \Delta T$	Temperature Coefficient of Output Voltage	±0.02	%/ °C

### **Thermal Characteristics**

Values are at  $T_A = 25$ °C unless otherwise noted.

Symbol	Parameter	Value	Unit
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	110	°C/W

### **Electrical Characteristics**

Refer to the test circuit, values are at  $V_{IN}$  = 5 V,  $C_{O}$  = 10  $\mu$ F, and  $T_{A}$  = 25°C,unless otherwise specified.

Symbol	Parameter	Conditions	Min.	Тур.	Max.	Unit
V <sub>OUT</sub>	Output Voltage	I <sub>O</sub> = 10 mA, T <sub>J</sub> = 25°C	3.27	3.30	3.33	V
V <sub>OUT</sub>	Output Voltage	$V_{IN} = 4.8 \text{ V to } 12 \text{ V},$ $I_{O} = 10 \text{ mA to } 800 \text{ mA},$ $T_{J} = -25^{\circ}\text{C to } 125^{\circ}\text{C}$	3.23	3.30	3.37	V
R <sub>line</sub>	Line Regulation	$V_{IN}$ = 4.8 V to 12 V, $I_{O}$ = 10 mA		1	10	mV
R <sub>load</sub>	Load Regulation	I <sub>O</sub> = 10 mA to 800 mA		1	20	mV
RR	Ripple Rejection	$f = 120 \text{ Hz}, I_O = 500 \text{ mA},$ $V_{IN} = 6.3 \pm 1 \text{ Vrms}$	55			dB
		I <sub>O</sub> = 100 mA		1.00	1.20	
$V_{drop}$	Dropout Voltage	I <sub>O</sub> = 500 mA		1.05	1.25	V
		I <sub>O</sub> = 800 mA		1.10	1.40	
Iq	Quiescent Current	V <sub>IN</sub> ≤ 12 V		5	10	mA
ΔV <sub>O</sub> / ΔΤ	Temperature Coefficient of Output Voltage	$T_J = -25^{\circ}\text{C to } 125^{\circ}\text{C},$ $I_O = 10 \text{ mA}$		0.2		mV/°C
I <sub>pk</sub>	Peak Output Current	V <sub>IN</sub> = 6.3 V	800			mA
V <sub>n</sub>	Output Noise Voltage	f = 10 Hz to 10 kHz		100		μVrms

# **Typical Application**




Figure 2. Typical Application<sup>(1)</sup>

### Note:

1. An input capacitor,  $C_{\text{IN}}$  is not necessary for stability, but improves the overall performance.

# **Physical Dimensions** TO-252 3L (DPAK) 6.80 6.40 Α - 5.55 MIN → F 0.90 6.50 MIN 2.90 2.50 С 0.96 MAX (0.64 LAND PATTERN RECOMMENDATION 4.83 MIN (6.80)SEE DETAIL A F 9.80 9.20 ○ 0.10 B **GAGE PLANE** F\1.02 NOTES:UNLESS OTHERWISE SPECIFIED I:UNLESS OTHERWISE SPECIFIED NOT COMPLIANT TO JEDEC TO-252 VARIATION AB ALL DIMENSION ARE IN MILLIMETER DIMENSIONS ARE EXCLUSIVE OF BURRS,MOLD FLASH, AND TIE BAR EXTRUSIONS LAD PATTERN PER IPC7351A ATANDARD TO228P991X239-3N DRAWING FILE NAME:MKT-TO252D03REV3. DOES NOT COMPLY JEDEC STANDARD VALUE. FAIRCHILD SEMICONDUCTOR. 0.127 MAX SEATING PLANE

Figure 3. 3-Lead, TO-252, JEDEC TO-252 VAR. AB, SURFACE MOUNT (DPAK)

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings: <a href="http://www.fairchildsemi.com/dwg/TO/TO252D03.pdf">http://www.fairchildsemi.com/dwg/TO/TO252D03.pdf</a>.

For current tape and reel specifications, visit Fairchild Semiconductor's online packaging area: <a href="http://www.fairchildsemi.com/packing\_dwg/PKG-TO252D03.pdf">http://www.fairchildsemi.com/packing\_dwg/PKG-TO252D03.pdf</a>.





#### **TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

F-PFS™ AccuPower™ AX-CAP®, FRFET® RitSiC™ Global Power Resource<sup>SM</sup> GreenBridge™ Build it Now™  $\mathsf{CorePLUS}^{\mathsf{TM}}$ Green FPS™ CorePOWFR™ Green FPS™ e-Series™ CROSSVOLT™ Gmax™ GTO™ CTL™

CILI™ GTO™

Current Transfer Logic™ IntelliMAX™

DEUXPEED® ISOPLANAR™

ISOPLANAR™

Dual Cool  $^{\text{IM}}$  Making Small Speakers Sound Louder EcoSPARK $^{\otimes}$  and Better  $^{\text{IM}}$ 

ECOSPARK

and Better™

EfficientMax™

ESBC™

MicROCOUPLER™

MicroFak™

MicroPak™

Fairchild®

Fairchild Semiconductor®

MilarDrive™

Fairchild Semiconductor
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™

MillerDrive™
MotionMax™
mWSaver®
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®

PowerTrench<sup>®</sup> PowerXS™

Programmable Active Droop™

QFET<sup>®</sup> QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™

SignalWise™ SmartMax™ SMART START™

Solutions for Your Success™

SPM<sup>®</sup>
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®

SyncFET™ Sync-Lock™ SYSTEM GENERAL®\*

TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®\*\*

μSerDes<sup>TM</sup>
SerDes<sup>TM</sup>
UHC<sup>®</sup>
Ultra FRFET<sup>TM</sup>
UniFET<sup>TM</sup>
VCX<sup>TM</sup>

Ultra FRFET™ UniFET™ VCX™ VisualMax™ VoltagePlus™ XS™ 仙童™

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN, NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

#### As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

### PRODUCT STATUS DEFINITIONS

### **Definition of Terms**

Datasheet Identification		Definition		
Preliminary First Production  No Identification Needed Full Production		Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
		Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
		Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. 168

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdf/Patent-Marking.pdf">www.onsemi.com/site/pdf/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

Phone: 421 33 790 2910

Japan Customer Focus Center

Phone: 81–3–5817–1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative