imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



	1	1 2		3			3	4			5			6	7		
Α		Wire	Spec	UL2725 (7/0.127TC*1P+D+AL+MYLAR)*2+ 7/0.127T*1P+7/0.20T*2C+F+ADB													A
	Cores			2P			1P	2C									
			AWG	28AWG	à		28AWG	24AWG							• • • •		
В			Material	Tinned Copper		Tinne	inned Copper Tinned Copper			Outer Jackter				ter			
		Conducto	r Construction	7/0.127±0.004mm		7/0.1	/0.127±0.004mm 7/0.2±0.004mm			Braid						в	
			O.D	0.38mm (REF)		0.38	38mm (REF) 0.60mm (REF)			AL/MYLAR UTP Conductor							
			Thickness	0.26mm (REF)		0.23	.23mm (REF) 0.25mm (REF)			AL/MILAR Conductor							
С		Insulation		0.90±0.05mm Yellow,Blue,Orange,Purple Foamed PE		0.84	±0.05mm 1	1.10±0.05mm									
						WHI	ITE,GREEN I	RED,BLACK						×_/	-Insulation		
								SR-PVC			AL Foil					C	
		— :	Filler			FIL	FILLER										
		Filler									1 D	Nire color	assignme	nt			
D		Braid	Material	AL-MG						Red White O Green							
			Construction	16/6/0.12mm													D
		Shield	AL foil	Color :Blue						Black							
		Shield	MYLAR	White									Black	<u> </u>			
E		Material	Tinned Copper									/ Yellow Drain	<u>) </u>				
	2	Drain Outer	Construction Material	7/0.127T						3 <u>Drain</u> Purple Orange							E
			O.D	80°C PVC 80P 5.5±0.20mm													
		Jacket Color		Black									Shield+Braid				
		Font	Color	White													
F	2	© Print: 24AWG/2C c AWM I/II A 80°C 30∨ FT1 USB CABLE Packing: 305M/Reel														F	
G	RoH	RoHS compliant			Free							Date	Name	Customer-No.			
	Unit:mm			TOLER	TOLERANCE						Drawn	26.01.2018	Winnie	-			
														ASSMANN WSW			G
					Correct Brown to Pur	ple	06.09.2018		Approved	29.08.2018	Winnie	ASSIMAININ WSW	KAB 6	641			
н				② Update ① Update			29.08.2018	8 Yavior				Drawing-No.					
		DIM	TOL				07.08.2018			SSMAN				rev03	3		
				0	Drawn 26.01		26.01.2018							10100	H		
		Angle	TOL	ld.	Modification D		Date	Name			nents	Replace	Sheet 1 /				
	1	1 2			3			4	4	5				6	7		CAB0844