



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





| Pos. 1 | Designate |
|--------|-----------|
| Pin #1 | Location  |



### CIRCUIT 9 POSITION

## NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC. (Switch)  
100mA @50VDC. (Carry)


## 5. CONTACT MATERIAL:

CONTACTS: (MOVABLE) Copper w/Gold Plate

TERMINALS: BRASS w/Gold Plate

6. INSULATION RESISTANCE;  
100 Mega-OHMS min. @500VDC
7. CONTACT RESISTANCE;  
50 MILLI-OHMS typical @2-4VDC @100mA
8. OPERATING TEMP.:-  
-40°C to +80°C
9. PACKAGE: IN DISPENSING TUBES  
WITH ALL POLES IN THE "OFF" POSITION.

RECOMMENDED P.C.B. LAYOUT



|  |         |                         |        |      |
|--|---------|-------------------------|--------|------|
| RECOMMENDED P.C.B. LAYOUT  |         |                         |        |      |
|  |         |                         |        |      |
| A  | 12540   | RELEASED FOR PRODUCTION | 7/1/02 | CJB  |
| REV.   | ECN No. | DESCRIPTION             | DATE   | CHKD |
| THE INFORMATION CONTAINED IN THIS DOCUMENT<br>IS PROPRIETARY TO E-SWITCH AND IS<br>NOT TO BE COPIED OR TRANSFERRED |         |                         |        |      |

|   |        |     |         |     |
|---|--------|-----|---------|-----|
| <b>E-SWITCH®</b>                                    |        |     |         |     |
| TITLE<br>KAJ09 SG GT (GOLD)<br>LOW PROFILE W/D TAPE |        |     |         |     |
| SCALE   | DATE   | DR  | DWG     | REV |
| 2:1   | 7/1/02 | CJB | W825229 | A   |