

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









KFM KFK025790



* KFM-2/FE 5D 3C Lg

KFM has a sturdy all-metal construction with a sleek design, flexible arm and excellent light output suitable for a variety of industrial, laboratory, cosmetology and low-vision applications. The flexibility of the neck assembly and patented internal spring 30" K-arm makes exact wishing easy: \$1.72554 (2.25X) lens. Weighted base. Color: Light grey.







| Optic | |
|------------------------|---------------|
| Color of reflector | White |
| Material of diffuser | Polycarbonate |
| Primary Lens (D) | 5 |
| Working distance (mm) | 200 |
| Material of reflector | PC |
| Magnification (X) | 2.25 |
| Electrical data | |
| Maximum frequency (Hz) | 6 0 |
| Minimum frequency (Hz) | 5 0 |
| Maximum voltage (V) | 1 2 0 |
| Voltage from (V) | 1 0 0 |
| Body | |
| Body color | Grey |
| Body material | Aluminum |
| Technical data | |
| IP classification | 2 0 |
| | |



| Lightsource | |
|---------------------------------|-----------------|
| Number of lamps | 1 |
| Lamp power (W) | 2 2 |
| Lamp base | G10Q |
| CRI and/or Color Temperature | 4 1 0 0 K |
| Lightsource | Т 9 |
| Dimensions | |
| Net weight (kg) | 0 |
| Arm length (in.) | 3 0 |
| Gross weight (lb.) | 5 0 |
| Termination | |
| Mounting | Table/desk base |
| Cord length (ft) | 6 |
| Ballast | |
| Type of Ballast | High frequency |