# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## кғм КFK025827

### KFM-2/AH 5D 3C Lg

KFM has a sturdy all-metal construction with a sleek design, flexible arm and excellent light output suitable for a variety of industrial, laboratory, cosmetology and low-vision application. The flexibility of the neck assembly and patented internal spring 30" K-arm makes exact **Outlitteng may: 1.72415L(2.**25X) optical-quality glass lens. Edge clamp mount. Color: light grey.



#### Optic

Color of reflector	White
Material of diffuser	Polycarbonate
Primary Lens (D)	5
Working distance (mm)	200
Material of reflector	PC
Magnification (X)	2.25

### Electrical data

Maximum frequency (Hz)	6 0
Minimum frequency (Hz)	5 0
Maximum voltage (V)	120
Voltage from (V)	100

#### Body

Body color	Grey
Body material	Aluminum
Technical data	

recimical data		
IP classification	2	0



Lightsource	
Number of lamps	1
Lamp power (W)	2 2
Lamp base	G 1 0 Q
CRI and/or Color Temperature	4 1 0 0 K
Lightsource	Т 9
Dimensions	
Net weight (kg)	4,34
Gross weight (lb.)	1 0
Arm length (in.)	3 0
Termination	
Cord length (ft)	6
Mounting	Edge clamp
Ballast	
Type of Ballast	High frequency