



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# KFM LED KFL026029



## 18215LG - KFM LED MAGNIFIER, 30" ARM, 5D LENS AND EDGE CLAMP

KFM LED produces nearly 75% greater light output than traditional KFM models. A heavy-duty, all-metal construction with sleek design, adjustable arm and excellent light output makes the KFM suitable for a wide range of industrial applications. No knobs to tighten, nothing to adjust. A flexible, self-balancing shade and fully-enclosed, hands-free



### Lightsource

|                              |               |
|------------------------------|---------------|
| Number of lamps              | 1             |
| Lamp power (W)               | 11            |
| Lightsource                  | LED           |
| CRI and/or Color Temperature | 80 CRI, 4000K |
| Lumen/Watt                   | 82            |
| Lumen Out                    | 900           |

### Optic

|                       |      |
|-----------------------|------|
| Primary Lens (D)      | 5    |
| Working distance (mm) | 200  |
| Magnification (X)     | 2.25 |

### Dimensions

|                  |      |
|------------------|------|
| Net weight (kg)  | 4,31 |
| Arm length (in.) | 30   |

### Electrical data

|                        |     |
|------------------------|-----|
| Maximum frequency (Hz) | 60  |
| Minimum frequency (Hz) | 50  |
| Maximum voltage (V)    | 120 |
| Voltage from (V)       | 100 |
| Total consumption (W)  | 11  |

### Technical data

|                                  |    |
|----------------------------------|----|
| Maximum ambient temperature (°C) | 25 |
| IP classification                | 20 |

### Body

|            |      |
|------------|------|
| Body color | Grey |
|------------|------|

### Termination

|          |            |
|----------|------------|
| Mounting | Edge clamp |
|----------|------------|