



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Cannon's ruggedized KPT/KPSE 26482 Series mini-circular connectors optimize performance, even in the harshest environments

Designed to meet stringent Mil-DTL-26482 Series I and VG95328 specifications for performance and intermateability, our robust KPT/KPSE connectors are engineered for durability and reliability, no matter the conditions.

KPT/KPSE connectors conform to MIL-C-26482 with a positive three point bayonet coupling, five-keyway polarization and high insert arrangement contact density. They are environmentally sealed, fully intermateable and accept a wide range of interchangeable accessories.



KPT | MIL-DTL-26482 Series I



KPSE | MIL-DTL-26482 Series I / VG95328

## The Cannon Difference

- A world leader in the design and manufacture of highly engineered connector solutions for multiple applications end markets
- More than a century of connector innovation and expertise
- RoHS compliant plating solutions that contribute to a more sustainable world

## Key Features

- Positive three point bayonet coupling rated at 500 mating cycles
- Five-keyway polarization for precise alignment
- High insert arrangement contact density
- Full range of metric, PG and standard accessories
- Solder contact configurations provide 30 PSI sealing
- Available with crimp contact for quick field termination
- Durable lightweight aluminum alloy shells
- Integrated backshell accommodates a wide variety of harnessing options and field termination applications

## Key Applications



Ground Transportation



Military Aviation



In-Flight Entertainment




Industrial Equipment



**How to Order | Part Number Configurator**

<b>Max. Voltage</b>	<b>Max. Current</b>	<b>Operating Temp</b>	<b>Durability</b>
1500-2300 VAC rms Sea Level	3.0 - 23.0 Amps	-55 to +125 degrees C	500 mating cycles

**26482 Product Line Talking Dog**



Series Prefix	KPT/KPSE	MS
Designation/Shell Style	00 - Wall mounting receptacle	3110 - Wall mounting receptacle (KPT)
	01 - Cable connecting receptacle	3111 - Cable connecting receptacle (KPT)
	02 - Box mounting receptacle (Class E only)	3112 - Box mounting receptacle (class E only) (KPT)
	06 - Straight plug	3114 - Jam nut receptacle (KPT)
	07 - Jam nut receptacle	3116 - Straight plug (KPT)
	08 - 90° angle plug	3119 - Thru bulkhead receptacle, (Class E Only) (KPT)
	B - Thru bulkhead receptacle (KPT)	
		3120 - Wall mounting receptacle (KPSE)
		3121 - Cable connecting receptacle (KPSE)
		3122 - Box mounting receptacle (KPSE)
	3124 - Jam nut receptacle (KPSE)	
	3126 - Straight plug (KPSE)	
Class	A - General duty (not MS approved)	A - General duty (not MS approved)
	B - General duty with strain relief (not MS approved) without grommet and ferrule	B - General duty with strain relief (not MS approved)
	E - With a grommet seal, not for 02 and 3112 (MS specification)	E - With a grommet seal, not for 02 and 3112 (MS specification)
	F - Grommet seal with strain relief (MS specification)	F - Grommet seal with strain relief (MS specification)
	J - Watertight gland seal with strain relief (MS specification) for jacketed cable (U.S. version)	J - Gland seal with strain relief for jacketed cable (U.S. version) (not MS approved)
	P - For potting (MS specification) (U.S. version)	P - For potting (MS specification) (U.S. version)
	PG - PG adapter (not available for shell #8)	
ME - Metric adapter (not available for shell #8)		
Shell Sizes	8, 10, 12, 14, 16, 18, 20, 22, 24	8, 10, 12, 14, 16, 18, 20, 22, 24
Contact Type	P - Pin	P - Pin
	S - Socket	S - Socket
Alternate Insert Position	W, X, Z (omit for normal)	W, X, Z (omit for normal)
Modification Code	A34 - Electroless nickel hardware, RoHS compliant (European version)	
	A71 - Electroless nickel hardware, RoHS compliant (U.S. version)	
	A206 - Black zinc cobalt hardware, RoHS compliant (U.S. version)	
	A232 - Black zinc cobalt hardware, RoHS compliant (European version)	
	A233 - Green zinc cobalt hardware (European version)	
	DN - Shrink boot adapter for shell styles 00, 01, 06 and 07 (Class E only)	
	A240 - Zinc Nickel Blue plating, RoHS Compliant (European version for all unshielded applications)	
	DZ - Endbell for shielding braids and shrink boots (Class E only)	
	07 - Clear chromate over cadmium hardware (U.S. version)	
	F42 - connectors without endbell and related parts	

Consult factory for other modifications. Omit first digit (0) of shell style indication when using a modification code.



## Why ITT

ITT is a focused, multi-industrial company that designs and manufactures highly engineered critical components and customized technology solutions.

ITT Interconnect Solutions' Cannon brand is a leading global manufacturer of connector products serving international customers in the aerospace and defense, medical, energy, transportation and industrial end markets. ITT's Interconnect Solutions business manufactures and supplies a variety of connectors and interconnects that make it possible to transfer data, signal and power in an increasingly connected world, including its VEAM and BIW Connector Systems brands.

Connect with your ITT Interconnect Solutions representative today or visit us at [www.ittcannon.com](http://www.ittcannon.com)

<b>North America</b> 56 Technology Drive Irvine, CA 92618 tel: 1.800.854.3028	<b>Europe</b> Jays Close, Viabes Estate, Basingstoke Hampshire, RG22 4BA, United Kingdom tel: +44.1256.311200	<b>Asia</b> 11-3, 5-Chome, Hibarigaoka, Zama-shi, Kanagawa, 228-0003, Japan tel: +81.462.57.2010
--	---	---