



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



TITLE	Number	Rev.	Page
KRS25F-xx series specifications	PRELIMINARY	0.1	1/5

Model number, Output ratings and Efficiency

MODEL No.	Output Voltage (VDC)	Output Current (A)		Efficiency at 100% Load (Typical)	
		100VAC	230VAC	100VAC	230VAC
KRS25F-03	3.3	6	6	69	69
KRS25F-05	5	5	5	74	74
KRS25F-12	12	2.1	2.1	80	80
KRS25F-15	15	1.7	1.7	80	80
KRS25F-24	24	1.1	1.1	80	80

Input specification

Input rating	100 – 230VAC (85 ~ 264VAC) 50 – 60Hz (47 ~ 63Hz) 3.3V output : 0.47 – 0.26A typical (at nominal output) Other outputs: 0.55 – 0.3A typical (at nominal output)
In-rush current	17 / 41 A typical (at 100/230VAC input)
Leakage current	0.5 / 0.75mA maximum (at 100/230VAC 63Hz input)

Output specifications

Voltage adjustment range $\pm 10\%$

Output voltage accuracy $\pm 5\%$

Input/Output regulation

MODEL No.	Input regulation (mVmax) (85-132/170-264VAC)	Load regulation (mVmax) (0~100% load)	Ripple and Noise (DC – 20MHz) (100% load)			
			100V _{in}		230V _{in}	
			*1	*2	*1	*2
KRS25F-03	16.5	100	200	250	150	150
KRS25F-05	25	100	200	250	150	150
KRS25F-12	60	100	250	250	100	100
KRS25F-15	75	100	350	350	100	100
KRS25F-24	120	100	400	450	100	150

*1:There is a capacitor on the output pin edge

*2:There is no capacitor on the output pin edge.

0.1	11-Jun-04	The part highlighted in red change			
REV	DATE	COMMENT	DRW	CHK	APP
		KAGA COMPONENTS CO., LTD.	Drawn	Checked	Approved
		Niigata factory	Engineering		
			DATE		
			14-May-04	komachi	sugimoto
				koike	

TITLE	Number	Rev.	Page
KRS25F-xx series specifications	PRELIMINARY	0.1	2/5

Tempertaure coeffecient	0.02%/°C maximum
Drift	(0.5%+15mV)maximum / 8H(after 1H warm-up)
Rise-up Time	300 mS maximum (at 100/230VAC input)
Hold-up Time	9 / 90 mS typical (at 100/230VAC input with nomial output)

Protection specifications

Over Voltage Protection	N/A
Over Current Protection	over 105%, Automatic recovery Avoid sustained operation in over load condition.
Thermal Shutdown	Power supply, and recycle on. The power supply will resume normal operation.


Isolation specifications

Isolation Resistance	Pri.-Sec	100MΩ MIN.	(500VDC)
	Pri.-Fg	100MΩ MIN.	(500VDC)
	Sec-Fg	100MΩ MIN.	(500VDC)
Isolation Voltage	Pri.-Sec	3000VAC / 1min	(10mA)
	Pri.-Fg	2000VAC / 1min	(10mA)
	Sec-Fg	500VAC / 1min	(10mA)

Environmental specifications

Operating Temp.	0 ~ +70 °C	(see derating curve Fig. 1)
Storage Temp.	-20 ~ +85°C	
Humidity	20 ~ 85%RH (No condensing)	

Fig.1 Derating curve (Load vs Ambient Temp.)



Note) 3.3V and 5V outputs are the input voltages of 100V or less and output current Dirating of 1%/V is necessary.

KAGA COMPONENTS CO., LTD.


Niigata factory

KGCOMP

TITLE	Number	Rev.	Page
KRS25F-xx series specifications	PRELIMINARY	0.1	3/5
<p>Application standard</p> <p>Safety: UL60950 CSA C22.2 No.60950 (cUL) CE (EN60950 A3 LVD) CB (IEC60950:1999,US/6301/UL)</p> <p>EMI: FCC Part 15 Class B meet EN55022 Class B meet VCCI(Ⅱ) meet</p> <p>Shock & Vibration</p> <p>Vibration: 10 ~ 55Hz 0.5mm width/1minute cycle 3 directions each 30 minutes</p> <p>Shock: 20G (3 directions each 3 times)</p> <p>CONDITION</p> <p>(Single)</p> <div data-bbox="485 1122 1358 1330" data-label="Diagram"> </div> <p>Vr : Measure point of line/load regulation and output voltage. Vn : Measure point of ripple and noise. (Bayonet tip probe used) C: 0.1μF film capacitor and 47μF electrolytic capacitor.</p> <p>Externals size 41 * 85 * 27.4mm</p> <p>Weight 100g (typ)</p> <p>Switching Frequency 100KHz(typ)</p>			
KAGA COMPONENTS CO., LTD. Niigata factory		KGCOMP	

TITLE	Number	Rev.	Page
KRS25F-xx series specifications	PRELIMINARY	0.1	4/5

Explanation of model name



Amends

After it delivers it, I will repair three years free of charge for an emergency breakdown. However, because handling is careless, it becomes for a fee.

Soldering condition

Dip: 240°C-255°C (within five seconds)

Hand solder: 350°C±10°C (within three seconds)

Others

This series is designed in our standard power supply for the general electronic equipment building in. Please do not use it for the equipment (medical equipment, aircraft, and nuclear power control system, etc.) by which the malfunction and the breakdown of the power supply threaten the human body and the life directly.

Directions

- ☆ The short-circuit leaving for a long time doesn't cause the breakdown and do not do, please.
- ☆ Please note that there is a case to cause a defective start when a mass capacitor (about 10,000μF) is connected with the load edge.
- ☆ The input fuse prevents secondary destruction due to the breakdown of the power supply, and it doesn't operate normally in the exchange only of the fuse. Please request the repair to the agency or our company when the input fuse fuses.

KAGA COMPONENTS CO., LTD.


Niigata factory

KGCOMP


TITLE	Number	Rev.	Page
Application standard	PRELIMINARY	0.1	5/5

Directions

- ☆ Please arrange it to separate the pattern from this power supply so that the voltage of the noise terminal might become large if it arranges it so that the pattern of the AC input line may pass under this power-supply unit. Moreover, please arrange it to separate the pattern from this power supply so that the output noise might become large if it arranges it so that the pattern of the DC output may pass under this power-supply unit.



- ☆ Please secure 5mm or more from the power supply when you arrange the pattern and parts (The chassis is included) that become different potential around the power supply. Please insert the insulating paper between those when becoming less than 5mm.



- ☆ It is likely to make an internal connection disconnected when the stress more than the necessity is added to the I/O pin of the power supply. Please adjust the stress to 2kgf or less by horizontal direction by 1kgf or less in the vertical direction as shown in the figure below.

