



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





LUXEON 2835 Line

Perfected performance, built on a proven legacy



LUXEON 2835 Line is a collection of compact devices which allows for design freedom and provides a superior overall system solution when a project requires high lumen output and good efficacy. With an industry standard footprint, the LUXEON 2835 Line is the perfect upgrade for other 2835 products and other common mid power offerings. The LUXEON 2835 Line is color targeted for application needs and delivers efficacy and reliability for a variety of applications. It is available in two product offerings, LUXEON 2835C for higher output and LUXEON 2835E for lower output ranges.

FEATURES AND BENEFITS

- 4 different configurations of voltage and die count to meet a wide range of application requirements
- Industry standard footprint for drop-in replacement designs
- Maximum drive current of up to 240mA allows for reduction of LED count
- Hot-color targeting and 1/9th micro-color binning enables tight color control
- 3-, 4- and 5-step MacAdam ellipse color kits available

PRIMARY APPLICATIONS

- Downlights
- Indoor Area Lighting
 - TLEDs
 - Troffers
- Lamps

LUXEON 2835 Line product performance at specified test current and temperature.

PRODUCT	VOLTAGE	NOMINAL CCT ^[1]	MINIMUM CRI ^[2, 3]	LUMINOUS FLUX ^[2, 3] (lm)		TYPICAL LUMINOUS EFFICACY (lm/W)	TEST CURRENT (mA)	PART NUMBER	
				MINIMUM	TYPICAL				
LUXEON 2835E	9V	2700K	80	67	75	137	60	L128-2780EC3500001	
		3000K	80	70	78	142	60	L128-3080EC3500001	
		3500K	80	72	80	147	60	L128-3580EC3500001	
		4000K	80	74	82	150	60	L128-4080EC3500001	
		5000K	80	74	82	150	60	L128-5080EC3500001	
		5700K	80	74	82	150	60	L128-5780EC3500001	
		6500K	80	74	82	150	60	L128-6580EC3500001	
		2700K	90	54	62	114	60	L128-2790EC3500001	
		3000K	90	57	65	119	60	L128-3090EC3500001	
	3500K	90	60	68	124	60	L128-3590EC3500001		
	4000K	90	62	70	128	60	L128-4090EC3500001		
	5000K	90	62	70	128	60	L128-5090EC3500001		
	6V	2700K	80	43	48	129	60	L128-2780EB3500001	
		3000K	80	44	49	132	60	L128-3080EB3500001	
		3500K	80	46	50	134	60	L128-3580EB3500001	
		4000K	80	47	52	140	60	L128-4080EB3500001	
		5000K	80	47	52	140	60	L128-5080EB3500001	
		5700K	80	47	52	140	60	L128-5780EB3500001	
	LUXEON 2835C	6V	2700K	80	93	105	141	120	L128-2780CB3500001
			3000K	80	96	108	145	120	L128-3080CB3500001
			3500K	80	99	111	149	120	L128-3580CB3500001
4000K			80	103	115	155	120	L128-4080CB3500001	
5000K			80	103	115	155	120	L128-5080CB3500001	
5700K			80	103	115	155	120	L128-5780CB3500001	
3V		2700K	80	51	56	154	120	L128-2780CA3500001	
		3000K	80	53	58	160	120	L128-3080CA3500001	
		3500K	80	54	59	164	120	L128-3580CA3500001	
		4000K	80	56	60	168	120	L128-4080CA3500001	
		5000K	80	56	60	168	120	L128-5080CA3500001	
		5700K	80	56	60	168	120	L128-5780CA3500001	
3V TVS	2700K	80	48	54	149	120	L128-2780CA35000T1		
	3000K	80	50	56	154	120	L128-3080CA35000T1		
	3500K	80	52	57	158	120	L128-3580CA35000T1		
	4000K	80	54	58	163	120	L128-4080CA35000T1		
	5000K	80	54	58	163	120	L128-5080CA35000T1		
	5700K	80	54	58	163	120	L128-5780CA35000T1		
		6500K	80	54	58	163	L128-6580CA35000T1		

Notes:

1. Correlated color temperature is cold-targeted at T_c=25°C for LUXEON 2835C 3V & LUXEON 2835C 3V TVS products and hot-targeted at T_c=85°C for everything else.
2. Luminous flux and CRI specs are based upon mounted package on highly reflective surface at T_c=25°C. Typical CRI is approximately 2 points higher than the minimum CRI specified, but this is not guaranteed.
3. Lumileds maintains a tolerance of ±2 on CRI and ±7.5% on luminous flux measurements.

©2016 Lumileds Holding B.V. All rights reserved.
LUXEON is a registered trademark of the Lumileds Holding B.V. in the United States and other countries.

lumileds.com

Lumileds Holding B.V. shall not be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding B.V. has attempted to provide the most accurate information and data, the materials and services information and data are provided "as is" and Lumileds Holding B.V. neither warranties, nor guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. reserves the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data.