

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

					BARREL									
PANDUIT PART NUMBER	CONDUCTOR SIZE	STUD SIZE	OVERALL LENGTH "A" +/12	BARREL LENGTH "B" MIN	I.D. +/01	O.D. +/01	TONGUE WIDTH "W" +/06	TONGUE THICKNESS "T" +/02	TONGUE LENGTH "P" MIN	HOLE OFFSET "G" +/03	STUD HOLE DIA "D" +/02	WRENCH CLEARANCE "C" REF	WIRE STRIP LENGTH	PANDUIT DIE COLOR CODE PANDUIT DIE INDEX NUMBER (BURNDY DIE INDEX NUMBER)
LAA6-14-X LAA6-56-X	#6 AWG	1/4" 5/16"	2.22	0.81	0.20	0.34	0.55	0.11	0.88	0.44	0.28 0.34	0.44	1"	GRAY DIE P29 (346)
LAA4-14-X		1/4"									0.28			GREEN DIE
LAA4-56-X	#4 AWG	5/16"	2.32	0.88	0.27	0.47	0.66	0.17	1.00	0.44	0.34	0.56	1-1/16"	P37 (375)
LAA4-38-X		3/8"									0.41			137 (373)
LAA2-14-X		1/4"					l				0.28			PINK DIE
LAA2-56-X	#2 AWG	5/16"	2.63	1.00	0.31	0.53	0.79	0.17	1.12	0.44	0.34	0.68	1"	P42 (348)
LAA2-38-X LAA1-14-X		3/8" 1/4"									0.41			
LAA1-14-X LAA1-56-X	#1 AWG	5/16"	2.63	1.00	0.35	0.53	0.75	0.17	1.12	0.44	0.28	0.68	1"	GOLD DIE
LAA1-38-X	#IAWG	3/8"	· I I	1.00	0.55	0.55	0.75	0.17	1.12	0.44	0.41	0.00	_	P45 (471)
LAA1/0-56-X		5/16"									0.34			
LAA1/0-38-X	#1/0 AWG	3/8"	3.22	1.25	0.39	0.64	0.88	0.25	1.25	0.63	0.41	0.62	1-9/16"	TAN DIE
LAA1/0-12-X		1/2"									0.53			P50 (296)

BANDUIT LAA1/0 C STR AL9CU TAN DIE P50(296) O.D. O.D.

NOTES:

- 1. MATERIAL: SEAMLESS ALUMINUM TUBING, TIN PLATED
- 2. BARREL COLOR CODED WITH DIE SET INDEX NUMBER
- 3. FOR STRANDED ALUMINUM AND COPPER WIRE
- 4. UL LISTED & CSA CERTIFIED TEMPERATURE RATED 90°C (AL9CU)
- 5. UL LISTED & CSA CERTIFIED VOLTAGE RATING 35 KV
- 6. ALL DIMENSIONS IN INCHES



DATE

9/96

TSMA



T	B (INTERNAL) I.D. BEVELED WIRE ENTRY
	OXIDE INHIBITOR JOINT COMPOUND

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN
02	3/13	JHNU	JHNU	RGB	REVISED TITLE BLOCK CONVERTED TO SOLIDWOKRS	N41203BA-C41203	-
03	10/14	JHNU	JHNU	RGB	REVISED I.D. FOR LAA1: .35 WAS .31	N41203BA-C41203	(.
04	3/15	JHNU	JHNU	RGB	REVISED DIMENSIONS REVISED NOTES ADDED BARREL MARKING ADDED COLOR CODE/DIE INDEX NUMBER	N41203BA-C41203	DIM
05	8/15	JHNU	JHNU	RGB	ADDED "D" DIMENSION	N41203BA-C41203	DATAS
06	12/15	JHNU	JHNU	RGB	REVISED A DIM FOR LAA6: 2.22 WAS 2.19 REVISED A DIM FOR LAA4: 2.32 WAS 2.22 REVISED A DIM FOR LAA1: 2.63 WAS 2.56 REVISED A DIM FOR LAA1/0: 3.22 WAS 3.23	N41203BA-C41203	ITEM R
							TITLE

LAA SERIES #6-1/0 ALUMINUM LUGS CUSTOMER DRAWING

WAREVISION NAME

N41203BA-C41203/06

TASET FILE NAME

C41203/06.SLDDRW

UNLESS OTHERWISE SPECIFIED,
IMENSIONAL TOLERANCES ARE: IN [mm]

.X ± .XXX ±

.XX ± ANGLES ±

THIRD ANGLE

NONE

PROJECTION

SCALE

C41203

SHEET 1 OF 1

SIZE
B