



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





LABC7-6V Charger

6V Lead-Acid Battery Smart Charger

INPUT SPECIFICATIONS

All specifications are typical at nominal input, full load.

INPUT SPECIFICATIONS

Input Voltage	AC 100 – 264VAC
Input Frequency	50 – 60Hz
Protection	Reverse Polarity, short circuit
Battery Sizes	6V volt SLA, VRLA, Gel, AGM or flooded



OUTPUT SPECIFICATIONS 6V /12V

Charge Voltage Limited	7.4V
Float Charge Voltage	6.8V
Charging Current	1.2 amp
Battery Types	All types 6V lead acid batteries

Charging Algorithm Auto 3 Stages

Constant Current	Stage 1 Constant current 1.2 amp
Constant Voltage	Stage 2 Constant voltage 7.4V
Floating	Stage 3 Float charge 6.8V

LED Indications	Pwr on, no battery connected –Green Charging – Red Charged - Flashing Green Charge/Float charging – Green Dim Reverse polarity – Red and Green flashing
-----------------	---

GENERAL SPECIFICATIONS

MTBF(Calculated)	30,000 Calculated hours at 25°C by MIL-HDBK-217F
Hi pot, ESD	3,000V, 1 minute ESD 8000V

FEATURES

- UNIVERSAL INPUT (AC100-240V)
- CONSTANT CURRENT/VOLTAGE,
- REVERSE POLARITY INDICATOR
- SHORT CIRCUIT PROTECTION
- 3 STAGE AUTO CHARGING

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-10°C~+40°C
Storage Temperature	-40°C ~ +70°C
Cooling.	Convection
Operating Humidity	20 – 80% Rh
Storage Humidity	10 – 90% Rh

MECHANICAL SPECIFICATIONS

Case Dimension	L81 x W51 x H28(mm)
Input Configuration	Fixed cord 2 pin USA
Output Connector	5.5 x 2.1 x 11.0 mm C+
Weight	150 grams



LABC7-6V Charger

Mechanical Drawing:

