



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



building a smarter, unified business foundation

UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN FOLLOW US



SOLUTIONS PRODUCTS AND SERVICES SUPPORT ABOUT US

Search Panduit.com Submi



Search within category

BUY NOW

DESIGN / INSTALL



LAM3B2-14-6Y

Two-hole, aluminum, three barrel lug, type LAM3B, NEMA hole sizes and spacing, #14 - #2 AWG, 1/4" (6.4mm) stud hole.
 LAM3B2-14-6Y replaces LAM3B2-14-6

Specs

★ Add to Favorites

🛒 Add to BOM

RoHS Compliancy Status	Compliant
Note	LAM3B2-14-6Y replaces LAM3B2-14-6
Product Type	Mechanical Connectors - Lugs
Material	Tin-Plated Aluminum
Height (mm)	11.9
Height (In.)	0.47
Length (mm)	63.2
Length (In.)	2.49
Stud Hole Size (In.)	1/4
Stud Hole Spacing (In.)	0.87
Tongue Width (In.)	1.63
Tongue Length	2.03
Aluminum or Copper Conductor Size Range	#14 AWG - #2 AWG
Figure No.	1
Tongue Thickness	0.19
CE Compliant	No
Tongue Length (mm)	51.6
Hex Key Size (In.)	**
Conductor Size Range (mm²)	2.5 - 35
Tightening Torque (In-Lbs)	50*
Tongue Type	Straight
Min. Order Qty.	1.0000